C: N		Description	Hait	Rate	e (Rs.)	Ref. Tech.
Sr. No	o.	Description	Unit	Labour	Composite	Specs.
23-1		Providing and fixing European type glazed earthenware water closet ICL Boch/Forte or approved equivalent make including cost of inlet pipe, lid cistern kit, stop cock deluxe and other accessories, fitting material such as brackets, PVC down pipe where required, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.				232.5.4 (a)
	a) i)	Water closet floride coupled/4030 White	Each	839.95	8,385.45	
	ii)	W.C. fregate coupled/4006	Each	839.95	8,147.15	
	b) i)	W.C. fregate coupled/4006  White	Each	839.95	6,548.95	
	,					
	ii)	Coloured	Each	839.95	7,457.85	
		W.C. non-coupled 7HU	Foob	930 OF	6 414 75	
	i)	White	Each	839.95	6,414.75	
	ii)	Coloured	Each	839.95	6,853.95	
23-2		Providing and fixing squatting type water closet with integral treads ICL Boch/Karam Cera or approved equivalent make including cost of inlet pipe cistern and lid cistern kit, stop cock deluxe type and other accessories, fittings, brackets, PVC down pipe, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.				23.2.5.4
	a)	W.C. Indian/Desi/902 with glazed earthen ware 4" (100 mm) trap				
	i)	White	Each	790.55	5,694.35	
	ii)	Coloured	Each	790.55	5,777.65	
		W.C. Orisa/Asian/900 with glazed earthen ware 4" (100 mm) trap				
	i)	White	Each	790.55	5,444.60	
	ii)	Coloured	Each	790.55	6,540.15	
23-3		Providing and fixing European type glazed earthenware water closet ICL Ifo/Forte or approved equivalent make including cost of inlet pipe, lid cistern kit, stop cock deluxe and other accessories, fitting material such as brackets, PVC down pipe where required, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.				23.2.5.4
	i)	White	Each	790.55	7,756.90	
	ii)	Coloured	Each	790.55	8,025.25	
23-4		Providing and fixing export quality ICL Boch/Karam Cera or equivalent make flat back lipped front urinal basin or glazed earthen ware with and including the cost of 1 gallon (4.5 lit) C.I automatic flushing cistern with fittings a pet cock C.I. or W.I. brackets standard flush pipe with fittings, standard waste pipe (enamelled iron) connection and making good with approved material.				23.2.5.7
	a)	Urinal 6003				
	i)	White	Each	592.90	6,518.45	
	ii)	Coloured	Each	592.90	6,640.45	
	b)	Urinal 6001				
	i)	White	Each	592.90	6,396.45	
	ii)	Coloured	Each	592.90	6,396.45	

		Poserintian Linit Rate (Rs.)		e (Rs.)	Ref. Tech.	
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
23-5		Providing and fixing export quality glazed earthen ware wash basin				23.2.5.1
		manufactured by ICL Boch/Karam Cera or equivalent approved make with single hole chromium plated mixer tap 1/2" (15mm), pillar tap one way delux, stop cocks, C.I. or W.I. brackets 6" (150mm) built into walls 1.5" (40mm) C.P. brass waste with malleable fron or C.P. brass trap with				
		malleable iron or brass union and making requisite number of holes in walls, plinth and floor for pipe connections and making good with approved material.				
	a) i)	Wash basin 18" (450 mm) without pedestal  White	Each	592.90	11,055.05	
	ii)	Coloured	Each	592.90	11,274.60	
	b)	Wash basin 24" (610 mm) Futura without pedestal				
	i)	White	Each	592.90	11,787.00	
	ii)	Coloured	Each	592.90	11,909.00	
	c)	Wash basin 26" (650 mm) without pedestal				
	i)	White	Each	592.90	12,153.00	
	ii)	Coloured	Each	592.90	12,031.00	
	d)	Extra over above for providing and fixing white glazed earthen ware pedestal manufactured by ICL/Karam Cera or approved equivalent make.				
	i)	White	Each	123.55	413.95	
	ii)	Coloured	Each	123.55	451.70	
23-6		Providing and fixing English or approved equivalent bath tub of desired colour with and including the cost of 1.5" dia. C.P. brass waste, 1.25" dia. brass overflow, (3/4") size C.P. brass pillar taps, C.P. brass chain with rubber plug and making required number of holes in walls plinth and floor for pipe connections and making good with approved material.				23.2.5.9
	a)	Porcelain enamelled cast iron bath tub 66" x 28" x 23" size	Each	1,976.40	29,469.70	
	b)	Fibre glass bath tub 72" x 28" x 23"	Each	1,976.40	25,809.70	
23-7		Providing and fixing ICL /Karam cera or approved equivalent make glazed earthen ware shower tray including fittings, bib cok, stop cock, shower kit, trap and making requisite numbers of holes and making good with approved material.	Each	790.55	5,041.35	
23-8		Providing and fixing stainless steel sink Pakistan made with C.I. or W.I brackets 6" built in wall, 1.5" (40 mm) rubber plug,C.P. brass chain, C.P. brass waste, pillar tap 2 way delux, 1.5" dia malleable iron or C.P. brass trap and unions and making requisite number of holes in walls, plinth and floor for pipe connections and making good with approved material.				23.2.5.3
	a)	Stainless steel sink 40" x 20" (1000 mm x 500 mm)	Each	790.55	5,823.05	
	b)	Stainless steel sink 33" x 18" (825 mm x 450 mm)	Each	790.55	5,335.05	
23-9		Providing and fixing floor trap of approved self cleaning design with screwed down grating with or without a vent arm with and including making requisite number of holes in walls, plinth and floor for pipe connection and making good with				23.2.4.1
	a)	C.I. floor trap 6" x 2" and 6" x 3" size with grating.	Each	197.65	1,417.65	
	b)	C.I. floor trap 4" dia. inlet and outlet with C.I. grating.	Each	197.65	1,661.65	
	c)	C.I. floor trap 6" x 2" size with grating including concrete chamber all round	Each	197.65	1,717.65	
	d)	C.l. floor trap 6" x 4" size with grating including concrete chamber all	Each	197.65	2,021.65	

Sr. No.	Description	Unit	Rate	(Rs.)	Ref. Tech.
31. 140.	Description		Labour	Composite	Specs.
	round				



Sr. No	_	Description	Unit	Rate	e (Rs.)	Ref. Tech.	
31. NO	J.	Description	Onn	Labour	Composite	Specs.	
23-10		Providing and fixing white glazed earthen ware export quality bidet with fittings in bath room.	Each	592.90	16,404.10	23.2.5.5	
23-11		Providing and fixing standing shower concealed in wall with approved quality control valves, mixer unit and moveable shower head.	Each	790.55	12,502.55	23.2.5.8	
23-12		Providing and fixing C.P. brass telephonic shower including holder clamps, screw and bib cock.	Each	148.25	3,881.45	23.2.5.8	
23-13		Providing and fixing approved quality chromium plated lowel rail with bracket and screws.					
	a)	Towel rail 24" x 3/4" (600mm x 20mm)	Each	39.55	2,607.72		
	b)	Towel rail 30" x 3/4" (750mm x 20mm)	Each	39.55	4,213.50		
23-14		Providing and fixing approved quality C.P. brass toilet paper holder Master /Sonex or equivalent make.	Each	98.80	1,031.72	23.2.5.11	
23-15		Providing and fixing looking mirror of Belgium/ Malaysian/ Indonesian glass with chromium plated screws.	Sq.m. Sq.ft.	197.65 18.35	1,027.43 95.50	23.2.5.2	
23-16		Providing and fixing shelf of standard size.				23.2.5.13	
	a)	Glass shelf of 24" x 5" size with guard rails & C.P. brackets.	Each	49.40	3,099.40		
	b)	Shelf (Master/Sonex make)	Each	49.40	2,489.40		
23-17		Providing and fixing white glazed vitreous China squatting type W.C. pan with integral treads similar to Orissa type.				23.2.5.4	
	a)	Without trap	Each	395.30	2,341.20		
	b)	With vitreous China trap	Each	395.30	2,506.20		
23-18		Providing and fixing approved quality fixtures				23.2.5.4	
	a)	European type White glazed earthen ware W.C. pan.	Each	395.30	2,274.10	20.2.0.	
	b)	Providing and fixing plastic flushing cistern of approved quality and colour.	Each	395.30	1,847.10		
	c)	Wash basin 18" (450 mm), White colour	Each	395.30	2,027.65		
	d)	Wash basin 24" (610 mm) ICL Futura make	Each	395.30	2,759.65		
23-19		Providing and fixing ICL (Boch) or Karam Cera export quality glazed earthen ware cistern with lid and kit.				23.2.5.4	
	a)	White	Each	197.65	2,081.55		
	b)	Coloured	Each	197.65	2,389.05		
23-20		Providing and fixing approved qualty of Bacolite plastic seat with lid.	Each	49.40	559.35	23.2.5.4	
23-21		Providing and fixing glazed pottery/C.P. brass pull.	Each	49.40	171.40	23.2.5.1(d)	
23-22		Providing and fixing rubber connection for flush pipe with European W.C.	Each	49.40	167.05	23.2.5.4	
23-23		Providing and fixing approved quality white glazed earthenware lavatory basin with 1/2" (15 mm) dia. single hole C.P. mixer tap, 2 way deluxe pillar tap, stop cocks, 6" C.I. or W.I. brackets built into walls, rubber plug, C.P. brass chain, C.P. brass waste, malleable iron or C.P. brass bottle trap with malleable iron or brass union and making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.				23.2.5.1	
	a)	Lavatory basin 22" x 16" (550 mm x 400 mm)	Each	592.90	14,715.00		
	b)	Lavatory basin 25" x 18" (625 mm x 450 mm)	Each	592.90	16,667.00		

Sr. No	_	Deceription	Unit	Rate	Rate (Rs.)	
SI. NO	J.	Description	Unit	Labour	Composite	Specs.
23-24		Providing and fixing approved quality glazed fire clay sink 24" x 18" with 6" (150mm) size C.I. or W.I. brackets built in walls, 1.5" (40 mm) rubber plug and C.P. brass chain, C.P. brass waste, pillar tap 2 way deluxe, malleable iron or C.P. brass trap and unions and making requisite numbers of holes in walls, plinth and floor for pipe connections and making good with approved material.	Each	790.55	6,799.05	23.2.5.3
23-25		Providfing and fixing C.P. chain for sink and lavatory basin.	Each	39.55	100.55	23.2.5.1
23-26		Providing and fixing rubber plug for sink and lavatory basin.	Each	39.55	59.70	
23-27		Providing and fixing glazed earthen ware foot rest.	Each	98.80	263.50	
23-28		Providing and fixing C.P. bottle trap with union and waste pipe				23.5.2.4
	a)	1.25" (30 mm) dia.	Each	197.65	1,509.15	
	b)	1.5" (40 mm) dia.	Each	197.65	2,149.65	
23-29		Providing and fixing soap dish.				23.2.5.11
	a)	Chromium plated	Each	39.55	917.95	
	b)	Glazed earthen ware	Each	39.55	1,152.20	
23-30		Providing and fitting superior quality plastic accessories of approved make				23.2.5.11
	a)	Soap dish	Each	39.55	368.95	
	b)	Toilet paper holder	Each	39.55	344.55	
	c)	Towel rod	Each	39.55	283.55	
	d)	Shelf 24" x 5" with bracket and railing.	Each	39.55	234.75	
23-31		Providing and fixing C.P. pillar-cock of superior quality of approved make.				23.2.5.10
	a)	1/2" (12 mm) dia.	Each	39.55	1,051.55	
	b)	3/4" (20 mm) dia.	Each	39.55	1,194.04	
23-32		Providing and fixing C.P. stop-cock of superior quality of approved make.				23.2.5.10
	a)	1/2" (12 mm) dia.	Each	39.55	1,089.80	
	b)	3/4" (20 mm) dia.	Each	39.55	1,392.75	
23-33		Providing and fixing undergound stop-cock with superior quality C.P. cover of approved make.				23.2.5.10
	a)	1/2" (12 mm) dia.	Each	39.55	1,177.68	
	b)	3/4" (20 mm) dia.	Each	39.55	1,471.04	
23-34		Providing and fixing superior quality C.P. bib cock of approved make.				23.2.5.10
	a)	1/2" (12 mm) dia.	Each	39.55	1,166.72	
	b)	3/4" (20 mm) dia.	Each	39.55	1,309.59	

C., N		Description	l lmit	Rate	e (Rs.)	Ref. Tech.
Sr. N	0.	Description	Unit	Labour	Composite	Specs.
23-35		Providing and fixing superior quality 1/2" size C.P. tee stop cock of approved make.	Each	39.55	525.32	23.2.6.3
23-36	a)	Providing and fixing C.P. brass shower 1/2" (12 mm) dia inlet and 6" (150 mm) dia. detachable fid	Each	39.55	765.78	23.2.5.8
	b)	1/2" (12 mm) dia inlet and 4" (100 mm) dia. detachable lid	Each	39.55	625.24	
23-37		Providing and fixing 1/2" (12 mm) single hole superior quality C.P. mixer of approved make for wash hand basin, sink or shower.  Providing and fixing 1" (25 mm) superior guality C.P. flushing valve of	Each	197.65	3,857.65	23.2.5.1(e)
23-38		Providing and fixing 1" (25 mm) superior quality C.P. flushing valve of approved make for wash hand basin, sink or shower.	Each	197.65	4,010.15	23.3.4.2
23-39		Providing and fixing superior quality gun-metal peet/gate valve (Class150) of approved make.				27.3.1.2
	,	Screwed ends				
	i)	1/2" (12 mm) dia.	Each	68.14	239.10	
	ii)	3/4" (20 mm) dia.	Each	68.14	275.55	
	iii)	1" (25 mm) dia.	Each	148.25	441.05	
	iv)	1.25" (30 mm) dia.	Each	148.25	388.31	
	v)	1.5" (40 mm) dia.	Each	136.31	464.03	
	vi)	2" (50 mm) dia.	Each	136.31	657.72	
	vii)	2.5" (65 mm) dia.	Each	477.07	1,381.55	
	viii	3" (75 mm) dia.	Each	477.07	1,675.21	
	ix)	4" (100 mm) dia.	Each	681.52	2,280.14	
	x)	6" (150 mm) dia.	Each	681.52	2,405.17	
	b)	Flanged ends				
	i)	1/2" (12 mm) dia.	Each	204.45	436.75	
	ii)	3/4" (20 mm) dia.	Each	204.45	409.40	
	iii)	1" (25 mm) dia.	Each	408.90	885.70	
	iv)	1.25" (30 mm) dia.	Each	408.90	823.70	
	v)	1.5" (40 mm) dia.	Each	263.52	1,370.05	
	vi)	2" (50 mm) dia.	Each	263.52	1,080.90	
	vii)	2.5" (65 mm) dia.	Each	702.71	5,785.20	
	viii	3" (75 mm) dia.	Each	702.71	5,309.40	
	ix)	4" (100 mm) dia.	Each	527.04	9,318.40	
	x)	6" (150 mm) dia.	Each	527.04	3,473.35	

Sr. No		Description	Unit	Rate	e (Rs.)	Ref. Tech.	
31. 140	,.	. Description	Ollit	Labour	Composite	Specs.	
23-40		Providing and fitting superior quality C.P. or brass oxidised 1/2" (12mm) swan neck pillar cock (tap) of approved make.				23.2.5.10	
	a)	Single way	Each	68.14	2,107.25	23.2.5.3 (e)	
23-41	b)	Double way  Providing and fixing brass bib cock/ stop cock of approved make.	Each	148.25	2,477.85		
25-41	a)	1/2" (12 mm) dia.	Each	49.40	171.40	23.2.5.10	
	b)	3/4" (20 mm) dia.	Each	49.40	195.80		
	c)	1" (25 mm) dia.	Each	49.40	354.40		
23-42		Providing and fixing 'P' trap including concrete chamber and C.I. grating.				23.2.5.4	
	a)	Cast iron 4" (100 mm) size	Each	197.65	2,103.90		
	b)	Glazed 4" (100 mm) size	Each	197.65	469.17		
23-43		Providing and fixing C.I. gully trap 6"x6"x4" including concrete embedment and cost of G.I. grating 6"x6" and masonry chamber 12"x12"	Each	49.40	1,725.70	23.2.4.2	
23-44		Providing, laying, cutting, jointing, testing and disinfecting cast iron soil pipe with spigot, socket chaulked lead or comet joint or flanged joints/fyton joints including cost of jointing material such as lead, comet and yarn.				23.2.3.1 23.2.6.4	
	a)	2" (50 mm) dia.	R.M. R.ft.	60.50 18.45	1,740.45 530.50		
	b)	3" (75 mm) dia.	R.M. R.ft.	60.50 18.45	2,580.40 786.50		
	c)	4" (100 mm) dia.	R.M. R.ft.	60.50 18.45	3,420.40 1,042.55		
23-45		Providing and laying Asbestos cement building and sanitary pipe with cement chaulked or comet joint including cost of sockets, bends and specials.				23.2.3.4	
	a)	2.5" (65 mm) inner dia.	R.M. R.ft.	152.20 46.40	537.95 163.95		
	b)	3" (75 mm) inner dia.	R.M. R.ft.	152.20 46.40	776.70 236.75		
	c)	4" (100 mm) inner dia.	R.M. R.ft.	304.40 92.80	1,161.80 354.10		
	d)	6" (150 mm) inner dia.	R.M.	304.40	1,650.85		

Sr. No		Deparintion	Unit	Rate	e (Rs.)	Ref. Tech.
SI. NO	<b>)</b> .	Description	Unit	Labour	Composite	Specs.
			R.ft.	92.80	503.20	
23-46		Providing and fixing C.I. specials such as bend, tees, collars, cross, reducers, tail pieces, flanged spigots, cap, flanged socket, taper, angle bends and plugs including turning threading, facing and fitting for C.I. pipe line.				23.2.3.1 23.2.6
	a)	Cast iron S.S. specials with spigot and socket joint				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	60.50 27.45	186.30 84.50	
	ii)	8" to 12" (200 mm to 300 mm) inner dia. ************************************	Kg. Lb.	45.40 20.60	171.20 77.65	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	30.25 13.70	156.05 70.80	
	b)	Cast iron flanged specials with flanged joints				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	30.25 13.70	156.05 70.80	
	ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg. Lb.	23.20 10.50	149.05 67.60	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	15.15 6.85	140.95 63.95	
	c)	Cast iron specials with tyton joints				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	15.15 6.85	163.85 74.30	
	ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg. Lb.	15.15 6.85	186.70 84.70	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	15.15 6.85	221.05 100.25	
23-47		Supplying and fitting C.I. manhole cover with frame weighing not less than 10.25 lbs/sq.ft (50 kg per sq.m.).				23.2.7,
	a)	12" (300 mm.) dia.	Each	541.56	1,390.30	25.4.2
	b)	18" (450 mm.) dia.	Each	541.56	1,480.75	
	c)	24" (600 mm.) dia.	Each	247.08	1,801.53	
	d)	12" (300 mm.) square	Each	668.58	1,938.07	
	e)	18" (450 mm.) square	Each	668.58	1,903.33	
	f)	24" (600 mm.) square	Each	668.58	2,415.59	
23-48		Providing and fitting C.P. or oxidised gas cock 1/4" (6 mm) dia.				23.3.5.1
	a)	Single way	Each	247.08	272.60	20.0.0.1
	b)	Double way	Each	247.08	411.52	
	c)	Three way	Each	247.08	704.43	

Sr. No	Description	Unit	Rate	e (Rs.)	Ref. Tech.
			Labour	Composite	Specs.
23-49	Providing and fitting nipple or bush 1/4" x 3/8" (6mm - 10mm) inner dia.	Each	39.55	76.15	23.3.5.1
23-50	Providing and fitting union/socket				23.3.5.1
	i) 1/2" (15 mm) inner dia.	Each	39.55	727.65	20.0.0.1
	ii) 3/4" (20 mm) inner dia.	Each	39.55	888.65	
	1" (25 mm) inner dia.	Each	39.55	1,093.65	
23-51	Providing and fixing brass gas cock.				23.3.5.1
	a) 1/2" (15 mm) inner dia.	Each	39.55	447.78	
	b) 3/4" (20 mm) inner dia.	Each	39.55	467.71	
23-52	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe with approved make/brand gas line including the cost of jointing material.				23.3.3
	a) Light duty				
	i) 1/2" (15 mm) inner dia.	R.M. R.ft.	81.50 24.85	291.40 88.80	
	ii) 3/4" (20 mm) inner dia.	R.M. R.ft.	81.50 24.85	385.95 117.65	
	1" (25 mm) inner dia.	R.M. R.ft.	93.50 28.50	522.75 159.35	
	iv) 1.25" (30 mm) inner dia.	R.M. R.ft.	93.50 28.50	658.90 200.85	
	v) 1.5" (40 mm) inner dia.	R.M. R.ft.	110.85 33.80	829.40 252.80	
	vi) 2" (50 mm) inner dia.	R.M. R.ft.	110.85 33.80	1,018.55 310.45	
23-53	Providing and fixing superior quality C.P. check valve of approved make for water supply or gas lines.				23.2.6.4 23.2.3
	a) 1/2" (12 mm) dia.	Each	49.40	2,001.40	
	b) 3/4" (20 mm) dia.	Each	49.40	2,611.40	
	c) 1" (25 mm) dia.	Each	68.14	2,996.15	
	d) 1.25" (30 mm) dia.	Each	148.25	4,418.25	
	e) 1.5" (40 mm) dia.	Each	197.65	5,809.65	
	f) 2" (50 mm) dia.	Each	304.40	8,844.40	
23-54	Providing and fixing C.P. waste coupling.				23.2.5.3(e)
	a) 1.25" (30 mm) dia.	Each	39.55	141.65	, ,
	b) 1.5" (40 mm) dia.	Each	39.55	198.22	
23-55	Providing and fixing C.P chain with rubber plug.				23.2.5.3(d)
	a) 1.25" (30 mm) dia.	Each	39.55	51.95	
	b) 1.5" (40 mm) dia.	Each	39.55	49.44	

Sr. No	<b>)</b> .	Description	Unit	Rate	e (Rs.)	Ref. Tech.
		2000 i piloti	O.I.I.	Labour	Composite	Specs.
23-56		Providing and fixing P.V.C. waste pipe				
25 50	a)	1.25" (30 mm) dia.	Each	39.55	215.09	23.2.5.3(f)
	b)	1.5" (40 mm) dia.	Each	39.55	132.79	
23-57	,	Providing and fixing P.V.C. waste flushing bend				23.3.6.3
	a)	1.25" (30 mm) dia.	Each	39.55	73.62	23.3.0.3
	b)	1.5" (40 mm) dia.	Each	39.55	102.79	
23-58		Providing and fixing angle iron brackets for wash hand basin, cistern and sinks.	Each	49.40	232.40	23.2.5.7 23.5.3
23-59		Providing and fixing 1/2" (12 mm) dia. connection pipe including check nuts.				23.2.6
	a)	Plastic rubber connection pipe	Each	39.55	127.50	
	b)	Copper connection pipe	Each	39.55	244.00	
23-60		Providing and fixing brass ball valve with unsoldered copper ball.				23.3.4.2
	a)	1/2" (12 mm) dia.	Each	49.40	140.30	
	b)	3/4" (20 mm) dia.	Each	49.40	195.20	
	c)	1" (25 mm) dia.	Each	68.14	237.90	
	d)	1.25" (30 mm) dia.	Each	148.25	396.50	
	e)	1.5" (40 mm) dia.	Each	197.65	518.50	
	f)	2" (50 mm) dia.	Each	304.40	915.00	
23-61		Providing chambers 9" x 6" x 24" for stop cocks and valves etc. with 4-1/2" (115mm) thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:4:8 in foundation, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, 1" thick concrete 1:2:4 flooring complete with C.I. hinged cover and frame 9" x 6" weighing 6.35 kg fixed in 1:2:4 concrete including curing, excavation, back filling and disposal of earth.	Each	394.60	2,348.25	23.3.14.2
23-62		Providing chambers 15" x 9" x 24" for house meters with 4-1/2" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:4:8 in foundation, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, 1" thick concrete 1:2:4 flooring complete with cast iron hinged cover and frame 15" x 9" weighing 12.7 kg fixed in 1:2:4 concrete including curing, excavation, back filling and disposal of earth.	Each	533.65	3,885.90	5.3 11.4.1 11.7.2(ii) 11.7.4
23-63	a)	Providing chambers 30" x 18" x 56" as per approved design for sluice valve 3" to 12" dia. with 18" dia. C.I. cover and frame weighing 88.9 Kg. fixed in 4" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing anf fixing C.I. foot rest at every 12" beyond 30" depth including curing, excavation, back filling and disposal of surplus earth.	Each	2,815.90	28,367.15	5.3 11.4.1 11.7.2(ii) 11.7.4
	b)	Extra for depth beyond 54" (1.37m) including cost of C.I.foot rest for every 12"(300mm) depth (for depth less than 54" (1.37m) deduct at the same rate).	Each	16.75	131.85	

Sr. No	`	Description	Unit	Rate (Rs.)		Ref. Tech.	
51.140	<i>J</i> .	Description	Oilit	Labour	Composite	Specs.	
23-64	a)	Providing chambers 42" x 42" x 7'-0" as per approved design for sluice valve 15" to 24" dia. with 24" dia. C.I. cover and frame weighing 127 Kg. fixed in 6" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing & fixing C.I foot rest at every 12" beyond 30" depth including curing, excavation, back filling and disposal of surplus earth.	Each	6,392.55	57,875.40	5.3 11.4.1 11.7.2(ii) 11.7.4	
	b)	Extra for depth beyond 7 ft.(2.14 m) including cost of C.I. foot rest for every 12" (300mm) depth (for depth less than 7 ft (2.14 m) deduct at the same rate).	Each	25.50	159.65		
23-65	a)	Providing chambers 45" x 42" x 8'-0" as per approved design for sluice valve 27" to 30" dia. with 30" dia. C.I. cover and frame weighing 190.5 Kg. fixed in 6" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing anf fixing C.I. foot rest at every 12" beyond 30" depth including curing, excavation, back filling and disposal of surplus earth.	Each	8,753.60	75,645.95	5.3 11.4.1 11.7.2(ii) 11.7.4	
	b)	Extra for depth beyond 8 ft (2.44 m) including cost of C.I. foot rest for every 12" (300mm) depth (for depth less than 8 ft (2.44 m) deduct at the same rate).	Each	26.25	164.25		
23-66		Supply and fix gas items including all accessories and fittings such as G.I pipe, rubber pipe, specials, gas stop cocks etc.				23.3	
	a)	Gyser 35 gallons capacity	Each	1,185.85	13,163.20		
	b)	Gyser 50 gallons capacity	Each	1,185.85	14,636.35		
	c)	Gas room heater (ordinary, single burner)	Each	790.55	1,495.10		
	d)	Gas room heater (ordinary, double burner)	Each	790.55	1,943.45		
	e)	Gas room heater (fancy, single burner)	Each	790.55	5,274.05		
	f)	Gas room heater (fancy, Double burner)	Each	790.55	7,836.05		
	g)	Gas room heater (fire place design with artificial log or coal, double burner)	Each	1,185.85	8,231.35		
	h)	Gas lamp (single)	Each	592.90	1,233.40		
	i)	Gas lamp (double)	Each	592.90	1,873.90		
23-67		Providing and connecting PVC/ Rubber pipe for gas connection	Per	52.45	209.25	23.3	
23-68	a)	Add extra for respective payable item of ground floor For first floor	Point % Increase	0.10	0.10	23.3	
	b)	For every additional floor above first floor	% Increase	0.08	0.08		