	<u>-</u>		Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure			2	11.7.2 (i) 11.17
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,012.65 57.00	8,916.21 252.50	
b) 11-2	Above 4.5" (115mm) nominal thick brickwork Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation	Cu.m. Cu.ft.	3,485.30 98.70	8,873.40 251.30	11.4.1 11.7.2(i)
	and substructure				11.7.4
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,575.90 44.65	9,538.95 270.15	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,168.60 33.10	8,573.10 242.80	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
					11.7.4
-	Upto 4.5" (115 mm) nominal thick brick work	0	4 575 00	44 440 05	
1)	Cement sand 1 : 2	Cu.m. Cu.ft.	1,575.90 44.65	11,112.65 314.70	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,575.90 44.65	10,642.91 301.40	
iii)	Cement sand 1:4	Cu.m.	1,575.90	10,192.35	
,		Cu.ft.	44.65	288.65	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	1,575.90 44.65	9,817.30 278.05	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,575.90 44.65	9,516.32 269.50	
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	1,575.90 44.65	9,224.93 261.25	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	1,575.90 44.65	8,936.28 253.10	
b)	Above 4.5" (115mm) nominal thick brickwork				
	Cement sand 1 : 2	Cu.m. Cu.ft.	1,168.60 33.10	10,839.50 307.00	

O N		Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No	о.	Description	Unit	Labour	Composite	Specs.
	ii)	Cement sand 1:3	Cu.m.	1,168.60	10,283.71	
			Cu.ft.	33.10	291.25	
			2000			
	iii)	Cement sand 1:4	Cu.m.	1,168.60	9,722.48	
			Cu.ft.	33.10	275.35	
		(*) [689]	200			
	iv)	Cement sand 1:5	Cu.m.	1,168.60	9,272.96	
			Cu.ft.	33.10	262.60	
	,	2	0			
	v)	Cement sand 1 : 6	Cu.m.	1,168.60	8,897.61	
		AMMU & KASH	Cu.ft.	33.10	252.00	
	VI)	Cement sand 1:7	Cu.m.	1,168.60	8,590.61	
			Cu.ft.	33.10	243.30	
	vii	Cement sand 1:8	Cu.m.	1,168.60	8,267.56	
		ocinicit sand 1.0	Cu.ft.	33.10	234.15	
			Ou.it.	33.10	204.10	
11-4		Extra for providing and laying first class burnt brick masonry				11.80
		for arches of any kind of wall including scaffolding, formwork				
		and its removal, raking out joints and curing in basement etc.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	842.53	2,770.10	
			Cu.ft.	22.90	71.55	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	808.68	2,525.93	
			Cu.ft.	23.85	78.45	
11-5		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork				11.80
		and its removal, raking out joints and curing in foundations,				11.90
		basement and plinth.				
	- 1	Linto Oli (220 mars) marsinal third: Usarasasasa	C	4 004 47	0.570.70	
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,231.17	2,579.79 73.05	
			Cu.ft.	34.85	73.05	
	h)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,163.28	2,308.24	
	IJ)	1 1200 1 (200 mm) nominal unor die masomy	Cu.ft.	32.95	65.35	
			Ju.it.	02.00	00.00	
11-6		Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	280.35	280.35	11.7.4
		foundation and basement masonry deeper than 6 ft (2 m)	Cu.ft.	7.95	7.95	
11-7		Extra for every additional 5 ft (1.5 m) or part thereof in plinth	Cu.m.	208.45	208.45	11.7.4
		higher than 5 ft (1.5m)	Cu.ft.	5.90	5.90	
11-8		Extra for every additional 6 ft (2m) or part thereof for arch	Cu.m.	280.35	322.40	11.80
		brick or tile masonry in foundation and basement masonry	Cu.ft.	7.95	9.15	11.90
		deeper than 6ft (2m)				

Cr. N	December Com.	1124	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-9	Extra for every additional 5 ft (1.5m) or part thereof for arch brick or tile masonry in plinth higher than 5ft (1.5m)	Cu.m. Cu.ft.	208.45 5.90	239.70 6.80	11.80 11.90
11-10	Providing and laying sundried clay bricks set in mud mortar including scaffolding in ground floor superstructure				11.7.2(i) 11.18
a	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,255.83 35.55	8,655.00 245.10	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,413.65 40.05	6,289.32 178.10	
11-11	Providing and laying first class solid burnt brick masonry set in mud mortar including scaffolding, raking out joints and curing in ground floor superstructure.				11.4.1 11.7.2(i) 11.7.4
a	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,962.25 55.55	10,511.59 297.70	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,453.22 41.15	7,417.55 210.05	
11-12	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure				11.4.1 11.7.2(ii)
a	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
	Cement sand 1 : 2	Cu.m. Cu.ft.	1,962.25 55.55	11,688.81 331.05	
ii	Cement sand 1 : 3	Cu.m. Cu.ft.	1,962.25 55.55	11,211.89 317.55	
iii	Cement sand 1 : 4	Cu.m. Cu.ft.	1,962.25 55.55	10,753.65 304.55	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,962.25 55.55	10,375.31 293.85	
V	Cement sand 1 : 6	Cu.m. Cu.ft.	1,962.25 55.55	10,086.46 285.65	
vi	Cement sand 1 : 7	Cu.m. Cu.ft.	1,962.25 55.55	9,794.52 277.40	
vi	Cement sand 1 : 8	Cu.m. Cu.ft.	1,962.25 55.55	9,507.85 269.25	

0:- N		D	11	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	,	Above 4.5" (115mm) nominal thick brickwork	_			
	i)	Cement sand 1 : 2	Cu.m.	1,554.95	11,348.25	
			Cu.ft.	44.05	321.40	
	ii۱	Cement sand 1 : 3	Cu.m.	1,554.95	10,787.28	
	")	Schicit sand 1.5	Cu.ft.	44.05	305.50	
		(-0-1			000.00	
	iii)	Cement sand 1:4	Cu.m.	1,554.95	10,219.57	
		M	Cu.ft.	44.05	289.40	
		Carrie Co.				
	iv)	Cement sand 1:5	Cu.m.	1,554.95	9,789.82	
		JAMMU & KASK	Cu.ft.	44.05	277.25	
	,,)	Cement sand 1 : 6	Cu.m.	1,554.95	9,405.75	
	٧)	Cernent Sand 1.0	Cu.ft.	44.05	266.40	
			0		2001.10	
	vi)	Cement sand 1:7	Cu.m.	1,554.95	9,106.93	
			Cu.ft.	44.05	257.90	
	Vii	Cement sand 1 : 8	Cu.m.	1,554.95	8,806.85	
			Cu.ft.	44.05	249.40	
11-13		Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80
	-١	Links 4.5" (445 may) is a spiral think haid, buildings	C	40.00	0.000.00	
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	48.60 1.40	2,083.26 59.00	
			Ou.it.	1.40	33.00	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	252.25	2,036.47	
			Cu.ft.	7.15	57.65	
11-14		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80 11.90
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	3,510.80	4,382.38	
	,		Cu.ft.	99.45	103.95	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	3,103.50	3,671.05	
			Cu.ft.	87.90	124.10	
11-15		Extra for masonry in pillars and columns in foundation				11.18
	رد	Rectangular or square shape	Cu.m.	1,075.85	1,463.95	
	a)	incotangular of Square Shape	Cu.m.	30.45	41.45	
				33.40	11.40	

				Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
				Luboui	Composito	
	b)	Round shape	Cu.m.	2,387.65	2,864.00	
	-,		Cu.ft.	67.60	81.10	
			•	01.00	00	
11-16		Extra for masonry in pillars and cloumns in ground floor				11.7.4
		superstructure				
	a)	Rectangular or square shape	Cu.m.	1,149.17	2,178.75	
	۵,	A Distriction of Order of the Control of the Contro	Cu.ft.	32.55	61.70	
		(Na	(m.m/1940)	02.00	00	
	b)	Round shape	Cu.m.	2,223.67	4,050.92	
	٠,	Z S	Cu.ft.	63.00	114.70	
		PO JAMMU & KASHM		00.00		
11-17		Extra for masonry of any description in steps.	Cu.m.	689.32	689.32	11.17.4
,		Extra for massing or any assembles in steps.	Cu.ft.	19.50	19.50	11.17.4
			Ou.it.	13.50	13.30	
11-18		Extra for masonry of any description for bonding old and new	Cu.m.	317.10	454.55	11.11
11 10		masonry including making recesses as required (New	Cu.ft.	9.00	12.85	11.11
		masonry inserted in old masonry to be measured)	Ou.it.	3.00	12.00	
11-19		Providing and laying first class burnt brick honey comb				11.10
11 13		masonry including scaffolding, raking out joints where				11.10
		required and curing in ground floor superstructure (opening				
		not to be deducted for the purpose of measurement).				
	a)	Upto 4.5" (115 mm) nominal thick brick work				
		Cement sand 1 : 2	Cu.m.	1,230.05	8,913.85	
	.,	0011011100111011101	Cu.ft.	34.85	252.45	
			•	000	202.10	
	ii)	Cement sand 1:3	Cu.m.	1,230.05	8,750.50	
	,		Cu.ft.	34.85	247.80	
	iii)	Cement sand 1:4	Cu.m.	1,230.05	8,586.05	
	,		Cu.ft.	34.85	243.15	
	iv)	Cement sand 1 : 5	Cu.m.	1,230.05	8,490.10	
	٠٠,		Cu.ft.	34.85	240.45	
	۷V	Cement sand 1:6	Cu.m.	1,230.05	8,421.60	
	•,		Cu.ft.	34.85	238.50	
	۷i)	Cement sand 1:7	Cu.m.	1,230.05	8,380.50	
	,		Cu.ft.	34.85	237.35	
	vii	Cement sand 1:8	Cu.m.	1,230.05	8,339.35	
	• • •		Cu.ft.	34.85	236.20	
	b)	Above 4.5" (115mm) nominal thick brickwork		000	200.20	
		Cement sand 1 : 2	Cu.m.	1,203.10	4,952.68	
	٠,		Cu.ft.	34.05	140.25	

Cr. No		Decariation	l lmi4	Rat	e (Rs.)	Ref. Tech.
Sr. No).	Description	Unit	Labour	Composite	Specs.
	ii)	Cement sand 1 : 3	Cu.m.	1,203.10	4,691.90	
			Cu.ft.	34.05	132.90	
			N-200 (11 (14 (14 (14 (14 (14 (14 (14 (14 (14			
	iii)	Cement sand 1 : 4	Cu.m.	1,203.10	4,462.34	
			Cu.ft.	34.05	126.40	
	iv)	Cement sand 1 : 5	Cu.m.	1,203.10	4,267.25	
			Cu.ft.	34.05	120.85	
		Cement sand 1 : 6	Cu.m.	1 202 10	4.060.00	
	۷)	Cernent sand 1.6	Cu.ft.	1,203.10 34.05	4,062.03 115.05	
		8 ASHM	Ou.it.	34.03	115.05	
	vi)	Cement sand 1:7	Cu.m.	1,203.10	3,917.89	
	V1)	ochicht sand 1.7	Cu.ft.	34.05	110.95	
				54.55	. 10.00	
	vii	Cement sand 1 : 8	Cu.m.	1,203.10	3,751.70	
	•		Cu.ft.	34.05	106.25	
11-20		Extra for providing and laying first class burnt brick masonry architrave of required shape of any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.12
			0	4 040 00	0.705.00	
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,619.62	3,795.90	
			Cu.ft.	45.85	107.50	
	h)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	907.23	2,259.07	
	D)	Above 10.5 (045 mm) Hominal thick blick work	Cu.ft.	25.70	64.00	
			ou.i	20.10	01.00	
11-21		Extra for providing and laying first class burnt tile masonry architrave of required shape of any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.80 11.12
	۱۾	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,832.96	2,179.53	
	aj	Sp. 3 (200 mm) Hormital thick the masonly	Cu.ft.	51.90	61.75	
			Ou.it.	01.00	01.70	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,692.67	1,753.29	
	-,	, , , , , , , , , , , , , , , , , , , ,	Cu.ft.	47.95	49.65	
11-22		Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	942.74	2,554.20	
			Cu.ft.	26.70	72.35	
			_			
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	866.44	2,146.85	
			Cu.ft.	24.55	60.80	

Sr. No	_	Decariation	Unit	Rat	e (Rs.)	Ref. Tech.
Sr. NO	0.	Description	Unit	Labour	Composite	Specs.
11-23		Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.	-			11.17
	a)	Upto 9" (230 mm) riominal thick tile masonry	Cu.m. Cu.ft.	1,590.58 45.05	9,003.17 254.95	
11-24	b)	Above 9" (230 mm) nominal thick tile masonry Extra for providing and laying first class burnt brick masonry	Cu.m. Cu.ft.	1,483.90 42.00	10,396.47 294.45	11.12
		cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	747.27	1,569.27	
			Cu.ft.	21.15	44.45	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	1,833.78	3,410.83	
			Cu.ft.	51.95	96.60	
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,590.58	8,390.81	
	,		Cu.ft.	45.05	237.65	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,051.13	9,555.41	
	۷,		Cu.ft.	29.75	270.60	
11-26	a)	Extra for brick masonry in first floor	Cu.m.	555.75	572.40	11.17
	,	,	Cu.ft.	15.75	16.20	
	h)	Extra for brick or tile masonry in every additional floor over	Cu.m.	336.35	346.45	
	D)	first floor.				
			Cu.ft.	9.55	9.80	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m.	699.50	802.20	11.17
			Cu.ft.	19.80	22.70	
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	480.10	550.55	11.17
			Cu.ft.	13.60	15.60	
11-28	a)	Extra for honey comb masonry in first floor	Cu.m.	412.00	424.35	11.10
5	۵)		Cu.ft.	11.65	12.00	
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	336.35	346.45	

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
31. NO.	Description	Offic	Labour	Composite	Specs.
		Cu.ft.	9.55	9.80	
11-29	Providing and laying first class brick masonry in steining of walls including scaffolding and curing upto 10 ft (3 m) depth.				11.70
а	Upto 13.5" (345 mm) nominal thick brick masonry				
i	Cement sand 1:2	Cu.m.	2,031.15	9,044.68	
	(*) X(Z)	Cu.ft.	57.50	256.15	
ii	Cement sand 1:3	Cu.m.	2,031.15	8,667.66	
		Cu.ft.	57.50	245.45	
iii	Cement sand 1 : 4	Cu.m.	2,031.15	8,347.60	
		Cu.ft.	57.50	236.40	
iv	Cement sand 1 : 5	Cu.m.	2,031.15	8,022.32	
		Cu.ft.	57.50	227.20	
V	Cement sand 1 : 6	Cu.m.	2,031.15	7,706.42	
		Cu.ft.	57.50	218.25	
vi	Cement sand 1 : 7	Cu.m.	2,031.15	7,477.87	
		Cu.ft.	57.50	211.80	
vi	Cement sand 1 : 8	Cu.m.	2,031.15	7,685.31	
		Cu.ft.	57.50	217.65	
	Above 13.5" (345 mm) nominal thick brick masonry				
i	Cement sand 1:2	Cu.m.	1,548.95	8,227.00	
		Cu.ft.	43.85	233.00	
ii	Cement sand 1:3	Cu.m.	1,548.95	7,938.79	
		Cu.ft.	43.85	224.85	
iii	Cement sand 1 : 4	Cu.m.	1,548.95	7,685.86	
		Cu.ft.	43.85	217.65	
iv	Cement sand 1 : 5	Cu.m.	1,548.95	7,538.31	
		Cu.ft.	43.85	213.50	
v	Cement sand 1:6	Cu.m.	1,548.95	7,432.93	
•		Cu.ft.	43.85	210.50	
vi	Cement sand 1:7	Cu.m.	1,548.95	7,369.69	
		Cu.ft.	43.85	208.70	
vi	i Cement sand 1 : 8	Cu.m.	1,548.95	7,306.45	
		Cu.ft.	43.85	206.90	
		Cu.ft.	43.85	206.90	

	5		Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
c)	Extra for every additional 5 ft (1.5 m) depth or part thereof for brick masonry in steining of walls.	Cu.m. Cu.ft.	256.35 7.25	264.05 7.50	
11-30	Providing and laying first class burnt brick masonry cavity walls bonded with wall ties of approved design at required horizontal and vertical spacings including scaffolding, raking out joints and curing in ground floor superstructure but excluding the cost of wall ties (No deduction will be made from the measurement for cavity in the wall).				11.14
	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on either side. Cement sand 1: 2	Cu.m.	2,469.10	10,680.35	
,	Cement sand 1 : 2	Cu.ft.	69.95	302.45	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,469.10 69.95	10,433.75 295.50	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,469.10 69.95	10,185.50 288.45	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,469.10 69.95	10,040.65 284.35	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,469.10 69.95	9,937.20 281.45	
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,469.10 69.95	9,875.15 279.65	
vii		Cu.m. Cu.ft.	2,469.10 69.95	9,813.10 277.90	
b)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on one side and 9" (230 mm) wall width on the other side.				
i)	Cement sand 1 : 2	Cu.m. Cu.ft.	2,618.85 74.15	11,531.70 326.60	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,618.85 74.15	11,227.45 317.95	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,618.85 74.15	10,921.10 309.30	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,618.85 74.15	10,742.40 304.25	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,618.85 74.15	10,614.75 300.60	

0- 1-	Paramintian.	11!1	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
	O	0	0.040.05	40 500 45	
VI)	Cement sand 1 : 7	Cu.m.	2,618.85	10,538.15	
		Cu.ft.	74.15	298.45	
vii	Cement sand 1 : 8	Cu.m.	2,618.85	10,461.60	
' "	Soliton Saina 115	Cu.ft.	74.15	296.30	
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230 mm)				
	wall width on either side.				
i)	Cement sand 1:2	Cu.m.	2,340.30	11,906.40	
	Control of the contro	Cu.ft.	66.30	337.20	
	Cement sand 1:3				
ii)	Cement sand 1:3	Cu.m.	2,340.30	11,468.00	
		Cu.ft.	66.30	324.80	
iii)	Cement sand 1 : 4	Cu.m.	2,340.30	11,026.65	
,	osmon cana 1. 1	Cu.ft.	66.30	312.30	
iv)	Cement sand 1 : 5	Cu.m.	2,340.30	10,769.20	
		Cu.ft.	66.30	305.00	
v)	Cement sand 1 : 6	Cu.m.	2,340.30	10,585.30	
		Cu.ft.	66.30	299.80	
vi	Cement sand 1 : 7	Cu.m.	2,340.30	10,474.95	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Cement sand 1.7	Cu.ft.	66.30	296.65	
		ou.i.i	00.00	200.00	
vii	Cement sand 1:8	Cu.m.	2,340.30	10,364.60	
		Cu.ft.	66.30	293.55	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5" (115mm) wall width on one side and 13.5" (345mm) wall width on other				
i)	side. Cement sand 1 : 2	Cu.m.	2,543.95	11,833.15	
		Cu.ft.	72.05	335.10	
ii)	Cement sand 1 : 3	Cu.m.	2,543.95	11,498.10	
		Cu.ft.	72.05	325.65	
iii/	Cement sand 1 : 4	Cu.m.	2,543.95	11,160.80	
""	S	Cu.ft.	72.05	316.10	
			100	2.30	
iv)	Cement sand 1:5	Cu.m.	2,543.95	10,964.05	
		Cu.ft.	72.05	310.50	
v)	Cement sand 1 : 6	Cu.m.	2,543.95	10,823.50	
		Cu.ft.	72.05	306.55	
اني.	Coment cand 1 · 7	Cum	2 5/3 05	10 730 20	
VI)	Cement sand 1 : 7	Cu.m.	2,543.95	10,739.20	

	Description		Rate (Rs.)		Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
				-		
		Cu.ft.	72.05	304.15		
vi	Cement sand 1:8	Cu.m.	2,543.95	10,654.85		
		Cu.ft.	72.05	301.75		
e)	Extra for brick masonry in cavity walls in first floor	Cu.m.	630.45	635.45		
	(*) [B]	Cu.ft.	17.85	18.00		
f)	Extra for brick masonry in cavity walls in every additional floor above first floor	Cu.m.	403.45	406.60		
	above ilist liooi	Cu.ft.	11.45	11.50		
44.04	D. III. III. III. III. III. III. III. I				44.70	
11-31	Providing and laying first class hollow burnt brick masonry in walls including scaffolding, raking out joints and curing in				11.70 11.10	
	ground floor superstructure.				11.10	
3)	Upto 4.5" (115 mm) nominal thick brick work					
	Cement sand 1 : 2	Cu.m.	2,037.09	13,301.65		
•,	Comone sund 1.2	Cu.ft.	57.70	376.70		
		Ou.it.	07.70	070.70		
ii)	Cement sand 1:3	Cu.m.	2,037.09	11,790.75		
,		Cu.ft.	57.70	333.90		
iii)	Cement sand 1:4	Cu.m.	2,037.09	11,638.60		
		Cu.ft.	57.70	329.60		
iv)	Cement sand 1:5	Cu.m.	2,037.09	11,549.80		
		Cu.ft.	57.70	327.10		
V)	Cement sand 1:6	Cu.m.	2,037.09	11,486.40		
		Cu.ft.	57.70	325.30		
•		0	0.007.00	44 440 40		
VI	Cement sand 1:7	Cu.m.	2,037.09	11,448.40		
		Cu.ft.	57.70	324.25		
vi	Cement sand 1:8	Cu.m.	2,037.09	11,410.35		
VI	Cement sand 1.0	Cu.ft.	57.70	323.15		
		Ou.it.	37.70	020.10		
b)	Above 4.5" (115mm) nominal thick brickwork					
	Cement sand 1 : 2	Cu.m.	1,918.10	12,946.45		
•		Cu.ft.	54.30	366.65		
ii)	Cement sand 1:3	Cu.m.	1,918.10	11,747.40		
		Cu.ft.	54.30	332.70		
iii)	Cement sand 1:4	Cu.m.	1,918.10	11,516.40		
		Cu.ft.	54.30	326.15		

	5		Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m.	1,918.10	11,381.65	
		Cu.ft.	54.30	322.35	
W	Cement sand 1 : 6	Cu.m.	1,918.10	11,285.45	
"	Cement sand 1.0	Cu.ft.	54.30	319.60	
		- Cuitti	04.00	010.00	
vi)	Cement sand 1:7	Cu.m.	1,918.10	11,227.70	
ĺ		Cu.ft.	54.30	318.00	
	M				
vii	Cement sand 1:8	Cu.m.	1,918.10	11,169.95	
	Eg CHARLE	Cu.ft.	54.30	316.35	
	PO JAMMU & KASHIM				
11-32	Providing and laying first class perforated brick masonry in				11.10
	Upto 4.5" (115 mm) nominal thick brick work	0	0.044.00	40 700 70	
1)	Cement sand 1 : 2	Cu.m.	2,341.09 66.30	12,732.70 360.60	
		Cu.ft.	00.30	300.00	
ii)	Cement sand 1:3	Cu.m.	2,341.09	12,055.10	
,		Cu.ft.	66.30	341.40	
iii)	Cement sand 1:4	Cu.m.	2,341.09	11,820.70	
		Cu.ft.	66.30	334.75	
iv)	Cement sand 1 : 5	Cu.m.	2,341.09	11,683.95	
		Cu.ft.	66.30	330.90	
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Cement sand 1 : 6	Cu.m.	2,341.09	11,586.25	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Cement sand 1.0	Cu.ft.	66.30	328.15	
		ou.i	00.00	020.10	
vi)	Cement sand 1 : 7	Cu.m.	2,341.09	11,527.65	
		Cu.ft.	66.30	326.45	
vii	Cement sand 1 : 8	Cu.m.	2,341.09	11,469.05	
		Cu.ft.	66.30	324.80	
	Ab 45 (445)				
	Above 4.5" (115mm) nominal thick brickwork Cement sand 1: 2	Cu.m.	2,204.80	12,548.85	
"	osmon sana 1.2	Cu.ft.	62.45	355.40	
			32.70	330.10	
ii)	Cement sand 1:3	Cu.m.	2,204.80	11,938.45	
ĺ		Cu.ft.	62.45	338.10	
iii)	Cement sand 1 : 4	Cu.m.	2,204.80	11,601.40	
		Cu.ft.	62.45	328.55	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
31. NO.	Description	Offic	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,204.80 62.45	11,404.75 323.00	
v)	Cement sand 1 : 6	Cu.m.	2,204.80	11,264.30 319.00	
vi)	Cement sand 1:7	Cu.m. Cu.ft.	2,204.80 62.45	11,180.05 316.65	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,204.80 62.45	11,095.80 314.25	
11-33 a)	Extra for hollow and perforated brick masonry in first floor	Cu.m. Cu.ft.	555.75 15.75	572.40 16.20	
b)	Extra for hollow and perforated brick masonry in every additional floor over first floor.	Cu.m. Cu.ft.	336.35 9.55	346.45 9.80	
11-34	Providing and laying fabric steel reinforcement 1" (25 mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embeded in every third horizontal course in basement, plinth and ground floor.	Kg. Lb.	18.85 8.55	144.65 65.60	11.15
11-35	Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.	Ton Tonne	8,426.15 8,561.40	85,378.90 83,951.72	11.15
11-36	Providing and laying hoop iron reinforcement in brick work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Kg. Lb.	24.45 11.10	131.55 59.65	11.15
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20 mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	_	27.85 12.65	131.75 59.75	11.14.3
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Tonne Ton	1,428.00 1,450.90	78,310.80 79,567.70	11.15
11-39	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	27.50 12.45	134.70 61.10	11.15
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in first	Kg. Lb.	4.90 2.20	5.25 2.40	11.15

Sr. No.		Description	Ini4	Rate (Rs.)		Ref. Tech.
Sr. No	ο.	Description	Unit	Labour	Composite	Specs.
	b)	Providing and placing hoop iron in steining of brick work in	Kg.	2.95	3.20	
		wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Lb.	1.35	1.45	
11-41		Extra for mild steel or hoop iron reinforcement in steining of	Kg.	5.35	5.75	11.15
		brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.	Lb.	2.45	2.60	
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,624.50	13,873.85	
	,		Cu.ft.	102.65	392.90	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m. Cu.ft.	3,115.35 88.25	10,116.50 286.50	
11-43		Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,131.30	16,854.90	
		places.	Cu.ft.	117.00	477.35	
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	3,622.15	16,469.25	
			Cu.ft.	102.60	466.40	
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,624.50	14,226.35	
		places.	Cu.ft.	102.65	402.90	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,115.35	13,677.75	
		places.	Cu.ft.	88.25	387.35	
11-45		Providing and laying fire brick lining in arches for fire places				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	4,131.30 117.00	15,227.05 431.25	

		5		Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	3,622.15 102.60	14,633.30 414.40	
11-46	a)	Extra for first floor over item 11-42 to 11-45	Cu.m. Cu.ft.	555.75 15.75	572.40 16.20	
	b)	Extra for every additional floor above first floor over item 11-46(a)	Cu.m.	336.35	346.45	
			Cu.ft.	9.55	9.80	
11-47		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.	Cu.ft.	2,284.60 64.70	13,923.80 394.35	11.70
11-48		Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4 including formwork and its removal, compacting, curing but excluding the cost of reinforcement in basement and ground floor.				
	a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	3,290.90 93.20	11,933.70 337.95	
	b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	2,284.60 64.70	10,439.83 295.65	
	c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5" thick cover on top and 4 brick panel laid in cement sand mortar 1:3.	Cu.m. Cu.ft.	2,068.95 58.60	9,622.21 272.50	
11-49		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in cantilever slab, sun shade etc. including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				11.70
	a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m. Cu.ft.	2,878.37 81.50	16,770.08 474.95	
	b)	4.5" (115mm) nominal thick cantilever slab and sun shade	Cu.m. Cu.ft.	2,422.41 68.60	14,792.27 418.95	
11-50		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing of required section including scaffolding and formwork and its removal, curing but excluding the cost of reinforcement in basement and ground floor.	Cu.m.	3,316.63	16,769.95	11.70
			Cu.ft.	93.95	474.95	

C: N	_	Description	l lmit	Rat	e (Rs.)	Ref. Tech.
Sr. No	о.	Description	Unit	Labour	Composite	Specs.
11-51	a)	Extra for R.B. masonry for first floor.	Cu.m.	271.65	349.75	
			Cu.ft.	7.70	9.90	
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	271.65	279.80	
			Cu.ft.	7.70	7.90	
44.50		Fixture labour for exactly and flored outstails	Cu.m.	440.05	455.05	
11-52		Extra labour for profile and flared out walls.	Cu.ft.	442.35 12.55	455.65 12.90	
		PO JAMMU & KASHIM	Ou.it.	12.55	12.90	
11-53		Extra labour for pucca brick work in piers and abutment.				
11 00		Extra labour for passa silen werk in piere and abatinents				
	a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m.	343.55	353.85	
	,	, , ,	Cu.ft.	9.75	10.00	
	b)	Above 20 ft (6 m) height	Cu.m.	640.05	659.25	
			Cu.ft.	18.15	18.65	
11-54		Extra to face work 4.5" (115 mm) nominal thick using special		110.00	120.98	
		bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.ft.	3.10	3.45	
11-55		Extra for dressing or chamfering bricks.				
	a)	Special architectural bricks	% Nos.	736.75	736.75	
	b)	All other numeroes	% Nos.	368.40	368.40	
	D)	All other purposes	% NOS.	300.40	300.40	
11-56		Providing and laying ghilafi brick work 13.5" (345mm) nominal				
11 30		thick including scaffolding and raking out joints with 1:5				11.20
		mortar				11.20
	a)	Foundation, basement and plinth	Cu.m.	1,488.80	8,758.35	
			Cu.ft.	42.15	248.05	
	b)	Walls in superstructure	Cu.m.	1,568.15	8,837.70	
			Cu.ft.	44.40	250.30	
11-57		Providing and laying first class burnt bricks flooring or pitching dry bricks laid flat.		599.00	9,737.80	
		ary brions laid flat.	Cu.ft.	16.95	275.80	14.80
11-58		Providing pise wall (mud walling) in superstructure.	Cu.m.	575.05	7 502 25	
11-30		i roviding pise wali (mud waliing) ili superstructure.	Cu.m.	16.30	7,583.35 214.75	11.7.2(A)
			Ju.it.	10.50	217.73	11.7.2(八)
11-59		Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	221.75	221.75	
1133		Stock may brioke distribution from Racia pacca masonity.	/0 INOS.	221.10	221.10	4.10
11-60		Scraping bricks dismantled from pacca masonry.	% Nos.	427.70	427.70	
		, J				

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
Sr. NO.			Labour	Composite	Specs.
					4.10
11-61	Supplying and filling sand under floor or plugging in wells.with	Cu.m.	314.34	1,122.63	
	lead upto 800 ft (250m)	Cu.ft.	8.90	31.80	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m.	712.80	1,033.04	
	(*) pla	Cu.ft.	20.20	29.25	
11-63	Replacing Kallar eaten bricks	Each	40.75	63.70	
11-64	Repairing corners of bridges and other hydraulic masonry	Each	407.30	866.95	
11-65	Extra labour for drains of bath rooms etc.	R.M.	101.85	101.85	
		R.ft.	31.05	31.05	
11-66	Extra work for Marrow corners.	Each	203.65	233.85	44.74.47
11-67	Extra for first class burnt solid or hollow block or tile masonry	Cu.m.	80.20	94.60	11.7.4.4 (c)
11-07	of any description in any floor or other than building for every	Cu.ft.	2.25	2.70	11.70
	1.50 m. height or part thereof beyond 4.5m.				
11-68	Extra for reinforcement in brick work of any description for	Tonne	1,456.75	1,485.90	
	every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.	Ton	1,480.15	1,509.75	5.40