O N		Description	11-21	Rat	e (Rs.)	Ref. Tech.
Sr. No	).	Description	Unit	Labour	Composite	Specs.
11-1		Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,105.05 59.60	11,331.25 320.90	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	4,469.90 126.60	11,670.82 330.50	
11-2		Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation and substructure				11.4.1 11.7.2(i) 11.7.4
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,648.50 46.70	12,290.55 348.10	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,222.45 34.60	11,118.15 314.85	
11-3		Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
						11.7.4
		Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m.	1 649 50	14 250 20	
	1)	Cement Sand 1.2	Cu.ft.	1,648.50 46.70	14,259.30 403.85	
	ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,648.50 46.70	13,688.61 387.65	
	iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,648.50 46.70	13,119.65 371.55	
	iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	1,648.50 46.70	12,643.03 358.05	
	v)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,648.50 46.70	12,259.78 347.20	
	vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	1,648.50 46.70	11,886.93 336.65	
	vii	Cement sand 1 : 8	Cu.m. Cu.ft.	1,648.50 46.70	11,517.49 326.20	
	b)	Above 4.5" (115mm) nominal thick brickwork				
		Cement sand 1 : 2	Cu.m. Cu.ft.	1,222.45 34.60	13,952.50 395.15	

C- 1:		Description	He-!4	Rat	e (Rs.)	Ref. Tech.
Sr. N	о.	Description	Unit	Labour	Composite	Specs.
	ii)	Cement sand 1:3	Cu.m.	1,222.45	13,284.24	
			Cu.ft.	34.60	376.20	
	:::\	Cement sand 1 : 4	Cu.m.	1 222 45	10 576 10	
	111)	Cement Sand 1.4	Cu.ft.	1,222.45 34.60	12,576.43 356.15	
		( - 4	Ou.it.	34.00	330.13	
	iv)	Cement sand 1:5	Cu.m.	1,222.45	12,005.05	
	,	( Ma	Cu.ft.	34.60	340.00	
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
	v)	Cement sand 1:6	Cu.m.	1,222.45	11,526.26	
		JAMMU & KASH	Cu.ft.	34.60	326.45	
	vi)	Cement sand 1:7	Cu.m.	1,222.45	11,132.76	
			Cu.ft.	34.60	315.30	
		Compart and 4 · 0	0	4 000 45	40.740.00	
	VII	Cement sand 1:8	Cu.m. Cu.ft.	1,222.45 34.60	10,718.26 303.55	
			Cu.ii.	34.60	303.55	
11-4		Extra for providing and laying first class burnt brick masonry				11.80
		for arches of any kind of wall including scaffolding, formwork				
		and its removal, raking out joints and curing in basement etc.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	881.27	3,012.14	
			Cu.ft.	23.95	76.00	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	845.85	2,682.96 85.30	
			Cu.ii.	24.95	65.30	
11-5		Extra for providing and laying first class tile masonry for				11.80
		arches of any kind of walls including scaffolding, formwork				11.90
		and its removal, raking out joints and curing in foundations, basement and plinth.				
		passinoni ana piinai.				
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,287.72	2,108.94	
			Cu.ft.	36.45	59.75	
	LV	About Oli (220 mm) massical thirty tile	0	4 040 70	4.040.04	
	D)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,216.72	1,848.94	
			Cu.ft.	34.45	52.35	
11-6		Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	293.20	293.20	11.7.4
		foundation and basement masonry deeper than 6 ft (2 m)	Cu.ft.	8.30	8.30	
11-7		Extra for every additional 5 ft (1.5 m) or part thereof in plinth	Cu.m.	218.00	218.00	11.7.4
		higher than 5 ft (1.5m)	Cu.ft.	6.15	6.15	
11-8		Extra for every additional 6 ft (2m) or part thereof for arch brick or tile masonry in foundation and basement masonry		293.20	337.20	11.80
		deeper than 6ft (2m)	Cu.ft.	8.30	9.55	11.90

C- 11	_	Description	[]m!i	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
11-9		Extra for every additional 5 ft (1.5m) or part thereof for arch brick or tile masonry in plinth higher than 5ft (1.5m)	Cu.m.	218.00	250.75	11.80
		brick of the masonry in plinter riigher than 5tt (1.5m)	Cu.ft.	6.15	7.10	11.90
11-10		Providing and laying sundried clay bricks set in mud mortar including scaffolding in ground floor superstructure				11.7.2(i) 11.18
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	1,313.48	11,048.19	
			Cu.ft.	37.20	312.90	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,478.55	8,030.55	
		Above 4.5" (115mm) nominal thick brickwork	Cu.ft.	41.85	227.45	
11-11		Providing and laying first class solid burnt brick masonry set				11.4.1
		in mud mortar including scaffolding, raking out joints and curing in ground floor superstructure.				11.7.2(i)
						11.7.4
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	2,052.55	13,377.71	
	,	,	Cu.ft.	58.15	378.85	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,520.14	9,442.81	
			Cu.ft.	43.05	267.45	
11-12		Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure				11.4.1 11.7.2(ii)
	a)	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
	i)	Cement sand 1 : 2	Cu.m.	2,052.55	14,912.20	
			Cu.ft.	58.15	422.30	
	ii)	Cement sand 1 : 3	Cu.m.	2,052.55	14,334.82	
	,	osmon cana 1.0	Cu.ft.	58.15	405.95	
	iii)	Cement sand 1 : 4	Cu.m.	2,052.55	13,758.03	
			Cu.ft.	58.15	389.65	
	iv)	Cement sand 1 : 5	Cu.m.	2,052.55	13,279.25	
	,		Cu.ft.	58.15	376.10	
	v)	Cement sand 1 : 6	Cu.m.	2,052.55	12,913.31	
			Cu.ft.	58.15	365.70	
	vi)	Cement sand 1 : 7	Cu.m.	2,052.55	12,541.75	
	.,		Cu.ft.	58.15	355.20	
	vii	Cement sand 1 : 8	Cu.m.	2,052.55	12,176.84	
			Cu.ft.	58.15	344.85	

	Description	Unit		e (Rs.)	Ref. Tech.
			Labour	Composite	Specs.
b)	Above 4.5" (115mm) nominal thick brickwork				
i)	Cement sand 1:2	Cu.m.	1,626.55	14,518.51	
		Cu.ft.	46.05	411.15	
ii)	Cement sand 1 : 3	Cu.m.	1,626.55	13,846.35	
		Cu.ft.	46.05	392.15	
iii)	Cement sand 1 : 4	Cu.m.	1,626.55 46.05	13,132.48 371.90	
iv)	Cement sand 1 : 5	Cu.m.	1,626.55 46.05	12,588.89 356.50	
v)	Cement sand 1 : 6	Cu.m.	1,626.55	12,101.18	
		Cu.ft.	46.05	342.70	
vi)	Cement sand 1 : 7	Cu.m.	1,626.55	11,720.41	
,		Cu.ft.	46.05	331.95	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	1,626.55 46.05	11,337.77 321.10	
	Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	50.90	2.423.43	
- /		Cu.ft.	1.45	68.65	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	263.90	2,266.59	
ŕ	· ·	Cu.ft.	7.45	64.20	
	Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80 11.90
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	3,672.05 104.00	3,518.31 79.25	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	3,246.05 91.95	2,798.27 99.65	
	Extra for masonry in pillars and columns in foundation				11.18
a)	Rectangular or square shape	Cu.m.	1,125.35	1,531.25	
iii iv v	, iii) >) >) <i>i</i> i) vii a) b)	iii) Cement sand 1 : 4  v) Cement sand 1 : 5  v) Cement sand 1 : 6  Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 4.5" (115 mm) nominal thick brick work  Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 9" (230 mm) nominal thick tile masonry  b) Above 9" (230 mm) nominal thick tile masonry	Cu.ft.  Cu.m. Cu.ft.  Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 4.5" (115 mm) nominal thick brick work  Cu.m. Cu.ft.  Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 9" (230 mm) nominal thick tile masonry  Cu.m. Cu.ft.  Extra for masonry in pillars and columns in foundation	Cu.ft. 46.05  Cu.m. 1,626.55 Cu.ft. 46.05  V) Cement sand 1 : 6  Cu.m. 1,626.55 Cu.ft. 46.05  V) Cement sand 1 : 6  Cu.m. 1,626.55 Cu.ft. 46.05  Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 4.5" (115 mm) nominal thick brick work  Cu.m. 50.90 Cu.ft. 1.45  Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.  a) Upto 9" (230 mm) nominal thick tile masonry  Cu.m. 3,672.05 Cu.ft. 104.00  Above 9" (230 mm) nominal thick tile masonry  Cu.m. 3,672.05 Cu.ft. 104.00  Extra for masonry in pillars and columns in foundation  a) Rectangular or square shape  Cu.m. 1,125.35	Cu.ft. 46.05 392.15  Cu.m. 1,626.55 13,132.48

				Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
				Labour	Composite	•
	b)	Round shape	Cu.m.	2,497.40	3,101.75	
	~)	Tround Chape	Cu.ft.	70.75	87.85	
			Ou.it.	70.70	07.00	
11-16		Extra for masonry in pillars and cloumns in ground floor				11.7.4
11.10		superstructure				
	a)	Rectangular or square shape	Cu.m.	1,202.08	2,278.95	
	u)	Trestangular of oquals shape	Cu.ft.	34.05	64.55	
		Na Company	ou.it.	04.00	04.00	
	h)	Round shape	Cu.m.	2,325.89	4,417.58	
	D)	Tround Shape	Cu.ft.	65.85	125.10	
		AMMU & KASHIM	ou.it.	00.00	123.10	
11-17		Extra for masonry of any description in steps.	Cu.m.	721.04	721.04	11.17.4
11-17		Extra for masonly or any description in steps.	Cu.ft.	20.40	20.40	11.17.4
			Cu.it.	20.40	20.40	
11-18		Extra for masonry of any description for bonding old and new	Cum	331.65	474.20	11.11
11-10		masonry including making recesses as required (New	Cu.m. Cu.ft.	9.40	13.45	11.11
		masonry inserted in old masonry to be measured)	Cu.ii.	9.40	13.45	
11-19		Draviding and laving first class burnt brief hancy comb				11.10
11-19		Providing and laying first class burnt brick honey comb masonry including scaffolding, raking out joints where				11.10
		required and curing in ground floor superstructure (opening				
		not to be deducted for the purpose of measurement).				
	۵)	Upto 4.5" (115 mm) nominal thick brick work				
		Cement sand 1:2	Cu.m.	1,286.65	11,457.95	
	1)	Cement Sand 1.2	Cu.ft.	36.45	324.50	
			Cu.ii.	30.43	324.30	
	ii۱	Cement sand 1:3	Cu.m.	1,286.65	11,272.20	
	")	Cement sand 1.3	Cu.ft.	36.45	319.25	
			Cu.ii.	30.43	319.23	
	:::\	Cement sand 1:4	Cu.m.	1.286.65	11 069 70	
	111)	Cement Sand 1.4		,	,	
			Cu.ft.	36.45	313.45	
	j, A	Coment cand 1 · 5	C ~	1 206 65	10.050.00	
	ıv)	Cement sand 1 : 5	Cu.m.	1,286.65	10,950.00	
			Cu.ft.	36.45	310.10	
	٠,٠	Coment and 1 · 6	Cu ~	1 206 65	10.065.00	
	V)	Cement sand 1 : 6	Cu.m.	1,286.65	10,865.20	
			Cu.ft.	36.45	307.70	
	۷:.,	Coment and 1 : 7	C	1 200 05	10.044.05	
	VI)	Cement sand 1 : 7	Cu.m.	1,286.65	10,814.35	
		Company and 4 + 0	Cu.ft.	36.45	306.25	
	VII	Cement sand 1:8	Cu.m.	1,286.65	10,763.45	
	, ,	Above 4.58 (445mm) months ald the little in	Cu.ft.	36.45	304.85	
		Above 4.5" (115mm) nominal thick brickwork	0	4.050.50	0.000.50	
	I)	Cement sand 1 : 2	Cu.m.	1,258.50	6,332.58	
			Cu.ft.	35.65	179.35	

			Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
i	Cement sand 1 : 3	Cu.m.	1,258.50	6,011.16	
		Cu.ft.	35.65	170.25	
ii	Cement sand 1 : 4	Cu.m.	1,258.50	5,720.66	
		Cu.ft.	35.65	162.00	
iv	Cement sand 1 : 5	Cu.m.	1,258.50	5,472.66	
		Cu.ft.	35.65	155.00	
\	Cement sand 1 : 6	Cu.m.	1,258.50	5,210.90	
	E SHAME	Cu.ft.	35.65	147.60	
	PO VAMMU & KASHIM	02000000			
V	Cement sand 1 : 7	Cu.m.	1,258.50	5,026.83	
		Cu.ft.	35.65	142.35	
	" O   4 0	0	4 050 50	4 04 4 40	
ľ	i Cement sand 1 : 8	Cu.m. Cu.ft.	1,258.50 35.65	4,814.43 136.35	
		Cu.ii.	33.03	130.33	
11-20	Extra for providing and laying first class burnt brick masonry architrave of required shape of any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.12
a	Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,694.17	4,085.25	
		Cu.ft.	48.00	115.70	
k	) Above 13.5" (345 mm) nominal thick brick work	Cu.m.	949.00	2,439.50	
		Cu.ft.	26.90	69.10	
11-21	Extra for providing and laying first class burnt tile masonry architrave of required shape of any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.80 11.12
	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,917.30	1,280.20	
	opio 5 (200 mm) nominar anok are masomy	Cu.ft.	54.30	36.25	
		Ou.it.	0 1.00	00.20	
l t	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,770.56	763.07	
	,	Cu.ft.	50.15	21.60	
11-22	Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
a	Upto 9" (230 mm) nominal thick brick work	Cu.m.	986.12	2,729.05	
		Cu.ft.	27.95	77.30	
	) About 42 51 (245 mm) = ================================	0	000.00	0.000.00	
"	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	906.33	2,303.00	
		Cu.ft.	25.65	65.20	

Sr. No	_	Decariation	Unit	Rate (Rs.)		Ref. Tech.
Sr. No	J.	Description	Unit	Labour	Composite	Specs.
11-23		Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
	a)	Upto 9" (230 mm) rominal thick tile masonry	Cu.m. Cu.ft.	1,663.71 47.10	11,454.69 324.40	
11-24	b)	Above 9" (230 mm) nominal thick tile masonry  Extra for providing and laying first class burnt brick masonry	Cu.m. Cu.ft.	1,552.15 43.95	13,319.60 377.20	11.12
11-24		cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	781.70	1,641.58	
			Cu.ft.	22.15	46.50	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	1,918.31	3,568.06	
			Cu.ft.	54.35	101.05	
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,663.71	10,651.92	
	·		Cu.ft.	47.10	301.65	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,099.50	12,354.90	
			Cu.ft.	31.15	349.90	
11-26	a)	Extra for brick masonry in first floor	Cu.m.	581.40	598.85	11.17
			Cu.ft.	16.45	16.95	
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	351.95	362.50	
			Cu.ft.	9.95	10.25	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m.	731.75	837.00	11.17
	/		Cu.ft.	20.70	23.70	
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	502.30	574.55	11.17
		11101.	Cu.ft.	14.25	16.25	
11-28	a)	Extra for honey comb masonry in first floor	Cu.m.	431.05	443.95	11.10
	,		Cu.ft.	12.20	12.55	-
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	351.95	362.50	

			Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
				·	
		Cu.ft.	9.95	10.25	
11-29	Providing and laying first class brick masonry in steining of walls including scaffolding and curing upto 10 ft (3 m) depth.				11.70
a)	Upto 13.5" (345 mm) nominal thick brick masonry				
i)	Cement sand 1 : 2	Cu.m.	2,124.60	11,520.04	
	(E) E'S)	Cu.ft.	60.15	326.25	
ii)	Cement sand 1:3	Cu.m.	2,124.60	11,068.72	
	2 CONT. CO.	Cu.ft.	60.15	313.45	
iii)	Cement sand 1:4	Cu.m.	2,124.60	10,668.36	
	THIO G	Cu.ft.	60.15	302.15	
iv)	Cement sand 1 : 5	Cu.m.	2,124.60	10,257.47	
,		Cu.ft.	60.15	290.50	
v)	Cement sand 1 : 6	Cu.m.	2,124.60	9,857.00	
		Cu.ft.	60.15	279.15	
vi)	Cement sand 1 : 7	Cu.m.	2,124.60	9,566.70	
		Cu.ft.	60.15	270.95	
vii	Cement sand 1 : 8	Cu.m.	2,124.60	9,834.21	
		Cu.ft.	60.15	278.50	
	Above 13.5" (345 mm) nominal thick brick masonry				
i)	Cement sand 1 : 2	Cu.m.	1,620.30	10,534.52	
		Cu.ft.	45.90	298.35	
ii)	Cement sand 1:3	Cu.m.	1,620.30	10,199.41	
		Cu.ft.	45.90	288.85	
iii)	Cement sand 1 : 4	Cu.m.	1,620.30	9,886.41	
		Cu.ft.	45.90	280.00	
iv)	Cement sand 1 : 5	Cu.m.	1,620.30	9,703.83	
,		Cu.ft.	45.90	274.80	
(v	Cement sand 1 : 6	Cu.m.	1,620.30	9,573.41	
		Cu.ft.	45.90	271.10	
vi)	Cement sand 1 : 7	Cu.m.	1,620.30	9,495.17	
		Cu.ft.	45.90	268.90	
vii	Cement sand 1 : 8	Cu.m.	1,620.30	9,416.90	
-		Cu.ft.	45.90	266.70	

C., N	December 11 - 12	11-24	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
c)	Extra for every additional 5 ft (1.5 m) depth or part thereof for brick masonry in steining of walls.	Cu.m. Cu.ft.	268.15 7.60	276.20 7.80	
11-30	Providing and laying first class burnt brick masonry cavity walls bonded with wall ties of approved design at required horizontal and vertical spacings including scaffolding, raking out joints and curing in ground floor superstructure but excluding the cost of wall ties (No deduction will be made from the measurement for cavity in the wall).				11.14
a)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on either side.				
i)	Cement sand 1 : 2	Cu.m. Cu.ft.	2,582.75 73.15	13,409.20 379.75	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,582.75 73.15	13,128.80 371.80	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,582.75 73.15	12,821.55 363.10	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,582.75 73.15	12,642.35 358.05	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,582.75 73.15	12,514.30 354.40	
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,582.75 73.15	12,437.50 352.25	
vii ·	Cement sand 1 : 8	Cu.m. Cu.ft.	2,582.75 73.15	12,360.70 350.05	
b)	$2^{ ext{"}}$ to $3^{ ext{"}}$ (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on one side and 9" (230 mm) wall width on the				
i)	other side. Cement sand 1 : 2	Cu.m. Cu.ft.	2,739.35 77.60	14,469.00 409.75	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,739.35 77.60	14,122.95 399.95	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,739.35 77.60	13,743.90 389.25	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,739.35 77.60	13,522.75 382.95	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,739.35 77.60	13,364.80 378.50	

_	_		Rate (Rs.)		Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
vi)	Cement sand 1:7	Cu.m.	2,739.35	13,270.00	
		Cu.ft.	77.60	375.80	
	0	Cum	0.700.05	40 475 05	
VII	Cement sand 1 : 8	Cu.m. Cu.ft.	2,739.35 77.60	13,175.25 373.15	
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230 mm)	Ou.it.	77.00	373.13	
-,	wall width on either side.				
i)	Cement sand 1:2	Cu.m.	2,448.05	14,970.55	
	Carried State	Cu.ft.	69.35	423.95	
	E. Hunter				
ii)	Cement sand 1:3	Cu.m.	2,448.05	14,472.00	
		Cu.ft.	69.35	409.85	
;;;\	Cement sand 1 : 4	Cu.m.	2,448.05	13,925.80	
111)	Cernent Sand 1 . 4	Cu.ff.	69.35	394.40	
		Cu.it.	09.55	334.40	
iv)	Cement sand 1 : 5	Cu.m.	2,448.05	13,607.20	
ŕ		Cu.ft.	69.35	385.35	
v)	Cement sand 1:6	Cu.m.	2,448.05	13,379.65	
		Cu.ft.	69.35	378.90	
	O	0	0.440.05	40.040.40	
VI)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,448.05 69.35	13,243.10 375.05	
		Cu.it.	09.55	373.03	
vii	Cement sand 1 : 8	Cu.m.	2,448.05	13,106.55	
		Cu.ft.	69.35	371.20	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5" (115mm) wall width on one side and 13.5" (345mm) wall width on other side.				
i)	Cement sand 1 : 2	Cu.m.	2,661.05	14,875.25	
		Cu.ft.	75.35	421.30	
ii)	Cement sand 1:3	Cu.m.	2,661.05	14,494.25	
		Cu.ft.	75.35	410.50	
;;;\	Cement sand 1 : 4	Cu.m.	2,661.05	14,076.85	
"")	Comon Sand 1. 7	Cu.ft.	75.35	398.65	
			. 0.00	333.30	
iv)	Cement sand 1:5	Cu.m.	2,661.05	13,833.35	
		Cu.ft.	75.35	391.75	
v)	Cement sand 1:6	Cu.m.	2,661.05	13,659.45	
		Cu.ft.	75.35	386.85	
, .:\	Coment cand 1 : 7	Cum	2 661 OF	12 555 05	
VI)	Cement sand 1 : 7	Cu.m.	2,661.05	13,555.05	

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
31. NO.	Description	Onit	Labour	Composite	Specs.
		0 "	75.05	000.00	
		Cu.ft.	75.35	383.90	
vii	Cement sand 1 : 8	Cu.m.	2,661.05	13,450.70	
	5	Cu.ft.	75.35	380.95	
e)	Extra for brick masonry in cavity walls in first floor	Cu.m.	659.55	666.20	
	(*) [69g]	Cu.ft.	18.70	18.85	
	Extra for brick masonry in cavity walls in every additional floor	Cu.m.	400.40	400.40	
1)	above first floor	Cu.ft.	422.10 11.95	426.40 12.10	
	Z. Sitt		11.50	12.10	
11-31	Providing and laying first class hollow burnt brick masonry in				11.70
	walls including scaffolding, raking out joints and curing in ground floor superstructure.				11.10
	ground noor superstructure.				
-1	Upto 4.5" (115 mm) nominal thick brick work				
· · · · · · · · · · · · · · · · · · ·	Cement sand 1 : 2	Cu.m.	2,130.76	16,699.85	
'/	School Sund 1.2	Cu.ft.	60.35	472.95	
ii)	Cement sand 1 : 3	Cu.m.	2,130.76	15,105.70	
		Cu.ft.	60.35	427.80	
:::\	Cement sand 1 : 4	Cum	2 120 76	14.017.40	
111)	Cement sand 1:4	Cu.m. Cu.ft.	2,130.76 60.35	14,917.40 422.45	
		ou.i.i	00.00	122.10	
iv)	Cement sand 1:5	Cu.m.	2,130.76	14,807.60	
		Cu.ft.	60.35	419.35	
		0	0.400.70	44.700.40	
V)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,130.76 60.35	14,729.10 417.15	
		Cu.it.	00.55	417.13	
vi)	Cement sand 1:7	Cu.m.	2,130.76	14,682.05	
		Cu.ft.	60.35	415.80	
vii	Cement sand 1 : 8	Cu.m.	2,130.76	14,634.95	
		Cu.ft.	60.35	414.45	
b)	Above 4.5" (115mm) nominal thick brickwork				
*	Cement sand 1 : 2	Cu.m.	2,006.31	16,326.30	
		Cu.ft.	56.80	462.35	
ii)	Cement sand 1 : 3	Cu.m.	2,006.31	15,051.15	
		Cu.ft.	56.80	426.25	
iii)	Cement sand 1 : 4	Cu.m.	2,006.31	14,765.30	
<b>'</b>		Cu.ft.	56.80	418.15	

	5		Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m.	2,006.31	14,598.60	
		Cu.ft.	56.80	413.45	
,,,	Cement sand 1 : 6	Cu.m.	2,006.31	14,479.50	
"	Cement Sand 1.0	Cu.ft.	56.80	410.05	
		Ou.it.	30.00	410.03	
vi)	Cement sand 1:7	Cu.m.	2,006.31	14,408.00	
ĺ		Cu.ft.	56.80	408.05	
	M				
vii	Cement sand 1:8	Cu.m.	2,006.31	14,336.55	
	E LIMIT	Cu.ft.	56.80	406.00	
	PO JAMMU & KASHM				
11-32	Providing and laying first class perforated brick masonry in				11.10
	Upto 4.5" (115 mm) nominal thick brick work				
i)	Cement sand 1 : 2	Cu.m.	2,448.74	16,068.20	
		Cu.ft.	69.35	455.05	
::\	Compart cond 4 + 2	C	0.440.74	45 000 45	
II)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,448.74 69.35	15,338.15 434.40	
		Cu.ii.	09.33	434.40	
iii)	Cement sand 1 : 4	Cu.m.	2,448.74	15,048.05	
<i>'</i>		Cu.ft.	69.35	426.15	
iv)	Cement sand 1:5	Cu.m.	2,448.74	14,878.85	
		Cu.ft.	69.35	421.40	
V)	Cement sand 1 : 6	Cu.m.	2,448.74	14,758.00	
		Cu.ft.	69.35	417.95	
vi\	Cement sand 1 : 7	Cu.m.	2,448.74	14,685.45	
V1)	Cement Sand 1.7	Cu.ft.	69.35	415.90	
		ou.it.	00.00	110.00	
vii	Cement sand 1 : 8	Cu.m.	2,448.74	14,612.95	
		Cu.ft.	69.35	413.85	
	Above 4.5" (115mm) nominal thick brickwork				
i)	Cement sand 1 : 2	Cu.m.	2,306.22	15,850.30	
		Cu.ft.	65.30	448.90	
	Coment and 1 : 2	C	2 200 00	45 404 00	
")	Cement sand 1 : 3	Cu.m.	2,306.22	15,181.30	
		Cu.ft.	65.30	429.95	
iii)	Cement sand 1 : 4	Cu.m.	2,306.22	14,764.15	
""		Cu.ft.	65.30	418.15	
	1		I		

C. N.	Decorieties	l lesia	Rate (Rs.)		Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,306.22 65.30	14,520.85 411.25		
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,306.22 65.30	14,347.05 406.30		
vi)	Cement sand 1:7	Cu.m. Cu.ft.	2,306.22 65.30	14,242.75 403.35		
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,306.22 65.30	14,138.45 400.40		
11-33 a)	Extra for hollow and perforated brick masonry in first floor	Cu.m. Cu.ft.	581.40 16.45	598.85 16.95		
b)	Extra for hollow and perforated brick masonry in every additional floor over first floor.	Cu.m. Cu.ft.	351.95 9.95	362.50 10.25		
11-34	Providing and laying fabric steel reinforcement 1" (25 mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embedded in every third horizontal	Kg. Lb.	19.75 8.95	187.85 85.20	11.15	
11-35	course in basement, plinth and ground floor.  Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.	Ton Tonne	8,819.55 8,961.10	111,637.95 109,771.83	11.15	
11-36	Providing and laying hoop iron reinforcement in brick work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Kg. Lb.	25.60 11.60	168.75 76.55	11.15	
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20 mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	Kg. Lb.	29.20 13.25	168.00 76.20	11.14.3	
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Tonne Ton	1,494.20 1,518.20	104,239.35 105,912.40	11.15	
11-39	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	28.85 13.10	172.00 78.00	11.15	
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in first	Kg. Lb.	5.10 2.30	5.50 2.50	11.15	

0	_	Description	11. 2	Rate (Rs.)		Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	b)	Providing and placing hoop iron in steining of brick work in	Kg.	3.10	3.35	
		wells including cutting, straightening, bending, wastage,	Lb.	1.40	1.50	
		overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.				
11-41		Extra for mild steel or hoop iron reinforcement in steining of	Kg.	5.60	6.05	11.15
		brickwork in wells for every additional 5 ft (1.5m) depth or part	Lb.	2.55	2.75	
		thereof beyond 5ft (1.5m) depth.				
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of				11.19
		crushed fire brick 1:2 including scaffolding in basement, plinth				
		and ground floor superstructures.				
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,791.10	17,328.35	
			Cu.ft.	107.35	490.75	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire		3,258.60	12,457.65	
			Cu.ft.	92.30	352.80	
11-43		Providing and laying fire brick lining in arches for fire places				11.19
11-43		laid in mortar of high alumina cement and fine aggregate of				11.19
		crushed fire brick 1:2 including scaffolding in basement, plinth				
		and ground floor superstructures.				
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	4,321.30	20,657.65	
		piacos.	Cu.ft.	122.40	585.05	
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	3,788.75	20,276.70	
		places.	Cu.ft.	107.30	574.25	
		Describing and leaving for heigh this area and for fire and a second				44.40
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement,				11.19
		plinth and ground floor.				
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire places.	Cu.m.	3,791.10	17,933.55	
			Cu.ft.	107.35	507.90	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,258.60	17,351.95	
	~)	places.				
			Cu.ft.	92.30	491.40	
11-45		Providing and laying fire brick lining in arches for fire places				11.19
		g , g				_
	دے	A FIL (AAF man) magainal shiple fire but to be to be and	C	4 004 00	40 400 40	
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,321.30	19,120.10	
			Cu.ft.	122.40	541.50	

0:- N		Description.	1124	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	3,788.75 107.30	18,478.20 523.30	
11-46	a)	Extra for first floor over item 11-42 to 11-45	Cu.m. Cu.ft.	581.40 16.45	598.85 16.95	
	b)	Extra for every additional floor above first floor over item 11-46(a)	Cu.m.	351.95	362.50	
			Cu.ft.	9.95	10.25	
11-47		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.	Cu.m. Cu.ft.	2,390.10 67.70	17,149.30 485.70	11.70
11-48		Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4 including formwork and its removal, compacting, curing but excluding the cost of reinforcement in basement and ground floor.				
	a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	3,442.60 97.50	13,064.70 370.00	
	b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	2,390.10 67.70	12,344.24 349.60	
	c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5" thick cover on top and 4 brick panel laid in cement sand mortar 1:3.	Cu.m. Cu.ft.	2,164.55 61.30	11,581.76 328.00	
11-49		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in cantilever slab, sun shade etc. including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				11.70
	a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m. Cu.ft.	3,011.06 85.25	19,250.95 545.20	
	b)	4.5" (115mm) nominal thick cantilever slab and sun shade	Cu.m. Cu.ft.	2,534.12 71.75	17,438.41 493.85	
11-50		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing of required section including scaffolding and formwork and its removal, curing but excluding the cost of reinforcement in basement and ground floor.	Cu.m.	3,469.32	20,014.35	11.70
			Cu.ft.	98.25	566.80	

0: N	_	Paraminting.	11!1	Rat	e (Rs.)	Ref. Tech.
Sr. No	o.	Description	Unit	Labour	Composite	Specs.
11-51	a)	Extra for R.B. masonry for first floor.	Cu.m.	284.25	366.00	
			Cu.ft.	8.05	10.35	
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	284.25	292.80	
			Cu.ft.	8.05	8.30	
11-52		Extra labour for profile and flared out walls.	Cu.m. Cu.ft.	462.85 13.10	476.70 13.50	
11-53		Extra labour for pucca brick work in piers and abutment.				
	a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m.	359.45	370.25	
			Cu.ft.	10.20	10.50	
	b)	Above 20 ft (6 m) height	Cu.m.	669.55	689.65	
			Cu.ft.	18.95	19.55	
11-54		Extra to face work 4.5" (115 mm) nominal thick using special bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.m. Cu.ft.	147.00 4.15	161.68 4.60	
11-55		Extra for dressing or chamfering bricks.				
	a)	Special architectural bricks	% Nos.	770.60	770.60	
	b)	All other purposes	% Nos.	385.30	385.30	
11-56		Providing and laying ghilafi brick work 13.5" (345mm) nominal thick including scaffolding and raking out joints with 1:5 mortar				11.20
	a)	Foundation, basement and plinth	Cu.m. Cu.ft.	1,557.25 44.10	11,231.15 318.05	
	b)	Walls in superstructure	Cu.m. Cu.ft.	1,640.25 46.45	11,314.15 320.40	
11-57		Providing and laying first class burnt bricks flooring or pitching dry bricks laid flat.	Cu.m.	626.50	12,840.00	14.90
		,	Cu.ft.	17.75	363.65	14.80
11-58		Providing pise wall (mud walling) in superstructure.	Cu.m. Cu.ft.	601.45 17.05	9,967.60 282.30	11.7.2(A)
11-59		Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	283.35	283.35	
11-60		Scraping bricks dismantled from pacca masonry.	% Nos.	546.50	546.50	4.10

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
31. NO.	Description	Onit	Labour	Composite	Specs.
					4.10
11-61	Supplying and filling sand under floor or plugging in wells.with	Cu.m.	416.88	1,488.84	
	lead upto 800 ft (250m)	Cu.ft.	11.80	42.15	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m.	745.55	1,080.51	
	(*) REG	Cu.ft.	21.10	30.60	
11-63	Replacing Kallar eaten bricks	Each	42.60	73.30	
11-64	Repairing corners of bridges and other hydraulic masonry	Each	426.00	1,040.30	
11-65	Extra labour for drains of bath rooms etc.	R.M.	106.50	106.50	
		R.ft.	32.45	32.45	
11-66	Extra work for Marrow corners.	Each	213.00	253.35	44744()
11-67	Extra for first class burnt solid or hollow block or tile masonry	Cu.m.	80.20	94.60	11.7.4.4 (c)
1107	of any description in any floor or other than building for every	Cu.ft.	2.25	2.70	11.70
	1.50 m. height or part thereof beyond 4.5m.				
11-68	Extra for reinforcement in brick work of any description for	Tonne	1,523.65	1,554.10	
	every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.	Ton	1,548.10	1,579.05	5.40