	Description		Rat	Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,012.65 57.00	8,916.21 252.50	
b)	Above 4.5" (115mm) nominal thick brickwork  Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation	Cu.m. Cu.ft.	3,485.30 98.70	8,873.40 251.30	11.4.1 11.7.2(i)
	and substructure				11.7.4
a'	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	1,576.10	9,539.15	11.7.4
		Cu.ft.	44.65	270.15	
b'	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,168.80	8,573.30	
2,	A DOTO NO (Tronning tallot brokmont	Cu.ft.	33.10	242.80	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
2,	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
	Cement sand 1 : 2	Cu.m.	1,576.10	11,112.90	
	osinon sana 1.2	Cu.ft.	44.65	314.70	
ii	Cement sand 1:3	Cu.m. Cu.ft.	1,576.10 44.65	10,643.11 301.40	
iii	Cement sand 1:4	Cu.m.	1,576.10	10,192.54	
,		Cu.ft.	44.65	288.65	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,576.10 44.65	9,817.48 278.05	
V)	Cement sand 1:6	Cu.m. Cu.ft.	1,576.10 44.65	9,516.55 269.50	
vij	Cement sand 1 : 7	Cu.m. Cu.ft.	1,576.10 44.65	9,225.11 261.25	
Vi	Cement sand 1 : 8	Cu.m. Cu.ft.	1,576.10 44.65	8,936.45 253.10	
b'	Above 4.5" (115mm) nominal thick brickwork				
	Cement sand 1 : 2	Cu.m.	1,168.80	10,839.70	
		Cu.ft.	33.10	307.00	

I	Rate (		e (Rs.)	Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.
				-	
ii)	Cement sand 1:3	Cu.m.	1,168.80	10,283.90	
		Cu.ft.	33.10	291.25	
iii)	Cement sand 1 : 4	Cu.m.	1,168.80	9,722.67	
		Cu.ft.	33.10	275.35	
iv)	Cement sand 1 : 5	Cu.m.	1,168.80	9,273.15	
10)	Germent sand 1.3	Cu.ft.	33.10	262.60	
			00.10	202.00	
v)	Cement sand 1:6	Cu.m.	1,168.80	8,897.79	
ĺ	Coment and 1:7	Cu.ft.	33.10	252.00	
vi)	Cement sand 1:7	Cu.m.	1,168.80	8,590.79	
		Cu.ft.	33.10	243.30	
vii ·	Cement sand 1:8	Cu.m.	1,168.80	8,267.73	
		Cu.ft.	33.10	234.15	
<b> </b>					44.00
	Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork				11.80
	and its removal, raking out joints and curing in basement etc.				
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	842.57	2,770.28	
- 7	, , , , , , , , , , , , , , , , , , , ,	Cu.ft.	22.90	71.55	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	808.73	2,526.11	
		Cu.ft.	23.85	78.45	
	Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork				11.80
	and its removal, raking out joints and curing in foundations,				11.90
	basement and plinth.				
6)	Linto 0" (230 mm) nominal thick tile mesonny	Cum	1 221 20	2 580 00	
a)	Opto 9 (200 mm) norminal thick the masonly				
		Ju.ii.	04.00	, 0.00	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,163.30	2,308.41	
	, , , , , , , , , , , , , , , , , , , ,	Cu.ft.	32.95	65.40	
	Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	280.35	280.35	11.7.4
	foundation and basement masonry deeper than 6 ft (2 m)	Cu.ft.	7.95	7.95	
	Extra for every additional 5 ft (1.5 m) or part thereof in plinth		208.45	208.45	11.7.4
	migner man ο π (1.οm)	Cu.ft.	5.90	5.90	
			000.0-	000.40	44.00
					11.80
	deeper than 6ft (2m)	Cu.ft.	7.95	9.15	11.90
a) b) 11-6 11-7	basement and plinth.  Upto 9" (230 mm) nominal thick tile masonry  Above 9" (230 mm) nominal thick tile masonry  Extra for every additional 6 ft (2 m) or part thereof in foundation and basement masonry deeper than 6 ft (2 m)  Extra for every additional 5 ft (1.5 m) or part thereof in plinth higher than 5 ft (1.5m)  Extra for every additional 6 ft (2m) or part thereof for arch brick or tile masonry in foundation and basement masonry	Cu.ft. Cu.m. Cu.ft. Cu.m. Cu.ft.	280.35 7.95 208.45	65.40 280.35 7.95 208.45	11.7

0- N-	Donasis ties	11!1	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-9	Extra for every additional 5 ft (1.5m) or part thereof for arch brick or tile masonry in plinth higher than 5ft (1.5m)	Cu.m. Cu.ft.	208.45 5.90	239.70 6.80	11.80 11.90
11-10	Providing and laying sundried clay bricks set in mud mortar including scaffolding in ground floor superstructure				11.7.2(i) 11.18
а	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,255.83 35.55	8,655.00 245.10	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,413.65 40.05	6,289.32 178.10	
11-11	Providing and laying first class solid burnt brick masonry set in mud mortar including scaffolding, raking out joints and curing in ground floor superstructure.				11.4.1 11.7.2(i) 11.7.4
а	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,962.45 55.60	10,511.88 297.70	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,453.41 41.15	7,417.81 210.10	
11-12	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure				11.4.1 11.7.2(ii)
а	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
i	Cement sand 1 : 2	Cu.m. Cu.ft.	1,962.45 55.60	11,689.01 331.05	
ii	Cement sand 1 : 3	Cu.m. Cu.ft.	1,962.45 55.60	11,212.08 317.55	
iii	Cement sand 1 : 4	Cu.m. Cu.ft.	1,962.45 55.60	10,753.85 304.55	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,962.45 55.60	10,375.49 293.85	
V	Cement sand 1 : 6	Cu.m. Cu.ft.	1,962.45 55.60	10,086.65 285.65	
vi	Cement sand 1 : 7	Cu.m. Cu.ft.	1,962.45 55.60	9,794.70 277.40	
V	i Cement sand 1 : 8	Cu.m. Cu.ft.	1,962.45 55.60	9,508.03 269.25	

		Description	11. 11	Rate (Rs.)		Ref. Tech.	
Sr. No	).	Description	Unit	Labour	Composite	Specs.	
		Above 4.5" (115mm) nominal thick brickwork					
	i)	Cement sand 1 : 2	Cu.m.	1,555.15	11,348.45		
			Cu.ft.	44.05	321.40		
	ii)	Cement sand 1 : 3	Cu.m.	1,555.15	10,787.48		
	,		Cu.ft.	44.05	305.50		
		(x) moder					
	iii)	Cement sand 1 : 4	Cu.m.	1,555.15	10,219.76		
		No.	Cu.ft.	44.05	289.45		
	iv)	Cement sand 1 : 5	Cu.m.	1,555.15	9,790.01		
		Cement sand 1:5	Cu.ft.	44.05	277.25		
	v)	Cement sand 1 : 6	Cu.m.	1,555.15	9,405.93		
	,		Cu.ft.	44.05	266.40		
	vi)	Cement sand 1 : 7	Cu.m.	1,555.15	9,107.11		
			Cu.ft.	44.05	257.90		
	::	Compart and 4 + 0	C	4 555 45	0.007.00		
	VII	Cement sand 1 : 8	Cu.m. Cu.ft.	1,555.15 44.05	8,807.02 249.40		
			Cu.ii.	44.05	249.40		
11-13		Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80	
	٥)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	48.65	2,083.48		
	a)	Opto 4.5 (115 mm) nominal thick blick work	Cu.ft.	1.40	59.00		
			Ou.it.	1.40	33.00		
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	252.35	2,036.63		
			Cu.ft.	7.15	57.70		
11-14		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80 11.90	
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	3,510.90	4,382.77		
	۵,	(	Cu.ft.	99.45	103.95		
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	3,103.55	3,671.35		
			Cu.ft.	87.90	124.10		
11-15		Extra for masonry in pillars and columns in foundation				11.18	
	٥)	Poetangular or equare chang	Cum	1 075 05	1 464 00		
	a)	Rectangular or square shape	Cu.m. Cu.ft.	1,075.95 30.45	1,464.08 41.45		
			Gu.ii.	30.43	71.40		

				Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
				Luboui	Composito	-
	b)	Round shape	Cu.m.	2,387.75	2,864.10	
			Cu.ft.	67.60	81.10	
11-16		Extra for masonry in pillars and cloumns in ground floor				11.7.4
		superstructure				
	a)	Rectangular or square shape	Cu.m.	1,149.33	2,178.90	
			Cu.ft.	32.55	61.70	
	b)	Round shape	Cu.m.	2,223.78	4,051.08	
		E IAMIT	Cu.ft.	63.00	114.75	
		JAMMU & KASHI	104700 N 10000 C 2			
11-17		Extra for masonry of any description in steps.	Cu.m.	689.39	689.39	11.17.4
			Cu.ft.	19.50	19.50	
			_			
11-18		Extra for masonry of any description for bonding old and new masonry including making recesses as required (New		317.10	454.55	11.11
		masonry inserted in old masonry to be measured)	Cu.ft.	9.00	12.85	
11-19		Draviding and loving first class burnt brief banay comb				11.10
11-19		Providing and laying first class burnt brick honey comb masonry including scaffolding, raking out joints where				11.10
		required and curing in ground floor superstructure (opening				
		not to be deducted for the purpose of measurement).				
	a)	Upto 4.5" (115 mm) nominal thick brick work				
		Cement sand 1 : 2	Cu.m.	1,230.20	8,914.00	
	,		Cu.ft.	34.85	252.45	
	ii)	Cement sand 1:3	Cu.m.	1,230.20	8,750.65	
			Cu.ft.	34.85	247.80	
	iii)	Cement sand 1:4	Cu.m.	1,230.20	8,586.20	
			Cu.ft.	34.85	243.15	
	iv)	Cement sand 1:5	Cu.m.	1,230.20	8,490.25	
			Cu.ft.	34.85	240.45	
	v)	Cement sand 1:6	Cu.m.	1,230.20	8,421.75	
			Cu.ft.	34.85	238.50	
					0.655	
	vi)	Cement sand 1:7	Cu.m.	1,230.20	8,380.65	
			Cu.ft.	34.85	237.35	
	VII	Cement sand 1:8	Cu.m.	1,230.20	8,339.50	
	۳,	Above 4.5" (115mm) nominal thick heighwork	Cu.ft.	34.85	236.20	
		Above 4.5" (115mm) nominal thick brickwork	C~	1 202 25	4 052 70	
	I)	Cement sand 1 : 2	Cu.m. Cu.ft.	1,203.25 34.10	4,952.78 140.25	
			Gu.II.	34.10	140.20	

			Rat	e (Rs.)	/∨\lr Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
i	Cement sand 1:3	Cu.m.	1,203.25	4,692.00	
		Cu.ft.	34.10	132.90	
ii I	Cement sand 1 : 4	Cu.m.	1,203.25	4,462.44	
		Cu.ft.	34.10	126.40	
	Cement sand 1 : 5	Cu.m.	1,203.25	1 267 24	
iv	Cernent Sand 1.5	Cu.ft.	34.10	4,267.34 120.85	
		Ou.it.	34.10	120.00	
	Cement sand 1:6	Cu.m.	1,203.25	4,062.12	
	Z. S.	Cu.ft.	34.10	115.05	
	PO VAMMU & KASHM	N=3000000000000000000000000000000000000			
v	Cement sand 1 : 7	Cu.m.	1,203.25	3,917.98	
		Cu.ft.	34.10	110.95	
	'		1		
v	i Cement sand 1 : 8	Cu.m.	1,203.25	3,751.78	
		Cu.ft.	34.10	106.25	
11-20	Extra for providing and laying first class burnt brick masonry architrave of required shape of any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.12
a	Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,619.79	3,796.30	
		Cu.ft.	45.85	107.50	
b	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	907.35	2,259.33	
		Cu.ft.	25.70	64.00	
11-21	Extra for providing and laying first class burnt tile masonry architrave of required shape of any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.80 11.12
a	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,833.13	2,180.00	
	, 5 (	Cu.ft.	51.90	61.75	
b	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,692.84	1,753.86	
		Cu.ft.	47.95	49.65	
11-22	Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
а	Upto 9" (230 mm) nominal thick brick work	Cu.m.	942.82	2,554.45	
		Cu.ft.	26.70	72.35	
b	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	866.56	2,147.10	
		Cu.ft.	24.55	60.80	

Sr. No	_	Description	l lni4	Rat	e (Rs.)	Ref. Tech.
Sr. NO	0.	Description	Unit	Labour	Composite	Specs.
11-23		Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
	a)	Upto 9" (230 mm) rominal thick tile masonry	Cu.m. Cu.ft.	1,590.69 45.05	9,003.31 255.00	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,484.03 42.05	10,396.63 294.45	
11-24		Extra for providing and laying first class burnt brick masonry cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	747.39	1,569.51	
			Cu.ft.	21.15	44.45	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	1,834.11 51.95	3,411.44 96.60	
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,590.69 45.05	8,390.92 237.65	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,051.25 29.75	9,555.58 270.60	
11-26	a)	Extra for brick masonry in first floor	Cu.m. Cu.ft.	555.85 15.75	572.55 16.20	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	336.50	346.60	
			Cu.ft.	9.55	9.80	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m. Cu.ft.	699.65 19.80	802.30 22.70	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	480.25	550.75	11.17
			Cu.ft.	13.60	15.60	
11-28	a)	Extra for honey comb masonry in first floor	Cu.m. Cu.ft.	412.10 11.65	424.50 12.00	11.10
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	336.50	346.60	

ii) Ce	Providing and laying first class brick masonry in steining of valls including scaffolding and curing upto 10 ft (3 m) depth.  Poto 13.5" (345 mm) nominal thick brick masonry sement sand 1 : 2  Sement sand 1 : 3	Cu.m. Cu.ft. Cu.m. Cu.ft. Cu.m. Cu.ft.	9.55  2,031.35 57.55  2,031.35 57.55  2,031.35 57.55	9.80 9,044.83 256.15 8,667.81 245.50	11.70
a) Up i) Ce ii) Ce iii) Ce	ralls including scaffolding and curing upto 10 ft (3 m) depth.  Ipto 13.5" (345 mm) nominal thick brick masonry ement sand 1 : 2  Element sand 1 : 3  Element sand 1 : 4	Cu.m. Cu.ft. Cu.m. Cu.ft. Cu.m.	2,031.35 57.55 2,031.35 57.55 2,031.35	9,044.83 256.15 8,667.81 245.50	11.70
a) Up i) Ce ii) Ce iii) Ce	ralls including scaffolding and curing upto 10 ft (3 m) depth.  Ipto 13.5" (345 mm) nominal thick brick masonry ement sand 1 : 2  Element sand 1 : 3  Element sand 1 : 4	Cu.m. Cu.ft. Cu.m. Cu.ft. Cu.m.	2,031.35 57.55 2,031.35 57.55 2,031.35	9,044.83 256.15 8,667.81 245.50	11.70
a) Up i) Ce ii) Ce iii) Ce	ralls including scaffolding and curing upto 10 ft (3 m) depth.  Ipto 13.5" (345 mm) nominal thick brick masonry ement sand 1 : 2  Element sand 1 : 3  Element sand 1 : 4	Cu.ft. Cu.m. Cu.ft. Cu.m.	57.55 2,031.35 57.55 2,031.35	256.15 8,667.81 245.50	11.70
i) Ce ii) Ce iii) Ce	Sement sand 1 : 2 Sement sand 1 : 3 Sement sand 1 : 4	Cu.ft. Cu.m. Cu.ft. Cu.m.	57.55 2,031.35 57.55 2,031.35	256.15 8,667.81 245.50	
ii) Ce	Sement sand 1:3	Cu.ft. Cu.m. Cu.ft. Cu.m.	57.55 2,031.35 57.55 2,031.35	256.15 8,667.81 245.50	
iii) Ce	Sement sand 1:4	Cu.m. Cu.ft.	2,031.35 57.55 2,031.35	8,667.81 245.50	
iii) Ce	Sement sand 1:4	Cu.ft.	57.55 2,031.35	245.50	
iii) Ce	Sement sand 1:4	Cu.m.	57.55 2,031.35	245.50	
			l		
iv) Ce		Cu.ft.	57.55	8,347.75	
iv) Ce			07.00	236.40	
	ement sand 1:5	Cu.m.	2,031.35	8,022.46	
		Cu.ft.	57.55	227.20	
v) Ce	ement sand 1 : 6	Cu.m.	2,031.35	7,706.55	
		Cu.ft.	57.55	218.25	
vi) Ce	ement sand 1:7	Cu.m.	2,031.35	7,478.00	
		Cu.ft.	57.55	211.80	
vii Ce	Gement sand 1:8	Cu.m.	2,031.35	7,685.45	
		Cu.ft.	57.55	217.65	
	bove 13.5" (345 mm) nominal thick brick masonry				
i) Ce	ement sand 1:2	Cu.m.	1,549.15	8,227.14	
		Cu.ft.	43.85	233.00	
ii) Ce	Gement sand 1:3	Cu.m.	1,549.15	7,938.93	
		Cu.ft.	43.85	224.85	
iii) Ce	Gement sand 1:4	Cu.m.	1,549.15	7,686.00	
		Cu.ft.	43.85	217.65	
iv) Ce	ement sand 1:5	Cu.m.	1,549.15	7,538.45	
		Cu.ft.	43.85	213.50	
v) Ce	Sement sand 1:6	Cu.m.	1,549.15	7,433.07	
		Cu.ft.	43.85	210.50	
vi) Ce	Sement sand 1:7	Cu.m.	1,549.15	7,369.83	
		Cu.ft.	43.85	208.70	
vii Ce	ement sand 1 : 8	Cu.m.	1,549.15	7,306.59	
*		Cu.ft.	43.85	206.95	

On N	December Com.	11	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
c)	Extra for every additional 5 ft (1.5 m) depth or part thereof for	Cu.m.	256.35	264.05	
	brick masonry in steining of walls.	Cu.ft.	7.25	7.50	
11-30	Providing and laying first class burnt brick masonry cavity walls bonded with wall ties of approved design at required horizontal and vertical spacings including scaffolding, raking out joints and curing in ground floor superstructure but excluding the cost of wall ties (No deduction will be made from the measurement for cavity in the wall).				11.14
a)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on either side.				
i)	Cement sand 1 : 2	Cu.m. Cu.ft.	2,469.40 69.95	10,680.65 302.50	
ii)	Cement sand 1:3	Cu.m.	2,469.40	10,434.05	
,		Cu.ft.	69.95	295.50	
iii)	Cement sand 1:4	Cu.m.	2,469.40	10,185.80	
		Cu.ft.	69.95	288.45	
iv)	Cement sand 1 : 5	Cu.m.	2,469.40	10,040.95	
17)	ocinion dana 1.0	Cu.ft.	69.95	284.35	
v)	Cement sand 1:6	Cu.m.	2,469.40	9,937.50	
		Cu.ft.	69.95	281.45	
, (1)	Coment and 1 . 7	Cum	2 460 40	0.075.45	
VI)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,469.40 69.95	9,875.45 279.70	
		Ou.it.	00.00	210.10	
vii	Cement sand 1 : 8	Cu.m.	2,469.40	9,813.40	
• •	osmon cana 110	Cu.ft.	69.95	277.90	
b)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on one side and 9" (230 mm) wall width on the				
i)	other side. Cement sand 1:2	Cu.m.	2,619.15	11,532.00	
,		Cu.ft.	74.20	326.60	
ii)	Cement sand 1:3	Cu.m.	2,619.15	11,227.75	
		Cu.ft.	74.20	318.00	
iii)	Cement sand 1 : 4	Cu.m.	2,619.15	10,921.40	
111)		Cu.ft.	74.20	309.30	
iv)	Cement sand 1 : 5	Cu.m.	2,619.15	10,742.70	
		Cu.ft.	74.20	304.25	
, A	Coment and 1 . 6	Cu	2 640 45	10.645.05	
V)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,619.15 74.20	10,615.05 300.60	
		Gu.II.	14.20	300.00	

Cr. No.	Description	l lmi4	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
, d)	Coment and 1 : 7	Cum	0.640.45	10 520 45	
VI)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,619.15 74.20	10,538.45 298.45	
		Cu.it.	74.20	230.43	
vii	Cement sand 1 : 8	Cu.m.	2,619.15	10,461.90	
٠		Cu.ft.	74.20	296.30	
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230 mm) wall width on either side.	4			
i)	Cement sand 1:2	Cu.m.	2,340.60	11,906.70	
	The second second	Cu.ft.	66.30	337.20	
	Cement sand 1:3	•			
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,340.60 66.30	11,468.30	
		Cu.it.	00.30	324.80	
iii)	Cement sand 1 : 4	Cu.m.	2,340.60	11,026.95	
ĺ		Cu.ft.	66.30	312.30	
iv)	Cement sand 1 : 5	Cu.m.	2,340.60	10,769.50	
		Cu.ft.	66.30	305.00	
\/\	Cement sand 1 : 6	Cu.m.	2,340.60	10,585.60	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Comon sand 1.0	Cu.ft.	66.30	299.80	
vi)	Cement sand 1:7	Cu.m.	2,340.60	10,475.25	
		Cu.ft.	66.30	296.65	
				40.004.00	
VII	Cement sand 1 : 8	Cu.m. Cu.ft.	2,340.60 66.30	10,364.90 293.55	
		Cu.ii.	00.30	293.55	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5" (115mm) wall width on one side and 13.5" (345mm) wall width on other				
(i	side. Cement sand 1 : 2	Cu.m.	2,544.25	11,833.45	
		Cu.ft.	72.05	335.15	
ii)	Cement sand 1 : 3	Cu.m.	2,544.25	11,498.40	
		Cu.ft.	72.05	325.65	
	Company and 4 : 4	C	0.544.05	44 404 40	
"")	Cement sand 1 : 4	Cu.m. Cu.ft.	2,544.25 72.05	11,161.10 316.10	
		Ou.ii.	7 2.00	310.10	
iv)	Cement sand 1 : 5	Cu.m.	2,544.25	10,964.35	
ĺ		Cu.ft.	72.05	310.50	
V)	Cement sand 1 : 6	Cu.m.	2,544.25	10,823.80	
		Cu.ft.	72.05	306.55	
vil	Cement sand 1 : 7	Cu.m.	2,544.25	10,739.50	
V1)	Comonicoana 1.7	Ou.III.	2,074.20	10,733.30	

C. 1.	_	Description	[lm!r	Rat	e (Rs.)	Ref. Tech.	
Sr. N	0.	Description	Unit	Labour	Composite	Specs.	
			Cu.ft.	72.05	304.15		
			_				
	Vİİ	Cement sand 1 : 8	Cu.m.	2,544.25	10,655.15		
			Cu.ft.	72.05	301.75		
	۵)	Extra for brick masonry in cavity walls in first floor	Cu.m.	630.60	635.60		
	٥,	Extra for briok finasarily in savity walled fines in savity	Cu.ft.	17.85	18.00		
		(*) [22]			10.00		
	f)	Extra for brick masonry in cavity walls in every additional floor	Cu.m.	403.60	406.75		
		above first floor	Cu.ft.	11.45	11.50		
		E					
11-31		Providing and laying first class hollow burnt brick masonry in				11.70	
		walls including scaffolding, raking out joints and curing in ground floor superstructure.				11.10	
		ground noor superstructure.					
	,						
		Upto 4.5" (115 mm) nominal thick brick work	0	0.007.04	40 004 05		
	I)	Cement sand 1 : 2	Cu.m. Cu.ft.	2,037.24 57.70	13,301.85 376.70		
			Cu.it.	57.70	376.70		
	ii)	Cement sand 1:3	Cu.m.	2,037.24	11,790.90		
	,	osmon cana 1.0	Cu.ft.	57.70	333.95		
	iii)	Cement sand 1:4	Cu.m.	2,037.24	11,638.75		
			Cu.ft.	57.70	329.60		
	iv)	Cement sand 1 : 5	Cu.m.	2,037.24	11,549.95		
			Cu.ft.	57.70	327.10		
	\	Cement sand 1 : 6	Cu.m.	2.027.24	11 10C EE		
	V)	Cement sand 1.6	Cu.m.	2,037.24 57.70	11,486.55 325.30		
			Cu.it.	37.70	323.30		
	vi)	Cement sand 1:7	Cu.m.	2,037.24	11,448.55		
	,		Cu.ft.	57.70	324.25		
	vii	Cement sand 1 : 8	Cu.m.	2,037.24	11,410.50		
			Cu.ft.	57.70	323.15		
	,	Above 4.5" (115mm) nominal thick brickwork			400.55		
	i)	Cement sand 1 : 2	Cu.m.	1,918.27	12,946.65		
			Cu.ft.	54.35	366.65		
	ii۱	Cement sand 1 : 3	Cu.m.	1,918.27	11,747.55		
	")	Someth Guilla 1 . G	Cu.ft.	54.35	332.70		
					3320		
	iii)	Cement sand 1:4	Cu.m.	1,918.27	11,516.60		
	Í		Cu.ft.	54.35	326.15		
		I.					

Sr. No.	Description		Rate (Rs.)		Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m.	1,918.27	11,381.85	
		Cu.ft.	54.35	322.35	
W	Cement sand 1 : 6	Cu.m.	1,918.27	11,285.60	
٧)	Cement Sand 1.0	Cu.ft.	54.35	319.60	
		Ou.it.	34.33	319.00	
vi)	Cement sand 1:7	Cu.m.	1,918.27	11,227.85	
,		Cu.ft.	54.35	318.00	
	M				
vii	Cement sand 1:8	Cu.m.	1,918.27	11,170.10	
	E	Cu.ft.	54.35	316.35	
	JAMMU & KASH				
11-32	Providing and laying first class perforated brick masonry in				11.10
	2011-14011 MADE 2014 10 10 10 10 10				
	Upto 4.5" (115 mm) nominal thick brick work				
i)	Cement sand 1 : 2	Cu.m.	2,341.26	12,732.90	
		Cu.ft.	66.30	360.60	
::\	Compart cond 4 + 2	C	0.044.00	40.055.05	
II)	Cement sand 1:3	Cu.m. Cu.ft.	2,341.26 66.30	12,055.25 341.40	
		Cu.ii.	00.30	341.40	
iii)	Cement sand 1:4	Cu.m.	2,341.26	11,820.85	
,		Cu.ft.	66.30	334.75	
iv)	Cement sand 1 : 5	Cu.m.	2,341.26	11,684.10	
		Cu.ft.	66.30	330.90	
v)	Cement sand 1 : 6	Cu.m.	2,341.26	11,586.45	
		Cu.ft.	66.30	328.15	
2\	O	0	0.044.00	44 507 05	
VI)	Cement sand 1 : 7	Cu.m.	2,341.26 66.30	11,527.85 326.50	
		Cu.ft.	00.30	320.30	
vii	Cement sand 1:8	Cu.m.	2,341.26	11,469.25	
· ;		Cu.ft.	66.30	324.80	
b)	Above 4.5" (115mm) nominal thick brickwork				
i)	Cement sand 1:2	Cu.m.	2,204.98	12,549.10	
		Cu.ft.	62.45	355.40	
ii)	Cement sand 1:3	Cu.m.	2,204.98	11,938.65	
		Cu.ft.	62.45	338.10	
	Company and 4 : 4	0	0.004.00	44 004 55	
(iii)	Cement sand 1 : 4	Cu.m.	2,204.98	11,601.55	
		Cu.ft.	62.45	328.55	

Cr N-	Description	l le:4	Rate (Rs.)		Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,204.98 62.45	11,404.95 323.00		
V)	Cement sand 1 : 6	Cu.m.	2,204.98 62.45	11,264.50 319.00		
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,204.98 62.45	11,180.25 316.65		
vi	Cement sand 1:8	Cu.m. Cu.ft.	2,204.98 62.45	11,095.95 314.25		
11-33 a)	Extra for hollow and perforated brick masonry in first floor	Cu.m. Cu.ft.	555.85 15.75	572.55 16.20		
b)	Extra for hollow and perforated brick masonry in every additional floor over first floor.	Cu.m. Cu.ft.	336.50 9.55	346.60 9.80		
11-34	Providing and laying fabric steel reinforcement 1" (25 mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embedded in every third horizontal	Kg. Lb.	18.85 8.55	144.65 65.60	11.15	
11-35	course in basement, plinth and ground floor.  Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.	Ton Tonne	8,432.40 8,567.75	85,385.25 83,957.96	11.15	
11-36	Providing and laying hoop iron reinforcement in brick work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Kg. Lb.	24.50 11.10	131.65 59.70	11.15	
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20 mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	Kg. Lb.	27.90 12.65	131.85 59.80	11.14.3	
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Tonne Ton	1,428.60 1,451.55	78,311.40 79,568.30	11.15	
11-39	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	27.60 12.50	134.75 61.10	11.15	
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in first	Kg. Lb.	4.90 2.20	5.25 2.40	11.15	

Sr. No.		Description	l lm!4	Rate (Rs.)		Ref. Tech.
Sr. No	ο.	Description	Unit	Labour	Composite	Specs.
	b)	Providing and placing hoop iron in steining of brick work in	Kg.	2.95	3.20	
		wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Lb.	1.35	1.45	
11-41		Extra for mild steel or hoop iron reinforcement in steining of	Kg.	5.35	5.75	11.15
		brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.	Lb.	2.45	2.60	
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,624.70	13,874.05	
	,	. ` '	Cu.ft.	102.65	392.90	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m. Cu.ft.	3,115.55 88.25	10,116.70 286.50	
11-43		Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,131.60	16,855.30	
		places.	Cu.ft.	117.00	477.35	
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	3,622.45	16,469.65	
			Cu.ft.	102.60	466.45	
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,624.70	14,226.55	
		places.	Cu.ft.	102.65	402.90	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,115.55	13,677.95	
		places.	Cu.ft.	88.25	387.35	
11-45		Providing and laying fire brick lining in arches for fire places				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,131.60	15,227.35	
	/	, , , , , , , , , , , , , , , , , , , ,	Cu.ft.	117.00	431.25	

		<b>5</b>		Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	3,622.45 102.60	14,633.60 414.45	
11-46	a)	Extra for first floor over item 11-42 to 11-45	Cu.m. Cu.ft.	555.85 15.75	572.55 16.20	
	b)	Extra for every additional floor above first floor over item 11-46(a)	Cu.m.	336.50	346.60	
			Cu.ft.	9.55	9.80	
11-47		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.	Cu.m. Cu.ft.	2,285.20 64.70	13,924.40 394.35	11.70
11-48		Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4 including formwork and its removal, compacting, curing but excluding the cost of reinforcement in basement and ground floor.				
	a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	3,291.50 93.20	11,934.30 338.00	
	b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	2,285.20 64.70	10,440.34 295.70	
	c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5" thick cover on top and 4 brick panel laid in cement sand mortar 1:3.	Cu.m. Cu.ft.	2,069.55 58.60	9,622.69 272.50	
11-49		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in cantilever slab, sun shade etc. including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				11.70
	a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m. Cu.ft.	2,878.90 81.55	16,770.61 474.95	
	b)	4.5" (115mm) nominal thick cantilever slab and sun shade	Cu.m. Cu.ft.	2,422.90 68.60	14,792.82 418.95	
11-50		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing of required section including scaffolding and formwork and its removal, curing but excluding the cost of reinforcement in basement and ground floor.	Cu.m.	3,317.06	16,770.55	11.70
			Cu.ft.	93.95	474.95	

Cr. N.	_	Decariution	l lnit	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
			N-Marine Area			
11-51	a)	Extra for R.B. masonry for first floor.	Cu.m.	271.80	349.94	
			Cu.ft.	7.70	9.90	
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	271.80	279.95	
			Cu.ft.	7.70	7.95	
11-52		Extra labour for profile and flared out walls.	Cu.m.	442.50	455.80	
11-32		Extra labour for profile and flared out walls.	Cu.ft.	12.55	12.90	
		PO JAMMU & KASHIM	Ou.it.	12.00	12.90	
11-53		Extra labour for pucca brick work in piers and abutment.				
	a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m.	343.70	354.00	
			Cu.ft.	9.75	10.05	
	b)	Above 20 ft (6 m) height	Cu.m.	640.20	659.40	
			Cu.ft.	18.15	18.65	
11-54		Extra to face work 4.5" (115 mm) nominal thick using special	Cu.m.	110.00	120.98	
		bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.ft.	3.10	3.45	
		, , ,				
11-55		Extra for dressing or chamfering bricks.				
	a)	Special architectural bricks	% Nos.	736.75	736.75	
	LV	All others are seen	0/ NI==	000.40	000.40	
	D)	All other purposes	% Nos.	368.40	368.40	
11-56		Providing and laying ghilafi brick work 13.5" (345mm) nominal				
11-30		thick including scaffolding and raking out joints with 1:5				11.20
		mortar				11.20
	a)	Foundation, basement and plinth	Cu.m.	1,488.90	8,758.45	
	,	,	Cu.ft.	42.15	248.05	
	b)	Walls in superstructure	Cu.m.	1,568.25	8,837.85	
			Cu.ft.	44.40	250.30	
11-57		Providing and laying first class burnt bricks flooring or pitching		599.00	9,737.80	
		dry bricks laid flat.	Cu.ft.	16.95	275.80	14.80
44.50		Describing this could be also as the state of the state o	O	F7F 0F	7 500 05	
11-58		Providing pise wall (mud walling) in superstructure.	Cu.m.	575.05	7,583.35	11 7 9/^\
			Cu.ft.	16.30	214.75	11.7.2(A)
11-59		Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	221.75	221.75	
11-59		Cleaning bricks dismartiled from Racia pacca masonly.	/0 INUS.	221.73	221.73	4.10
11-60		Scraping bricks dismantled from pacca masonry.	% Nos.	427.70	427.70	5
		orașing brione diemanilou nom pacca macomy.	/U 1100.	0	.27.70	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
31. NO.	Description	Onit	Labour	Composite	Specs.
					4.10
11-61	Supplying and filling sand under floor or plugging in wells.with	Cu.m.	314.34	1,122.63	
	lead upto 800 ft (250m)	Cu.ft.	8.90	31.80	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m.	712.80	1,033.04	
	(*) P. (*)	Cu.ft.	20.20	29.25	
11-63	Replacing Kallar eaten bricks	Each	40.75	63.70	
11-64	Repairing corners of bridges and other hydraulic masonry	Each	407.30	866.95	
11-65	Extra labour for drains of bath rooms etc.	R.M.	101.85	101.85	
		R.ft.	31.05	31.05	
11-66	Extra work for Marrow corners.	Each	203.65	233.85	
44.07	Future for first slove burnet solid or bollow block or tile recognity	C	00.00	04.00	11.7.4.4 (c)
11-67	Extra for first class burnt solid or hollow block or tile masonry of any description in any floor or other than building for every	Cu.m.	80.20	94.60	44.70
	1.50 m. height or part thereof beyond 4.5m.	Cu.ft.	2.25	2.70	11.70
11-68	Extra for reinforcement in brick work of any description for	Tonne	1,456.75	1,485.90	
	every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.	Ton	1,480.15	1,509.75	5.40