Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
31. NO.	Description	Onit	Labour	Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
ā) Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,049.60 58.05	9,861.10 279.25	
) Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	3,870.45 109.60	9,967.19 282.30	
11-2	Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation and substructure				11.4.1 11.7.2(i) 11.7.4
a) Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,605.05 45.45	10,615.35 300.65	
t) Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,190.25 33.70	9,568.60 271.00	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
					11.7.4
	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m.	1,605.05	12,295.50	
	y Centent Sand 1.2	Cu.ft.	45.45	348.20	
i) Cement sand 1 : 3	Cu.m. Cu.ft.	1,605.05 45.45	11,802.98 334.25	
ii) Cement sand 1 : 4	Cu.m. Cu.ft.	1,605.05 45.45	11,314.44 320.45	
iv) Cement sand 1 : 5	Cu.m. Cu.ft.	1,605.05 45.45	10,904.62 308.85	
\) Cement sand 1 : 6	Cu.m. Cu.ft.	1,605.05 45.45	10,574.87 299.50	
V) Cement sand 1 : 7	Cu.m. Cu.ft.	1,605.05 45.45	10,253.78 290.40	
٧	ii Cement sand 1 : 8	Cu.m. Cu.ft.	1,605.05 45.45	9,935.58 281.40	
ŀ) Above 4.5" (115mm) nominal thick brickwork				
) Cement sand 1 : 2	Cu.m. Cu.ft.	1,190.25 33.70	11,987.60 339.50	

				Rat	e (Rs.)	Ref. Tech.
Sr. N	Ο.	Description	Unit	Labour	Composite	Specs.
	ii)	Cement sand 1:3	Cu.m.	1,190.25	11,411.46	
			Cu.ft.	33.70	323.20	
	iii)	Cement sand 1 : 4	Cu.m.	1,190.25	10,805.14	
			Cu.ft.	33.70	306.00	
		(*) [B]	16.20			
	iv)	Cement sand 1:5	Cu.m.	1,190.25	10,315.23	
			Cu.ft.	33.70	292.15	
	v)	Cement sand 1 : 6	Cu.m.	1,190.25	9,904.59	
	.,	JAMMU & KASK	Cu.ft.	33.70	280.50	
	VI)	Cement sand 1 : 7	Cu.m.	1,190.25	9,566.89	
			Cu.ft.	33.70	270.95	
	, ;;;	Cement sand 1 : 8	Cu.m.	1,190.25	9,211.11	
	V II	Gement sand 1.0	Cu.ft.	33.70	260.85	
			Ou.it.	00.70	200.00	
11-4		Extra for providing and laying first class burnt brick masonry				11.80
		for arches of any kind of wall including scaffolding, formwork				
		and its removal, raking out joints and curing in basement etc.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	858.04	2,881.66	
			Cu.ft.	23.30	73.75	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	823.58	2,604.29	
			Cu.ft.	24.30	81.60	
11-5		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork				11.80
		and its removal, raking out joints and curing in foundations,				11.90
		basement and plinth.				
	_ >	Linto Oli (220 mars) marsinal third: (11- mars a second	O	4 050 00	0.440.00	
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,253.80	2,416.68 68.45	
			Cu.ft.	35.50	00.40	
	h)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,184.67	2,148.73	
	D)	1 100 10 (200 mm) nominal triok the masonly	Cu.ft.	33.55	60.85	
			Ju.it.	30.00	30.00	
11-6		Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	285.50	285.50	11.7.4
-		foundation and basement masonry deeper than 6 ft (2 m)	Cu.ft.	8.10	8.10	
11-7		Extra for every additional 5 ft (1.5 m) or part thereof in plinth	Cu.m.	212.30	212.30	11.7.4
		higher than 5 ft (1.5m)	Cu.ft.	6.00	6.00	
11-8		Extra for every additional 6 ft (2m) or part thereof for arch	Cu.m.	285.50	328.30	11.80
		brick or tile masonry in foundation and basement masonry	Cu.ft.	8.10	9.30	11.90
		deeper than 6ft (2m)				

o .:			Rat	Rate (Rs.)	
Sr. No.	Description	Unit	Labour	Composite	Ref. Tech. Specs.
11-9	Extra for every additional 5 ft (1.5m) or part thereof for arch brick or tile masonry in plinth higher than 5ft (1.5m)	Cu.m. Cu.ft.	212.30 6.00	244.10 6.90	11.80 11.90
11-10	Providing and laying sundried clay bricks set in mud mortar including scaffolding in ground floor superstructure				11.7.2(i) 11.18
a	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,278.90 36.20	9,591.23 271.65	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,439.60 40.75	6,970.50 197.40	
11-11	Providing and laying first class solid burnt brick masonry set in mud mortar including scaffolding, raking out joints and curing in ground floor superstructure.				11.4.1 11.7.2(i) 11.7.4
a	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,998.50 56.60	11,633.12 329.45	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,480.09 41.90	8,210.05 232.50	
11-12	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure				11.4.1 11.7.2(ii)
a	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
i	Cement sand 1 : 2	Cu.m. Cu.ft.	1,998.50 56.60	12,900.90 365.35	
ii	Cement sand 1 : 3	Cu.m. Cu.ft.	1,998.50 56.60	12,401.72 351.20	
iii	Cement sand 1 : 4	Cu.m. Cu.ft.	1,998.50 56.60	11,905.58 337.15	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,998.50 56.60	11,492.91 325.50	
V	Cement sand 1 : 6	Cu.m. Cu.ft.	1,998.50 56.60	11,177.39 316.55	
Vİ	Cement sand 1 : 7	Cu.m. Cu.ft.	1,998.50 56.60	10,856.54 307.45	
vi	i Cement sand 1 : 8	Cu.m. Cu.ft.	1,998.50 56.60	10,541.32 298.55	

				Rat	e (Rs.)	Ref. Tech.
Sr. No	ο.	Description	Unit	Labour	Composite	Specs.
					-	
		Above 4.5" (115mm) nominal thick brickwork				
	i)	Cement sand 1 : 2	Cu.m.	1,583.70	12,517.96	
			Cu.ft.	44.85	354.50	
	::\	Cement sand 1 : 3	Cu.m.	1,583.70	11 027 20	
	11)	Cernent sand 1.3	Cu.ft.	44.85	11,937.38 338.05	
		(-0-)	Od.it.	44.03	330.03	
	iii)	Cement sand 1:4	Cu.m.	1,583.70	11,324.95	
		M	Cu.ft.	44.85	320.75	
		The second second				
	iv)	Cement sand 1 : 5	Cu.m.	1,583.70	10,857.95	
		JAMMU & KASHIM	Cu.ft.	44.85	307.50	
	v)	Cement sand 1 : 6	Cu.m.	1,583.70	10,438.55	
	٠,	Somer said 1.5	Cu.ft.	44.85	295.65	
	vi)	Cement sand 1 : 7	Cu.m.	1,583.70	10,110.82	
			Cu.ft.	44.85	286.35	
			•	4 500 70	0.704.40	
	VII	Cement sand 1 : 8	Cu.m. Cu.ft.	1,583.70 44.85	9,781.48 277.00	
			Cu.it.	44.03	277.00	
11-13		Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork and its removal, raking out joints and curing in ground floor superstructures.				11.80
	-\	Linto 4.5" (445 may) in agricul thick brick work	C	40.55	0.000.07	
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	49.55 1.40	2,236.87 63.35	
			Ou.it.	1.40	00.00	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	256.95	2,144.80	
			Cu.ft.	7.30	60.75	
11-14		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing in ground floor				11.80 11.90
		superstructures.				
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	3,575.35	4,082.38	
	-		Cu.ft.	101.25	95.35	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	3,160.55	3,366.54	
			Cu.ft.	89.50	115.60	
11-15		Extra for masonry in pillars and columns in foundation				11.18
	٥,	Poetengular or equare chang	Cu ~~	1 005 70	1 400 00	
	a)	Rectangular or square shape	Cu.m. Cu.ft.	1,095.70 31.05	1,490.92 42.20	
			ou.it.	01.00	72.20	
			Gu.ii.	31.00	72.20	

				Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	b)	Round shape	Cu.m.	2,431.60	2,958.00	
	,	·	Cu.ft.	68.85	83.75	
11-16		Extra for masonry in pillars and cloumns in ground floor				11.7.4
		superstructure				
	a)	Rectangular or square shape	Cu.m.	1,170.42	2,218.95	
	,		Cu.ft.	33.15	62.85	
		(Na	CONTRACTOR SANC			
	b)	Round shape	Cu.m.	2,264.61	4,195.83	
	,	Z S	Cu.ft.	64.15	118.85	
		AMMU & KASHM	X2222X444			
11-17		Extra for masonry of any description in steps.	Cu.m.	702.04	702.04	11.17.4
		Zama ioi massany aran'i	Cu.ft.	19.90	19.90	
			•	10.00	10.00	
11-18		Extra for masonry of any description for bonding old and new	Cu.m.	322.90	462.40	11.11
11 10		masonry including making recesses as required (New	Cu.ft.	9.15	13.10	
		masonry inserted in old masonry to be measured)	Ou.it.	5.15	15.10	
11-19		Providing and laying first class burnt brick honey comb				11.10
11-19		masonry including scaffolding, raking out joints where				11.10
		required and curing in ground floor superstructure (opening				
		not to be deducted for the purpose of measurement).				
	a)	Upto 4.5" (115 mm) nominal thick brick work				
		Cement sand 1:2	Cu.m.	1,252.80	9,874.10	
	',	ocmone sand 1.2	Cu.ft.	35.50	279.65	
			Cu.it.	33.30	279.00	
	ii۱	Cement sand 1:3	Cu.m.	1,252.80	9,713.60	
	")	Cement sand 1.5	Cu.ft.	35.50	275.10	
			Cu.it.	33.30	273.10	
	:::\	Cement sand 1:4	Cu.m.	1,252.80	9,539.70	
	111)	Cement sand 1.4		· ·		
			Cu.ft.	35.50	270.15	
	j, A	Coment cand 1 · 5	C ~	1 252 00	0.420.05	
	ıv)	Cement sand 1 : 5	Cu.m.	1,252.80	9,438.25 267.30	
			Cu.ft.	35.50	207.30	
	٠,٠	Coment and 1 · 6	Cu ~	1 252 00	0.265.00	
	V)	Cement sand 1 : 6	Cu.m.	1,252.80	9,365.80	
			Cu.ft.	35.50	265.25	
	۷:.,	Coment and 1 : 7	C	1 050 00	0.220.25	
	VI)	Cement sand 1 : 7	Cu.m.	1,252.80	9,322.35	
		Company and 4 + 0	Cu.ft.	35.50	264.00	
	VII	Cement sand 1:8	Cu.m.	1,252.80	9,278.85	
	, ,	Above 4.58 (445mm) months ald the little in	Cu.ft.	35.50	262.80	
		Above 4.5" (115mm) nominal thick brickwork	0	4 005 05	F 470 00	
	I)	Cement sand 1 : 2	Cu.m.	1,225.35	5,473.68	
			Cu.ft.	34.70	155.00	

C: N		Description	l lm:4	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	ii)	Cement sand 1 : 3	Cu.m.	1,225.35	5,195.90	
			Cu.ft.	34.70	147.15	
	:::\	Coment and 4 : 4	Cu.m.	1 225 25	4 0 4 5 9 4	
	111)	Cement sand 1 : 4	Cu.ft.	1,225.35 34.70	4,945.81	
			Gu.it.	34.70	140.05	
	iv)	Cement sand 1 : 5	Cu.m.	1,225.35	4,731.96	
	.,	Committee and 110	Cu.ft.	34.70	134.00	
		(Nam)		"""	1000	
	v)	Cement sand 1 : 6	Cu.m.	1,225.35	4,506.06	
	,	Z. C.	Cu.ft.	34.70	127.60	
		JAMMU & KASHI				
	vi)	Cement sand 1:7	Cu.m.	1,225.35	4,347.11	
			Cu.ft.	34.70	123.10	
	vii	Cement sand 1 : 8	Cu.m.	1,225.35	4,163.65	
			Cu.ft.	34.70	117.90	
11-20		Extra for providing and laying first class burnt brick masonry architrave of required shape of any kind of walls including				11.12
		cutting bricks to required shape, scaffolding, raking out joints				
		and curing in ground floor superstructure.				
	٥/	Linto O" (220 mm) nominal thick heigh work	C	1 640 FF	2.040.70	
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	1,649.55 46.70	3,910.70 110.75	
			Cu.ii.	46.70	110.75	
	h)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	924.02	2,330.60	
	۵)	7 15070 TOTO (O TO TITITI) TIGHTIMICA MINOK SHOK WORK	Cu.ft.	26.15	66.00	
11-21		Extra for providing and laying first class burnt tile masonry				11.80
		architrave of required shape of any kind of walls including				11.12
		cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				
		and caring in ground noor superstructure.				
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,866.80	1,830.67	
			Cu.ft.	52.85	51.85	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,723.93	1,368.86	
			Cu.ft.	48.80	38.75	
11 00		Extra for providing and leving first sless have bridge				11.17
11-22		Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting				11.17
		bricks to required shape, scaffolding, raking out joints and				
	ا۾	curing in ground floor superstructure. Upto 9" (230 mm) nominal thick brick work	Cu.m.	960.14	2,623.65	
	u)	Sp. 5 (200 mm) Homman and Short Work	Cu.ft.	27.20	74.30	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	882.47	2,208.85	
	,	` <i>'</i>	Cu.ft.	25.00	62.55	
				1	J	

Sr. No	_	Decariation	Unit	Rat	e (Rs.)	Ref. Tech.
Sr. NO) .	Description	Unit	Labour	Composite	Specs.
11-23		Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.	0			11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,619.89 45.90	9,962.39 282.15	
11-24	b)	Above 9" (230 mm) nominal thick tile masonry Extra for providing and laying first class burnt brick masonry	Cu.m. Cu.ft.	1,511.28 42.80	11,540.07 326.80	11.12
1124		cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	761.11 21.55	1,598.34 45.25	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	1,867.79 52.90	3,474.09 98.40	
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,619.89 45.90	9,275.57 262.70	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,070.55 30.30	10,650.44 301.65	
11-26	a)	Extra for brick masonry in first floor	Cu.m. Cu.ft.	566.10 16.05	583.05 16.50	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m. Cu.ft.	342.65 9.70	352.95 10.00	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m. Cu.ft.	712.50 20.20	816.20 23.10	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	489.05 13.85	560.25 15.85	11.17
11-28	a)	Extra for honey comb masonry in first floor	Cu.m. Cu.ft.	419.70 11.90	432.25 12.25	11.10
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	342.65	352.95	

			Rat	e (Rs.)	Ref. Tech.
Sr. No	Description	Unit	Labour	Composite	Specs.
		Cu.ft.	9.70	10.00	
11-29	Providing and laying first class brick masonry in steining of walls including scaffolding and curing upto 10 ft (3 m) depth.				11.70
	a) Upto 13.5" (345 mm) nominal thick brick masonry				
	i) Cement sand 1 : 2	Cu.m.	2,068.65	9,966.99	
	(S) E(S)	Cu.ft.	58.60	282.25	
	ii) Cement sand 1 : 3	Cu.m.	2,068.65	9,576.79	
	7 6 7 7	Cu.ft.	58.60	271.20	
	ii) Cement sand 1 : 4	Cu.m.	2,068.65	9,233.15	
	THING &	Cu.ft.	58.60	261.50	
	v) Cement sand 1 : 5	Cu.m.	2,068.65	8,879.19	
	onicin dana 1.0	Cu.ft.	58.60	251.45	
	v) Cement sand 1 : 6	Cu.m.	2,068.65	8,533.65	
		Cu.ft.	58.60	241.70	
	i) Cement sand 1 : 7	Cu.m.	2,068.65	8,283.00	
		Cu.ft.	58.60	234.60	
	vii Cement sand 1 : 8	Cu.m.	2,068.65	8,515.31	
		Cu.ft.	58.60	241.15	
	Above 13.5" (345 mm) nominal thick brick masonry				
	i) Cement sand 1 : 2	Cu.m.	1,577.60	9,075.97	
		Cu.ft.	44.70	257.05	
	ii) Cement sand 1 : 3	Cu.m.	1,577.60	8,787.28	
		Cu.ft.	44.70	248.85	
	ii) Cement sand 1 : 4	Cu.m.	1,577.60	8,519.79	
		Cu.ft.	44.70	241.30	
	v) Cement sand 1 : 5	Cu.m.	1,577.60	8,363.76	
		Cu.ft.	44.70	236.85	
	v) Cement sand 1 : 6	Cu.m.	1,577.60	8,252.31	
		Cu.ft.	44.70	233.70	
	(i) Cement sand 1 : 7	Cu.m.	1,577.60	8,185.45	
		Cu.ft.	44.70	231.80	
	/ii Cement sand 1 : 8	Cu.m.	1,577.60	8,118.55	
	1	Cu.ft.	44.70	229.90	
				2.22	
<u> </u>	L		l		

			Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
c)	Extra for every additional 5 ft (1.5 m) depth or part thereof for	Cu.m.	261.10	268.90	
	brick masonry in steining of walls.	Cu.ft.	7.40	7.60	
11-30	Providing and laying first class burnt brick masonry cavity				11.14
	walls bonded with wall ties of approved design at required horizontal and vertical spacings including scaffolding, raking				
	out joints and curing in ground floor superstructure but				
	excluding the cost of wall ties (No deduction will be made				
	from the measurement for cavity in the wall).				
a)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (415 mm) wall width on either side.				
		0			
I)	Cement sand 1:2	Cu.m.	2,514.75	11,695.70	
	AMMU & KA	Cu.ft.	71.20	331.25	
ii)	Cement sand 1:3	Cu.m.	2,514.75	11,453.40	
")	ocinion sand 1.5	Cu.ft.	71.20	324.35	
		Ou.i	7 1.20	02 1.00	
iii)	Cement sand 1 : 4	Cu.m.	2,514.75	11,190.85	
,		Cu.ft.	71.20	316.95	
iv)	Cement sand 1 : 5	Cu.m.	2,514.75	11,037.70	
		Cu.ft.	71.20	312.60	
v)	Cement sand 1 : 6	Cu.m.	2,514.75	10,928.30	
		Cu.ft.	71.20	309.50	
		•	0.544.75	40 000 70	
VI)	Cement sand 1:7	Cu.m. Cu.ft.	2,514.75 71.20	10,862.70 307.65	
		Cu.it.	71.20	307.03	
vii	Cement sand 1 : 8	Cu.m.	2,514.75	10,797.05	
-		Cu.ft.	71.20	305.80	
b)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm)				
	wall width on one side and 9" (230 mm) wall width on the				
i)	other side. Cement sand 1 : 2	Cu.m.	2,667.25	12,616.30	
,		Cu.ft.	75.55	357.30	
ii)	Cement sand 1:3	Cu.m.	2,667.25	12,317.35	
		Cu.ft.	75.55	348.85	
iii)	Cement sand 1:4	Cu.m.	2,667.25	11,993.40	
		Cu.ft.	75.55	339.65	
;, A	Coment cand 1 · 5	Cu ~	2 667 25	11 004 40	
IV)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,667.25 75.55	11,804.40 334.30	
		Gu.II.	10.00	JJ4.JU	
v)	Cement sand 1 : 6	Cu.m.	2,667.25	11,669.40	
\ ,		Cu.ft.	75.55	330.50	
		Cu.ft.	/5.55	330.50	

			Rat	e (Rs.)	Sudh Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
			Luboui	Composite	•
vi)	Cement sand 1 : 7	Cu.m.	2,667.25	11,588.45	
		Cu.ft.	75.55	328.20	
		_			
vii	Cement sand 1 : 8	Cu.m.	2,667.25	11,507.45	
۵۱	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230 mm)	Cu.ft.	75.55	325.90	
()	wall width on either side.				
i)	Cement sand 1:2	Cu.m.	2,383.60	13,011.85	
,		Cu.ft.	67.50	368.50	
	E. Just				
ii)	Cement sand 1:3	Cu.m.	2,383.60	12,581.10	
		Cu.ft.	67.50	356.30	
		_			
iii)	Cement sand 1 : 4	Cu.m.	2,383.60	12,114.40	
		Cu.ft.	67.50	343.10	
iv/)	Cement sand 1 : 5	Cu.m.	2,383.60	11,842.10	
10)	Cernent Sand 1.5	Cu.ft.	67.50	335.40	
		0	07.00	000110	
v)	Cement sand 1:6	Cu.m.	2,383.60	11,647.65	
		Cu.ft.	67.50	329.85	
vi)	Cement sand 1 : 7	Cu.m.	2,383.60	11,530.95	
		Cu.ft.	67.50	326.55	
vii	Cement sand 1 : 8	Cu.m.	2,383.60	11,414.25	
VII	ocinicit sand 1.0	Cu.ft.	67.50	323.25	
				5=5:=5	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5" (115mm) wall width on one side and 13.5" (345mm) wall width on other				
i)	side. Cement sand 1 : 2	Cu.m.	2,591.00	12,952.10	
[Cu.ft.	73.40	366.80	
ii)	Cement sand 1 : 3	Cu.m.	2,591.00	12,622.95	
		Cu.ft.	73.40	357.50	
,,,,	Compate and 1 : 4	Cu	2 504 00	10.000.05	
"")	Cement sand 1 : 4	Cu.m. Cu.ft.	2,591.00 73.40	12,266.25 347.40	
		Ou.ii.	7 3.40	347.40	
I iv)	Cement sand 1:5	Cu.m.	2,591.00	12,058.15	
<u> </u>		Cu.ft.	73.40	341.50	
v)	Cement sand 1 : 6	Cu.m.	2,591.00	11,909.55	
		Cu.ft.	73.40	337.30	
/:.,	Coment and 1 : 7	Cu ~	2 504 00	11 000 05	
VI)	Cement sand 1 : 7	Cu.m.	2,591.00	11,820.35	

C 1:	_	D	1124	Rat	e (Rs.)	Ref. Tech.
Sr. N	0.	Description	Unit	Labour	Composite	Specs.
			Cu.ft.	73.40	334.75	
	vii	Cement sand 1:8	Cu.m.	2,591.00	11,731.20	
			Cu.ft.	73.40	332.25	
	e)	Extra for brick masonry in cavity walls in first floor	Cu.m.	642.20	647.85	
		(*) [893]	Cu.ft.	18.20	18.35	
			•			
	f)	Extra for brick masonry in cavity walls in every additional floor above first floor	Cu.m.	411.00	414.60	
		above mat noor	Cu.ft.	11.65	11.75	
11-31		Providing and laying first class hollow burnt brick masonry in				11.70
11-31		walls including scaffolding, raking out joints and curing in				11.70
		ground floor superstructure.				11.10
	a)	Upto 4.5" (115 mm) nominal thick brick work				
		Cement sand 1 : 2	Cu.m.	2,074.63	14,599.35	
	,		Cu.ft.	58.75	413.45	
	ii)	Cement sand 1 : 3	Cu.m.	2,074.63	13,066.00	
			Cu.ft.	58.75	370.05	
	iii)	Cement sand 1 : 4	Cu.m.	2,074.63	12,905.10	
			Cu.ft.	58.75	365.50	
	iv)	Cement sand 1 : 5	Cu.m.	2,074.63	12,811.25	
			Cu.ft.	58.75	362.80	
	v)	Cement sand 1 : 6	Cu.m.	2,074.63	12,744.20	
	٧)	ochioni sand 1.0	Cu.ft.	58.75	360.90	
			ou.i	00.70	000.00	
	vi)	Cement sand 1 : 7	Cu.m.	2,074.63	12,703.95	
	,		Cu.ft.	58.75	359.80	
	vii	Cement sand 1 : 8	Cu.m.	2,074.63	12,663.70	
			Cu.ft.	58.75	358.65	
	,	Above 4.5" (115mm) nominal thick brickwork		4 0=0 :=	44 000 ==	
	i)	Cement sand 1 : 2	Cu.m.	1,953.47	14,220.05	
			Cu.ft.	55.30	402.70	
	įίλ	Cement sand 1 : 3	Cu.m.	1,953.47	13,007.10	
	")	omon dana 1.0	Cu.ft.	55.30	368.35	
			Ou.it.	00.00	000.00	
	iii)	Cement sand 1 : 4	Cu.m.	1,953.47	12,762.85	
	,		Cu.ft.	55.30	361.45	
				I	I	

			Rat	e (Rs.)	SUGNI Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1:5	Cu.m.	1,953.47	12,620.35	
		Cu.ft.	55.30	357.40	
,		C	4 050 47	40 540 55	
(V)	Cement sand 1 : 6	Cu.m.	1,953.47	12,518.55	
		Cu.ft.	55.30	354.55	
vi)	Cement sand 1:7	Cu.m.	1,953.47	12,457.50	
V1)	Cernetit Sand 1.7	Cu.ft.	55.30	352.80	
		Od.it.	00.00	002.00	
vii	Cement sand 1:8	Cu.m.	1,953.47	12,396.45	
	7.	Cu.ft.	55.30	351.05	
	Droviding and loving first class perferated brick masons in				
11-32	Providing and laying first class perforated brick masonry in				11.10
a)	Upto 4.5" (115 mm) nominal thick brick work				
	Cement sand 1 : 2	Cu.m.	2,384.24	13,988.20	
,		Cu.ft.	67.50	396.15	
ii)	Cement sand 1:3	Cu.m.	2,384.24	13,306.40	
		Cu.ft.	67.50	376.85	
iii)	Cement sand 1 : 4	Cu.m.	2,384.24	13,058.50	
		Cu.ft.	67.50	369.80	
iv)	Cement sand 1 : 5	Cu.m.	2,384.24	12,913.90	
		Cu.ft.	67.50	365.75	
W	Cement sand 1 : 6	Cu.m.	2,384.24	12,810.60	
v)	Cement Sand 1.0	Cu.ft.	67.50	362.80	
		Ou.it.	07.50	302.00	
vi)	Cement sand 1:7	Cu.m.	2,384.24	12,748.65	
,		Cu.ft.	67.50	361.05	
vii	Cement sand 1:8	Cu.m.	2,384.24	12,686.65	
		Cu.ft.	67.50	359.30	
	Above 4.5" (115mm) nominal thick brickwork				
i)	Cement sand 1:2	Cu.m.	2,245.47	13,769.15	
		Cu.ft.	63.60	389.95	
			0045 45	40.450.50	
li)	Cement sand 1:3	Cu.m.	2,245.47	13,159.50	
		Cu.ft.	63.60	372.70	
;::\	Coment cand 1 : 4	Cum	2 245 47	12 202 05	
"")	Cement sand 1 : 4	Cu.m. Cu.ft.	2,245.47 63.60	12,803.05 362.60	
		Gu.II.	03.00	302.00	

Cr. No.	Description	l lni4	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,245.47 63.60	12,595.10 356.70	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,245.47	12,446.60 352.50	
vi)	Cement sand 1:7	Cu.m. Cu.ft.	2,245.47 63.60	12,357.45 349.95	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,245.47 63.60	12,268.35 347.45	
11-33 a)	Extra for hollow and perforated brick masonry in first floor	Cu.m. Cu.ft.	566.10 16.05	583.05 16.50	
b)	Extra for hollow and perforated brick masonry in every additional floor over first floor.	Cu.m. Cu.ft.	342.65 9.70	352.95 10.00	
11-34	Providing and laying fabric steel reinforcement 1" (25 mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embeded in every third horizontal course in basement, plinth and ground floor.	Kg. Lb.	19.20 8.70	161.55 73.30	11.15
11-35	Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.	Ton Tonne	8,587.30 8,725.15	95,651.05 94,052.16	11.15
11-36	Providing and laying hoop iron reinforcement in brick work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Kg. Lb.	24.95 11.30	146.15 66.30	11.15
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20 mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	Kg. Lb.	28.45 12.90	145.95 66.20	11.14.3
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Tonne Ton	1,454.85 1,478.20	88,447.30 89,866.90	11.15
11-39	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	28.10 12.75	149.35 67.75	11.15
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in first	Kg. Lb.	4.95 2.25	5.35 2.45	11.15

Sr. No.		Description	11	Rate (Rs.)		Ref. Tech.
Sr. No	o.	Description	Unit	Labour	Composite	Specs.
	b)	Providing and placing hoop iron in steining of brick work in	Kg.	3.00	3.25	
		wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Lb.	1.35	1.45	
11-41		Extra for mild steel or hoop iron reinforcement in steining of	Kg.	5.45	5.90	11.15
		brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.	Lb.	2.45	2.70	71.10
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,691.25	15,168.60	
	,		Cu.ft.	104.55	429.60	
			10000-10000-0000			
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m. Cu.ft.	3,172.75 89.85	10,976.85 310.85	
11-43		Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,207.50	18,295.75	
		places.	Cu.ft.	119.15	518.15	
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	3,689.00	17,906.90	
			Cu.ft.	104.45	507.15	
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,691.25	15,677.20	
		places.	Cu.ft.	104.55	444.00	
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,172.75	15,115.45	
		places.	Cu.ft.	89.85	428.10	
11-45		Providing and laying fire brick lining in arches for fire places				11.19
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	4,207.50 119.15	16,750.80 474.40	

0 11		Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No).	Description	Unit	Labour	Composite	Specs.
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m.	3,689.00	16,138.05	
			Cu.ft.	104.45	457.05	
		AC COST TRANSPORT TO PRODUCE TO				
11-46	a)	Extra for first floor over item 11-42 to 11-45	Cu.m.	566.10	583.05	
			Cu.ft.	16.05	16.50	
		(*) [B]g				
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	342.65	352.95	
		46(a)	Cu.ft.	9.70	10.00	
11-47		Providing and laying reinforced first class burnt bricks set in		2,327.15	15,174.85	11.70
		cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of	Cu.ft.	65.90	429.75	
		reinforcement in basement, plinth and ground floor.				
		, , , , , , , , , , , , , , , , , , ,				
44.45						
11-48		Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded				
		shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4				
		including formwork and its removal, compacting, curing but				
		excluding the cost of reinforcement in basement and ground floor.				
		illoof.				
	a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs	Cu.m.	3,351.95	12,570.05	
		and 1.5" thick cover on top.	Cu.ft.	94.95	356.00	
	b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C.	Cu.m.	2,327.15	11,199.52	
		ribs and 1.5" thick cover on top.	Cu.ft.	65.90	317.20	
	c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5"	Cu.m.	2,107.55	10,384.66	
		thick cover on top and 4 brick panel laid in cement sand mortar 1:3.	Cu.ft.	59.70	294.10	
		mortal 1.5.				
11-49		Providing and laying reinforced first class burnt bricks set in				11.70
		cement sand mortar 1:3 in cantilever slab, sun shade etc.				
		including formwork and its removal curing but excluding the				
		cost of reinforcement in basement and ground floor.				
	٥)	3" nominal thick cantilever slab and sun shade etc.	Cu ~~	2 024 76	17 000 00	
	a)	o nominai inick camilever siad and sun snade etc.	Cu.m.	2,931.76	17,989.22 509.45	
			Cu.ft.	83.05	JU9.45	
	b١	4.5" (115mm) nominal thick cantilever slab and sun shade	Cu.m.	2,467.39	15,955.68	
	IJ)	T.O (110/11111) Homina unok cambevel siab and sull shade	Cu.ft.	69.90	451.85	
			Ju.it.	55.50	+01.00	
11-50		Providing and laying reinforced first class burnt bricks set in	Cu.m.	3,377.96	18,125.45	11.70
		cement sand mortar 1:3 in stair case waist slab and landing			,	-
		of required section including scaffolding and formwork and its				
		removal, curing but excluding the cost of reinforcement in basement and ground floor.				
			Cu.ft.	95.65	513.30	

Sr. No.		Description	l l m i t	Rate (Rs.)		Ref. Tech.
Sr. No	ο.	Description	Unit	Labour	Composite	Specs.
11-51	a)	Extra for R.B. masonry for first floor.	Cu.m. Cu.ft.	276.80 7.85	356.38 10.10	
	b)	Extra for every additional floor above first floor over item 11-	Cu.m. Cu.ft.	276.80 7.85	285.10 8.05	
11-52		Extra labour for profile and flared out walls. Extra labour for pucca brick work in piers and abutment	Cu.m. Cu.ft.	450.65 12.75	464.15 13.15	
11-53		Extra labour for pucca brick work in piers and abutment.				
	a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m. Cu.ft.	350.00 9.90	360.50 10.20	
	b)	Above 20 ft (6 m) height	Cu.m. Cu.ft.	651.95 18.45	671.50 19.00	
11-54		Extra to face work 4.5" (115 mm) nominal thick using special bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.m. Cu.ft.	124.45 3.50	136.89 3.90	
11-55		Extra for dressing or chamfering bricks.				
	a)	Special architectural bricks	% Nos.	750.30	750.30	
	b)	All other purposes	% Nos.	375.15	375.15	
11-56		Providing and laying ghilafi brick work 13.5" (345mm) nominal thick including scaffolding and raking out joints with 1:5 mortar				11.20
	a)	Foundation, basement and plinth	Cu.m. Cu.ft.	1,516.25 42.95	9,710.85 275.00	
	b)	Walls in superstructure	Cu.m. Cu.ft.	1,597.05 45.25	9,791.70 277.30	
11-57		Providing and laying first class burnt bricks flooring or pitching dry bricks laid flat.	Cu.m. Cu.ft.	610.00 17.30	10,950.70 310.15	14.80
11-58		Providing pise wall (mud walling) in superstructure.	Cu.m. Cu.ft.	585.60 16.60	8,515.60 241.15	11.7.2(A)
11-59		Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	246.40	246.40	4.10
11-60		Scraping bricks dismantled from pacca masonry.	% Nos.	475.20	475.20	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
31. NO.			Labour	Composite	Specs.
					4.10
11-61	Supplying and filling sand under floor or plugging in wells.with	Cu.m.	354.43	1,265.80	
	lead upto 800 ft (250m)	Cu.ft.	10.05	35.85	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m.	725.90	1,052.03	
	(*) pt/s	Cu.ft.	20.55	29.80	
11-63	Replacing Kallar eaten bricks	Each	41.50	67.50	
11-64	Repairing corners of bridges and other hydraulic masonry	Each	414.80	934.90	
11-65	Extra labour for drains of bath rooms etc.	R.M.	103.70	103.70	
		R.ft.	31.60	31.60	
11-66	Extra work for Marrow corners.	Each	207.40	241.55	
44.07		C	00.00	04.00	11.7.4.4 (c)
11-67	Extra for first class burnt solid or hollow block or tile masonry of any description in any floor or other than building for every	Cu.m.	80.20	94.60	44.70
	1.50 m. height or part thereof beyond 4.5m.	Cu.ft.	2.25	2.70	11.70
11-68	Extra for reinforcement in brick work of any description for	Tonne	1,483.50	1,513.20	
	every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.	Ton	1,507.30	1,537.50	5.40