

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-1	Boring for tubewell in all types of soil except shingle, gravel and rock from ground bed to 100ft (30m) depth including sinking and withdrawing casing pipe & disposal of excavated material within 100ft (30m)			
a)	3" (75 mm) inner dia.	R.M. R.ft.	306.60 93.45	328.25 100.05
b)	4" (100 mm) inner dia.	R.M. R.ft.	459.90 140.20	492.40 150.10
c)	5" (125 mm) inner dia.	R.M. R.ft.	689.85 210.25	738.60 225.15
d)	6" (150 mm) inner dia.	R.M. R.ft.	1034.80 315.40	1107.90 337.70
e)	8" (200 mm) inner dia.	R.M. R.ft.	1552.20 473.10	1661.85 506.55
f)	10" (250 mm) inner dia.	R.M. R.ft.	1940.25 591.40	2077.30 633.15
g)	12" (300 mm) inner dia.	R.M. R.ft.	2425.30 739.25	2596.65 791.45
h)	15" (375 mm) inner dia.	R.M. R.ft.	3031.65 924.05	3245.80 989.35
i)	18" (450 mm) inner dia.	R.M. R.ft.	3789.55 1155.05	4057.25 1236.65
27-2	Boring for tubewell in all types of soil except shingle, gravel and rock from depth 100 ft. to 200 ft. (30m to 60m.) below ground level including sinking and withdrawing of casing pipe			
a)	5" (125 mm) inner dia.	R.M. R.ft.	1172.75 357.45	1255.60 382.70
b)	6" (150 mm) inner dia.	R.M. R.ft.	1655.70 504.65	1772.65 540.30
c)	8" (200 mm) inner dia.	R.M. R.ft.	2017.85 615.05	2160.40 658.50
d)	10" (250 mm) inner dia.	R.M. R.ft.	2328.30 709.65	2492.75 759.80
e)	12" (300 mm) inner dia.	R.M. R.ft.	2789.10 850.15	2986.15 910.20
f)	15" (375 mm) inner dia.	R.M. R.ft.	3486.40 1062.65	3732.65 1137.75
g)	18" (450 mm) inner dia.	R.M. R.ft.	4358.00 1328.35	4665.85 1422.15

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-3	Boring for tubewell in all types of soil except shingle, gravel and rock from depth 200 ft. to 300 ft. (60m to 90m.) below ground level including sinking and withdrawing of casing pipe			
a)	5" (125 mm) inner dia.	R.M. R.ft.	1583.20 482.55	1695.05 516.65
b)	6" (150 mm) inner dia.	R.M. R.ft.	2069.65 630.85	2393.10 729.45
c)	8" (200 mm) inner dia.	R.M. R.ft.	2522.30 768.80	2700.50 823.10
d)	10" (250 mm) inner dia.	R.M. R.ft.	2793.95 851.60	2991.30 911.75
e)	12" (300 mm) inner dia.	R.M. R.ft.	3346.90 1020.15	3583.40 1092.25
f)	15" (375 mm) inner dia.	R.M. R.ft.	3835.05 1168.95	4105.90 1251.50
g)	18" (450 mm) inner dia.	R.M. R.ft.	4793.80 1461.15	5132.45 1564.40
27-4	Boring for tubewell in all types of soil except shingle, gravel and rock from depth 300 ft. to 400 ft. (90m to 120m) below ground level including sinking and withdrawing of casing pipe			
a)	8" (200 mm) inner dia.	R.M. R.ft.	3026.75 922.55	3240.60 987.75
b)	10" (250 mm) inner dia.	R.M. R.ft.	3352.75 1021.95	3589.55 1094.10
c)	12" (300 mm) inner dia.	R.M. R.ft.	4016.30 1224.20	4300.10 1310.70
d)	15" (375 mm) inner dia.	R.M. R.ft.	4602.05 1402.70	4927.10 1501.80
e)	18" (450 mm) inner dia.	R.M. R.ft.	5752.55 1753.40	6158.95 1877.25
27-5	Direct rotary and/or reverse rotary drilling for exploratory holes for 4" to 5" (100mm to 125mm) dia. in any kind of soil except shingle, gravel or rock.	R.M. R.ft.	- -	5064.80 1543.75
27-6	Direct rotary and/or reverse rotary drilling for exploratory holes for 4" to 5" (100mm to 125mm) dia. in shingle, gravel or rock.	R.M. R.ft.	- -	10129.60 3087.55
27-7	Direct rotary and/or reverse rotary drilling of bore for tubewells including extraction of casing pipes in all types of soil except shingle, gravel and rock.			
a)	From ground level upto 250 ft. (75 m) below ground level			
i)	15" to 18" (375 mm to 450 mm) inner dia.	R.M. R.ft.	- -	7122.75 2171.05

Sr. No.	Description	Unit	Rate (Rs.)		
			Labour	Composite	
27-8	ii) 20" to 30" (500 mm to 750 mm) inner dia.	R.M. R.ft.	- -	8121.00 2475.30	
	b) Exceeding 250 ft (75 m.) depth below ground level				
	i) 15" to 18" (375 mm to 450 mm) inner dia.	R.M. R.ft.	- -	8191.15 2496.70	
	ii) 20" to 30" (500 mm to 750 mm) inner dia.	R.M. R.ft.	- -	9339.15 2846.60	
	a) From ground level upto 250 ft. (75 m) below ground level				
	i) 15" to 18" (375 mm to 450 mm) inner dia.	R.M. R.ft.	- -	7122.75 2171.05	
	ii) 20" to 30" (500 mm to 750 mm) inner dia.	R.M. R.ft.	- -	8121.00 2475.30	
	b) Exceeding 250 ft (75 m.) depth below ground level				
	i) 15" to 18" (375 mm to 450 mm) inner dia.	R.M. R.ft.	- -	8191.15 2496.70	
	ii) 20" to 30" (500 mm to 750 mm) inner dia.	R.M. R.ft.	- -	9339.15 2846.60	
	27-9	Providing box 48"x 30"x 9" (1.2m x 0.75m x 0.23m) of deodar wood planks with compartment 4" x 4" (100mm x 100mm) including locking arrangement for preserving strata samples from borehole and painted with two coats of paint. The top and bottom of the box to be of 1/2" (12mm) planks, sides and compartments to be of 1/4" (6mm) planks.	Each	672.55	11428.50
	27-10	Furnishing sample of water from bore hole.	Per set of two bottles	597.80	768.60
27-11	Providing and installing brass strainer in tubewell bore hole including specials, sockets and studs of the nominal inner diameter.				
	a) 2" (50 mm) dia. and 5/32" (4 mm) wall thickness	R.M. R.ft.	47.75 14.55	5647.55 1721.40	
	b) 3" (75 mm) dia. and 5/32" (4 mm) wall thickness	R.M. R.ft.	47.75 14.55	7514.15 2290.35	
	c) 4" (100 mm) dia. and 3/16" (5 mm) wall thickness	R.M. R.ft.	47.75 14.55	9380.75 2859.30	
	d) 5" (125 mm) dia. and 3/16" (5 mm) wall thickness	R.M. R.ft.	47.75 14.55	10625.15 3238.60	
	e) 6" (150 mm) dia. and 3/16" (5 mm) wall thickness	R.M. R.ft.	47.75 14.55	11247.35 3428.25	
	f) 7" (175 mm) dia. and 3/16" (5 mm) wall thickness	R.M. R.ft.	47.75 14.55	11869.55 3617.90	

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
g)	8" (200 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	47.75	15602.75
		R.ft.	14.55	4755.80
h)	9" (225 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	47.75	16847.15
		R.ft.	14.55	5135.05
i)	10" (250 mm) dia. with 3/16" (5 mm) wall thickness	R.M.	47.75	18091.55
		R.ft.	14.55	5514.35
j)	10" (250 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	18091.55
		R.ft.	14.55	5514.35
k)	12" (300 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	19335.95
		R.ft.	14.55	5893.65
l)	15" (375 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	24313.55
		R.ft.	14.55	7410.85
m)	18" (450 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	33646.55
		R.ft.	14.55	10255.60
n)	20" (500 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	43601.75
		R.ft.	14.55	13290.00
o)	22" (550 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	47.75	48579.35
		R.ft.	14.55	14807.15
27-12	Providing and installing M.S. bail plug in tubewell bore hole 1.5 ft. (50cm) long and of the nominal inner diameter.			
a)	2" (50 mm) inner dia.	Each	87.55	585.35
b)	3" (75 mm) inner dia.	Each	87.55	747.10
c)	4" (100 mm) inner dia.	Each	87.55	821.75
d)	5" (125 mm) inner dia.	Each	87.55	1020.85
e)	6" (150 mm) inner dia.	Each	87.55	1145.30
f)	7" (175 mm) dia	Each	87.55	1331.95
g)	8" (200 mm) inner dia.	Each	87.55	1568.40
h)	9" (225 mm) inner dia.	Each	87.55	1618.15
i)	10" (250 mm) inner dia.	Each	87.55	1742.60
j)	12" (300 mm) inner dia.	Each	87.55	2103.50
27-13	Providing and installing fibre glass strainer in tubewell bore hole including sockets and solvents.			
a)	8" (200 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	39.80	4209.45
		R.ft.	12.15	1283.05
b)	10" (250 mm) dia. and 0.2" to 0.22" (5 mm to 5.5 mm) wall thickness	R.M.	39.80	4672.75
		R.ft.	12.15	1424.25

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-14	Providing and installing fibre glass bail/end plug in tubewell bore.			
a)	8" (200 mm) inner dia.	Each	39.80	4968.60
b)	10" (250 mm) inner dia.	Each	39.80	5215.05
27-15	Providing and installing fibre glass blank pipe Zamrock or similar make in tubewell bore hole including coupling and jointing with strainer.			
a)	8" (200 mm) dia. and 3/16" (5 mm) wall thickness	R.M. R.ft.	39.80 12.15	3243.15 988.50
b)	10" (250 mm) dia. with 3/16" (5 mm) wall thickness	R.M. R.ft.	47.75 14.55	3613.80 1101.50
c)	14" (350 mm) dia. and 3/16" to 1/4" (5 mm to 6 mm) wall thickness	R.M. R.ft.	47.75 14.55	5665.55 1726.90
27-16	Providing and installing P.V.C. strainer in tubewell bore hole including sockets and solvent Shavyl Karachi or equivalent make of the nominal inner diameter.			
a) Class B				
i)	3" (75 mm) inner dia.	R.M. R.ft.	47.75 14.55	265.55 80.95
ii)	4" (100 mm) inner dia.	R.M. R.ft.	47.75 14.55	358.85 109.40
iii)	5" (125 mm) inner dia.	R.M. R.ft.	59.95 18.25	495.50 151.05
iv)	6" (150 mm) inner dia.	R.M. R.ft.	59.95 18.25	701.80 213.90
v)	8" (200 mm) inner dia.	R.M. R.ft.	98.20 29.95	984.20 300.00
vi)	10" (250 mm) inner dia.	R.M. R.ft.	98.20 29.95	1467.05 447.15
vii)	12" (300 mm) inner dia.	R.M. R.ft.	119.40 36.40	2141.55 652.75
viii)	14" (350 mm) inner dia.	R.M. R.ft.	119.40 36.40	2508.65 764.65
b) Class D				
i)	1.25" (30 mm) inner dia.	R.M. R.ft.	31.85 9.70	140.10 42.70
ii)	1.5" (40 mm) inner dia.	R.M. R.ft.	31.85 9.70	147.60 45.00
iii)	2" (50 mm) inner dia.	R.M. R.ft.	39.80 12.15	207.80 63.35

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
iv)	3" (75 mm) inner dia.	R.M.	47.75	389.95
		R.ft.	14.55	118.85
v)	4" (100 mm) inner dia.	R.M.	47.75	589.05
		R.ft.	14.55	179.55
vi)	5" (125 mm) inner dia.	R.M.	79.60	869.80
		R.ft.	24.25	265.10
vii)	6" (150 mm) inner dia.	R.M.	79.60	1199.55
		R.ft.	24.25	365.65
27-17	Providing and installing P.V.C. elbow Shavyl or equivalent make.			
	a) Class B			
i)	3" (75 mm) inner dia.	Each	23.90	218.00
ii)	4" (100 mm) inner dia.	Each	23.90	272.80
iii)	5" (125 mm) inner dia.	Each	23.90	600.05
iv)	6" (150 mm) inner dia.	Each	31.85	809.60
v)	8" (200 mm) inner dia.	Each	31.85	5865.60
vi)	10" (250 mm) inner dia.	Each	31.85	6851.15
vii)	12" (300 mm) inner dia.	Each	47.75	9847.40
viii)	14" (350 mm) inner dia.	Each	47.75	15291.65
	b) Class D			
i)	1.25" (30 mm) inner dia.	Each	15.90	109.25
ii)	1.5" (40 mm) inner dia.	Each	15.90	137.85
iii)	2" (50 mm) inner dia.	Each	15.90	171.45
iv)	3" (75 mm) inner dia.	Each	23.90	404.65
v)	4" (100 mm) inner dia.	Each	23.90	490.55
vi)	5" (125 mm) inner dia.	Each	23.90	448.25
vii)	6" (150 mm) inner dia.	Each	23.90	736.95
27-18	Providing and installing M.S. blind pipe socketed seamless welded joint or hand welded joint, M.S. reducer where necessary in tubewell bore hole including jointing and welding with strainer of the nominal inner diameter.			
a)	2" (50 mm) dia. and 1/8" (3 mm) wall thickness	R.M.	79.60	783.30
		R.ft.	24.25	238.75
b)	3" (75 mm) dia. and 1/8" (3 mm) wall thickness	R.M.	79.60	1460.90
		R.ft.	24.25	445.30

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
c)	4" (100 mm) dia. and 1/8" (3 mm) wall thickness	R.M.	103.50	1970.10
		R.ft.	31.55	600.50
d)	5" (125 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	103.50	3463.40
		R.ft.	31.55	1055.65
e)	6" (150 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	159.20	4290.60
		R.ft.	48.50	1307.80
f)	7" (175 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	159.20	5273.70
		R.ft.	48.50	1607.45
g)	8" (200 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	180.45	7186.40
		R.ft.	55.00	2190.45
h)	9" (225 mm) dia. and 3/16" (5 mm) wall thickness	R.M.	180.45	8393.50
		R.ft.	55.00	2558.35
i)	10" (250 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	180.45	9637.90
		R.ft.	55.00	2937.65
j)	12" (300 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	238.80	10816.20
		R.ft.	72.80	3296.80
k)	15" (375 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	238.80	14424.95
		R.ft.	72.80	4396.80
l)	18" (450 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	238.80	16416.00
		R.ft.	72.80	5003.65
m)	20" (500 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	278.60	21433.40
		R.ft.	84.90	6533.00
n)	22" (550 mm) dia. and 1/4" (6 mm) wall thickness	R.M.	278.60	25913.25
		R.ft.	84.90	7898.45
27-19	Providing and Installing P.V.C. blind pipe Shavyl or equivalent make in tubewell bore hole and/or laying, cutting, jointing, testing and disinfecting P.V.C. pipe lines in trenches.			
	a) Class B			
i)	3" (75 mm) inner dia.	R.M.	79.60	316.05
		R.ft.	24.25	96.35
ii)	4" (100 mm) inner dia.	R.M.	79.60	415.60
		R.ft.	24.25	126.70
iii)	5" (125 mm) inner dia.	R.M.	119.40	592.30
		R.ft.	36.40	180.55
iv)	6" (150 mm) inner dia.	R.M.	119.40	778.95
		R.ft.	36.40	237.45
v)	8" (200 mm) inner dia.	R.M.	159.20	1241.85
		R.ft.	48.50	378.50

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
vi)	10" (250 mm) inner dia.	R.M.	159.20	1870.25
		R.ft.	48.50	570.05
vii)	12" (300 mm) inner dia.	R.M.	199.00	2625.60
		R.ft.	60.65	800.30
viii)	14" (350 mm) inner dia.	R.M.	199.00	3117.10
		R.ft.	60.65	950.10
b) Class D				
i)	1.25" (30 mm) inner dia.	R.M.	39.80	126.90
		R.ft.	12.15	38.70
ii)	1.5" (40 mm) inner dia.	R.M.	39.80	151.80
		R.ft.	12.15	46.25
iii)	2" (50 mm) inner dia.	R.M.	58.40	226.35
		R.ft.	17.80	69.00
iv)	3" (75 mm) inner dia.	R.M.	58.40	406.85
		R.ft.	17.80	124.00
v)	4" (100 mm) inner dia.	R.M.	79.60	764.05
		R.ft.	24.25	232.90
vi)	6" (150 mm) inner dia.	R.M.	79.60	1742.75
		R.ft.	24.25	531.20
27-20	Testing and development of tubewell of size 6" (150 mm) inner dia. and above continuously			
a)	Upto 1.5 cusecs (0.0425 cumec) discharge	Job	-	36331.05
b)	Above 1.5 cusecs (0.0425 cumec) capacity	Job	-	45413.80
27-21	Shrouding with graded pea gravel 3/8" to 1/8" (10 mm to 3mm) around tubewell bore hole.	Cu.m.	530.70	1384.70
		Cu.ft.	15.05	39.20
27-22	Providing, laying, cutting, jointing, testing and disinfecting C.I. pipe line in trenches with spigot and socket, chaulked lead or comet joints or flanged joints or tyton joints including cost of materials such as lead, comet and yarn. (Cost of specials and their installation not included).			
i)	3" (75 mm) inner dia.	R.M.	31.85	1214.00
		R.ft.	9.70	370.05
ii)	4" (100 mm) inner dia.	R.M.	31.85	1324.00
		R.ft.	9.70	403.55
iii)	6" (150 mm) inner dia.	R.M.	47.75	3780.95
		R.ft.	14.55	1152.45
iv)	8" (200 mm) inner dia.	R.M.	79.60	7546.00
		R.ft.	24.25	2300.05



Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-23	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line III or equivalent make including the cost of specials and cost of painting 2 coats with bitumen to pipes and specials after cleaning and wrapping tightly hessian cloth soaked in Mexphalt composition around pipes.			
	a) Light duty			
	i) 1/2" (15 mm) inner dia.	R.M. R.ft.	31.85 9.70	223.95 68.25
	ii) 3/4" (20 mm) inner dia.	R.M. R.ft.	31.85 9.70	304.75 92.90
	iii) 1" (25 mm) inner dia.	R.M. R.ft.	39.80 12.15	424.35 129.35
	iv) 1.25" (30 mm) inner dia.	R.M. R.ft.	39.80 12.15	536.00 163.35
	v) 1.5" (40 mm) inner dia.	R.M. R.ft.	58.40 17.80	684.85 208.75
	vi) 2" (50 mm) inner dia.	R.M. R.ft.	58.40 17.80	846.10 257.90
	vii) 2.5" (65 mm) inner dia.	R.M. R.ft.	71.65 21.84	1150.90 350.88
	viii) 3" (75 mm) inner dia.	R.M. R.ft.	71.65 21.85	1150.90 350.80
	ix) 4" (100 mm) inner dia.	R.M. R.ft.	71.65 21.85	1336.95 407.50
	b) Medium duty			
	i) 1/2" (15 mm) inner dia.	R.M. R.ft.	31.85 9.70	267.55 81.55
	ii) 3/4" (20 mm) inner dia.	R.M. R.ft.	31.85 9.70	335.75 102.35
	iii) 1" (25 mm) inner dia.	R.M. R.ft.	39.80 12.15	498.80 152.05
	iv) 1.25" (30 mm) inner dia.	R.M. R.ft.	39.80 12.15	622.85 189.85
	v) 1.5" (40 mm) inner dia.	R.M. R.ft.	58.40 17.80	728.25 221.95
	vi) 2" (50 mm) inner dia.	R.M. R.ft.	58.40 17.80	846.10 257.90
	vii) 2.5" (65 mm) inner dia.	R.M. R.ft.	71.65 21.85	1231.50 375.35
	viii) 3" (75 mm) inner dia.	R.M. R.ft.	71.65 21.85	1566.45 477.45

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
ix)	4" (100 mm) inner dia.	R.M.	79.60	2207.05
		R.ft.	24.25	672.70
x)	5" (125 mm) inner dia.	R.M.	98.20	2994.75
		R.ft.	29.95	912.80
xi)	6" (150 mm) inner dia.	R.M.	98.20	3521.95
		R.ft.	29.95	1073.50
27-24	Replacing burst/damaged G.I. pipe line with all excavation, cutting, providing new G.I. medium duty pipe, union, tees, bends, sockets, including threading etc. and painting with 2 coats of bitumen to pipes and specials after cleaning and wrapping tightly hessian cloth soaked in Maxphalt composition around pipes including cost of testing and disinfecting (cost of pipes and all accessories included)			
i)	1/2" (15 mm) inner dia.	R.M.	159.20	394.90
		R.ft.	48.50	120.35
ii)	3/4" (20 mm) inner dia.	R.M.	159.20	463.10
		R.ft.	48.50	141.15
iii)	1" (25 mm) inner dia.	R.M.	159.20	618.20
		R.ft.	48.50	188.45
iv)	1.25" (30 mm) inner dia.	R.M.	159.20	742.25
		R.ft.	48.50	226.25
v)	1.5" (40 mm) inner dia.	R.M.	159.20	829.05
		R.ft.	48.50	252.70
vi)	2" (50 mm) inner dia.	R.M.	159.20	946.90
		R.ft.	48.50	288.60
vii)	2.5" (65 mm) inner dia.	R.M.	159.20	1319.05
		R.ft.	48.50	402.05
viii)	3" (75 mm) inner dia.	R.M.	159.20	1654.00
		R.ft.	48.50	504.15
ix)	4" (100 mm) inner dia.	R.M.	159.20	2286.65
		R.ft.	48.50	697.00
x)	5" (125 mm) inner dia.	R.M.	159.20	3055.75
		R.ft.	48.50	931.40
xi)	6" (150 mm) inner dia.	R.M.	159.20	3582.95
		R.ft.	48.50	1092.10
27-25	Providing, laying, cutting, jointing, testing and disinfecting asbestos cement pipe line in trenches including comet joint and rubber ring.			
a)	Class B working pressure			
i)	3" (75 mm) inner dia.	R.M.	79.60	546.25
		R.ft.	24.25	166.50

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
ii)	4" (100 mm) inner dia.	R.M.	79.60	689.35
		R.ft.	24.25	210.10
iii)	6" (150 mm) inner dia.	R.M.	119.40	1133.60
		R.ft.	36.40	345.55
iv)	8" (200 mm) inner dia.	R.M.	119.40	1208.25
		R.ft.	36.40	368.30
v)	10" (250 mm) inner dia.	R.M.	199.00	1710.95
		R.ft.	60.65	521.50
vi)	12" (300 mm) inner dia.	R.M.	199.00	2358.05
		R.ft.	60.65	718.75
vii)	14" (350 mm) inner dia.	R.M.	278.60	3308.73
		R.ft.	84.90	1008.50
viii)	16" (400 mm) inner dia	R.M.	278.60	4397.55
		R.ft.	84.90	1340.40
ix)	18" (450 mm) inner dia.	R.M.	358.20	4713.60
		R.ft.	109.20	1436.70
x)	20" (500 mm) inner dia.	R.M.	358.20	5335.80
		R.ft.	109.20	1626.35
xi)	24" (600 mm) inner dia.	R.M.	398.05	7242.25
		R.ft.	121.35	2207.45
b) Class C working pressure				
i)	3" (75 mm) inner dia.	R.M.	79.60	384.48
		R.ft.	24.25	117.20
ii)	4" (100 mm) inner dia.	R.M.	79.60	484.03
		R.ft.	24.25	147.55
iii)	6" (150 mm) inner dia.	R.M.	119.40	1002.92
		R.ft.	36.40	305.70
iv)	8" (200 mm) inner dia.	R.M.	119.40	1351.36
		R.ft.	36.40	411.90
v)	10" (250 mm) inner dia.	R.M.	199.00	2202.48
		R.ft.	60.65	671.35
vi)	12" (300 mm) inner dia.	R.M.	199.00	3030.01
		R.ft.	60.65	923.55
vii)	14" (350 mm) inner dia.	R.M.	278.60	4117.57
		R.ft.	84.90	1255.05
viii)	16" (400 mm) inner dia	R.M.	278.60	5523.75
		R.ft.	84.90	1683.65
ix)	18" (450 mm) inner dia.	R.M.	358.20	6965.96
		R.ft.	109.20	2123.25

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
x)	20" (500 mm) inner dia.	R.M. R.ft.	358.20 109.20	12802.20 3902.15
xi)	24" (600 mm) inner dia.	R.M. R.ft.	398.05 121.35	15175.30 4625.50
c)	Class D working pressure			
i)	3" (75 mm) inner dia.	R.M. R.ft.	79.60 24.25	334.70 102.00
ii)	4" (100 mm) inner dia.	R.M. R.ft.	79.60 24.25	583.58 177.90
iii)	6" (150 mm) inner dia.	R.M. R.ft.	119.40 36.40	1189.58 362.60
iv)	8" (200 mm) inner dia.	R.M. R.ft.	119.40 36.40	1936.22 590.15
v)	10" (250 mm) inner dia.	R.M. R.ft.	199.00 60.65	3222.89 982.35
vi)	12" (300 mm) inner dia.	R.M. R.ft.	199.00 60.65	4535.73 1382.50
vii)	14" (350 mm) inner dia.	R.M. R.ft.	278.60 84.90	5666.85 1727.30
viii)	16" (400 mm) inner dia.	R.M. R.ft.	278.60 84.90	7931.66 2417.60
ix)	18" (450 mm) inner dia.	R.M. R.ft.	358.20 109.20	9877.86 3010.80
x)	20" (500 mm) inner dia.	R.M. R.ft.	358.20 109.20	12528.43 3818.70
27-26	Providing, laying, cutting, jointing, testing and disinfecting Ductile iron pipe line in trenches including all fittings and accessories.			
i)	4" (100 mm) inner dia.	R.M. R.ft.	278.60 84.90	1398.60 426.30
ii)	6" (150 mm) inner dia.	R.M. R.ft.	278.60 84.90	2269.65 691.80
iii)	8" (200 mm) inner dia.	R.M. R.ft.	358.20 109.20	2598.15 791.95
iv)	10" (250 mm) inner dia.	R.M. R.ft.	358.20 109.20	3220.30 981.55
v)	12" (300 mm) inner dia.	R.M. R.ft.	517.45 157.70	4250.65 1295.60
vi)	16" (400 mm) inner dia.	R.M. R.ft.	517.45 157.70	5495.05 1674.90

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
vii)	18" (450 mm) inner dia.	R.M.	796.05	6395.85
		R.ft.	242.65	1949.50
viii)	20" (500 mm) inner dia.	R.M.	796.05	7391.35
		R.ft.	242.65	2252.90
ix)	24" (600 mm) inner dia.	R.M.	955.25	8670.55
		R.ft.	291.15	2642.80
27-27	Providing and fixing C.I. specials of class-B such as bends, tees, cross, collars, reducers, tail pieces, flanged spigot, caps, flanged sockets, tapers, angle, branch and plugs including turning threading, facing and fitting for C.I. pipe line.			
a)	Cast iron S.S. specials with spigot and socket joint			
i)	3" to 6" (75 mm to 150 mm) dia.	Kg.	31.85	139.20
		Lb.	14.45	63.15
ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg.	23.90	131.25
		Lb.	10.85	59.55
iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg.	15.90	123.30
		Lb.	7.20	55.95
b)	Cast iron flanged specials with flanged joints			
i)	3" to 6" (75 mm to 150 mm) dia.	Kg.	15.90	123.25
		Lb.	7.20	55.90
ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg.	12.20	119.55
		Lb.	5.55	54.25
iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg.	7.95	115.30
		Lb.	3.60	52.30
c)	Cast iron specials with tyton joints			
i)	3" to 6" (75 mm to 150 mm) dia.	Kg.	7.95	115.30
		Lb.	3.60	52.30
ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg.	7.95	115.30
		Lb.	3.60	52.30
iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg.	7.95	115.30
		Lb.	3.60	52.30
27-28	Providing and fixing C.I. special of BSS, Class-B such as bends, tees, cross, collar, reducers, tail pieces, flanged sockets, flanged spigots, caps, tapers, angle branch and plugs for asbestos cement pipe line with comet joint and rubber ring.			
i)	3" to 6" (75 mm to 150 mm) dia.	Kg.	39.80	147.16
		Lb.	18.05	66.75
ii)	8" to 18" (200 mm to 450 mm) inner dia.	Kg.	28.15	135.49
		Lb.	12.75	61.45
iii)	20" to 24" (500 mm to 600 mm) inner dia.	Kg.	20.17	127.53
		Lb.	9.15	57.85

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-29	Providing and fixing C.I. sluice valve of BSS quality and weight, Class B, for C.I. pipe line and A.C. pipe line including cost of jointing material.			
a)	3" (75 mm) inner dia.	Each	111.45	4491.37
b)	4" (100 mm) inner dia.	Each	111.45	4615.81
c)	6" (150 mm) inner dia.	Each	137.98	6359.98
d)	9" (225 mm) inner dia.	Each	137.98	12505.10
e)	12" (300 mm) inner dia.	Each	199.01	23346.55
f)	15" (375 mm) inner dia.	Each	199.01	38705.26
g)	18" (450 mm) inner dia.	Each	278.62	77291.12
h)	21" (525 mm) inner dia.	Each	278.62	108096.12
i)	24" (600 mm) inner dia.	Each	398.03	169913.09
j)	27" (675 mm) inner dia.	Each	398.03	254539.28
k)	30" (750 mm) inner dia.	Each	477.63	347033.88
27-30	Providing and fixing C.I. sluice valve of BSS quality and weight for asbestos cement pipe line with comet joint and rubber ring including cost of jointing material.			
a)	3" (75 mm) inner dia.	Each	111.45	4576.65
b)	4" (100 mm) inner dia.	Each	111.45	4831.20
c)	6" (150 mm) inner dia.	Each	137.98	6872.38
27-31	Providing and fixing fire hydrants standard pattern 3" (75mm) dia. inlet and 2.5" (65mm) dia screw outlet. BSS quality and weight, cost of jointing material is included.	Each	185.75	1568.01
27-32	Providing and fixing air valve 2.5" (65 mm) inner dia.of BSS quality and weight, cost of jointing material is included.			
a)	Single	Each	398.03	2282.93
b)	Double	Each	398.03	2618.43
27-33	Cutting C.I. pipe and welding spigot or socket flanged or tyton end including finishing ends of pipe.			
a)	3" to 6" (75 mm to 150 mm) dia.	Per 1" dia. of pipe	74.30	74.30
b)	8" to 12" (200 mm to 300 mm) inner dia.	Per 1" dia. of pipe	81.73	81.73
c)	15" to 18" (375 mm to 450 mm) inner dia.	Per 1" dia. of pipe	89.90	89.90

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
27-34	Providing and installing P.V.C. bends of Shayl or equivalent make.			
	a) Class B			
	i) 3" (75 mm) inner dia.	Each	145.94	312.47
	ii) 4" (100 mm) inner dia.	Each	145.94	363.71
	iii) 5" (125 mm) inner dia.	Each	238.82	571.88
	iv) 6" (150 mm) inner dia.	Each	238.82	981.80
	v) 8" (200 mm) inner dia.	Each	318.42	1484.13
	b) Class D			
	i) 1.25" (30 mm) inner dia.	Each	79.61	124.44
	ii) 1.5" (40 mm) inner dia.	Each	79.61	134.70
	iii) 2" (50 mm) inner dia.	Each	119.40	193.70
	iv) 3" (75 mm) inner dia.	Each	119.40	296.20
	v) 4" (100 mm) inner dia.	Each	159.20	485.85
	vi) 5" (125 mm) inner dia.	Each	159.20	882.95
	vii) 6" (150 mm) inner dia.	Each	238.80	1711.95
27-35	Providing and installing P.V.C. tees of Shayl or equivalent make			
	a) Class B			
	i) 3" (75 mm) inner dia.	Each	199.00	521.10
	ii) 4" (100 mm) inner dia.	Each	199.00	695.55
	iii) 5" (125 mm) inner dia.	Each	318.40	1190.70
	iv) 6" (150 mm) inner dia.	Each	318.40	1687.25
	v) 8" (200 mm) inner dia.	Each	557.25	1597.30
	vi) 10" (250 mm) inner dia.	Each	557.25	2738.00
	vii) 12" (300 mm) inner dia.	Each	796.05	4016.85
	viii) 14" (350 mm) inner dia.	Each	796.05	9116.45
	b) Class D			
	i) 1.25" (30 mm) inner dia.	Each	79.61	124.44
	ii) 1.5" (40 mm) inner dia.	Each	79.61	134.70
	iii) 2" (50 mm) inner dia.	Each	119.40	193.70
	iv) 3" (75 mm) inner dia.	Each	119.40	296.20

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
v)	4" (100 mm) inner dia.	Each	159.20	485.85
vi)	5" (125 mm) inner dia.	Each	159.20	882.95
vii)	6" (150 mm) inner dia.	Each	238.80	1711.95
27-36	Providing and installing P.V.C. bail or end plug of Shayvl or equivalent make.			
a) Class B				
i)	3" (75 mm) inner dia.	Each	238.80	440.10
ii)	4" (100 mm) inner dia.	Each	238.80	457.55
iii)	5" (125 mm) inner dia.	Each	318.40	604.25
iv)	6" (150 mm) inner dia.	Each	318.40	821.65
v)	8" (200 mm) inner dia.	Each	557.25	1119.55
vi)	10" (250 mm) inner dia.	Each	557.25	1396.00
vii)	12" (300 mm) inner dia.	Each	716.45	2109.45
viii)	14" (350 mm) inner dia.	Each	716.45	2393.95
b) Class D				
i)	1.25" (30 mm) inner dia.	Each	106.15	165.20
ii)	1.5" (40 mm) inner dia.	Each	106.15	163.85
iii)	2" (50 mm) inner dia.	Each	159.20	259.85
iv)	3" (75 mm) inner dia.	Each	159.20	280.00
v)	4" (100 mm) inner dia.	Each	278.60	446.35
vi)	5" (125 mm) inner dia.	Each	278.60	600.70
vii)	6" (150 mm) inner dia.	Each	318.40	871.30
27-37	Providing and installing P.V.C. tapered core of Shayvl or equivalent make.			
a) Class B				
i)	3" (75 mm) inner dia.	Each	61.05	103.75
ii)	4" (100 mm) inner dia.	Each	61.05	137.30
iii)	5" (125 mm) inner dia.	Each	238.80	330.30
iv)	6" (150 mm) inner dia.	Each	238.80	374.55
v)	8" (200 mm) inner dia.	Each	318.40	501.42
b) Class D				
i)	1.25" (30 mm) inner dia.	Each	71.65	102.15



Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
	ii) 1.5" (40 mm) inner dia.	Each	71.65	114.35
	iii) 2" (50 mm) inner dia.	Each	79.60	140.60
27-38	Providing and installing P.V.C. conduit of Class B or D of Beta or equivalent make			
	a) 1.25" (30 mm) inner dia.	Each	58.40	133.10
	b) 1.5" (40 mm) inner dia.	Each	58.40	168.20
	c) 2" (50 mm) inner dia.	Each	79.60	229.05
	d) 3" (75 mm) inner dia.	Each	79.60	335.80
	e) 4" (100 mm) inner dia.	Each	119.40	517.45
27-39	Providing and installing P.V.C. V socket of Class B or D of Beta or equivalent make.			
	a) 1.25" (30 mm) inner dia.	Each	39.80	123.70
	b) 1.5" (40 mm) inner dia.	Each	39.80	177.05
	c) 2" (50 mm) inner dia.	Each	79.60	262.60
	d) 3" (75 mm) inner dia.	Each	79.60	590.50
	e) 4" (100 mm) inner dia.	Each	119.40	462.55
27-40	Providing and installing P.V.C. crosser of Beta or equivalent make.			
	a) Class B			
	i) 3" (75 mm) inner dia.	Each	119.40	342.20
	ii) 4" (100 mm) inner dia.	Each	119.40	461.60
	iii) 5" (125 mm) inner dia.	Each	199.00	963.95
	iv) 6" (150 mm) inner dia.	Each	199.00	1440.35
	v) 8" (200 mm) inner dia.	Each	318.40	2197.20
	vi) 10" (250 mm) inner dia.	Each	318.40	2908.45
	vii) 12" (300 mm) inner dia.	Each	477.65	5237.70
	viii) 14" (350 mm) inner dia.	Each	477.65	10370.85
	b) Class D			
	i) 1.25" (30 mm) inner dia.	Each	79.60	173.55
	ii) 1.5" (40 mm) inner dia.	Each	79.60	280.90
	iii) 2" (50 mm) inner dia.	Each	119.40	354.25
	iv) 3" (75 mm) inner dia.	Each	119.40	488.45

Sr. No.	Description	Unit	Rate (Rs.)	
			Labour	Composite
v)	4" (100 mm) inner dia.	Each	199.00	836.45
vi)	5" (125 mm) inner dia.	Each	199.00	1726.20
vii)	6" (150 mm) inner dia.	Each	238.80	2705.40
27-41	Add extra for respective payable item of ground floor			
a)	For first floor	% Increase		10%
b)	For every additional floor above first floor	% Increase		7.5%

