Sr. No.	Description	Unit	Rate	e (Rs.)	Ref. Tech.
31. NO.	Description	Offic	Labour	Composite	Specs.
23-1	Providing and fixing European type glazed earthenware water closet ICL Boch/Forte or approved equivalent make including cost of inlet pipe, lid cistern kit, stop cock deluxe and other accessories, fitting material such as brackets, PVC down pipe where required, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.				232.5.4 (a)
a)	Water closet floride coupled/4030				
i)	White	Each	956.25	8,547.65	
ii)	Coloured	Each	956.25	8,443.15	
b)	W.C. fregate coupled/4006				
i)	White	Each	956.25	6,805.65	
ii)		Each	956.25	7,736.90	
c) i)	W.C. non-coupled 7HU White	Each	956.25	6,668.15	
ii)	Coloured AMMU & KASHIM	Each	956.25	7,118.15	
23-2 a)	Providing and fixing squatting type water closet with integral treads ICL Boch/Karam Cera or approved equivalent make including cost of inlet pipe cistern and lid cistern kit, stop cock deluxe type and other accessories, fittings, brackets, PVC down pipe, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material. W.C. Indian/Desi/902 with glazed earthen ware 4" (100 mm) trap				23.2.5.4
i)	White	Each	900.00	5,924.40	
ii)	Coloured	Each	900.00	6,009.75	
b)	W.C. Orisa/Asian/900 with glazed earthen ware 4" (100 mm) trap				
i)		Each	900.00	5,578.50	
ii)	Coloured	Each	900.00	6,791.00	
23-3 i)	Providing and fixing European type glazed earthenware water closet ICL Ifo/Forte or approved equivalent make including cost of inlet pipe, lid cistern kit, stop cock deluxe and other accessories, fitting material such as brackets, PVC down pipe where required, rubber rings/washers, making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material.	Each	900.00	8,037.65	23.2.5.4

Sr. No.	Description	Unit	it		Ref. Tech.
31. NO.	Description	Offic	Labour	Composite	Specs.
ii)	Coloured	Each	900.00	8,312.65	
23-4	Providing and fixing export quality ICL Boch/Karam Cera or equivalent make flat back lipped front urinal basin or glazed earthen ware with and including the cost of 1 gallon (4.5 lit) C.I automatic flushing cistern with fittings a pet cock C.I. or W.I. brackets standard flush pipe with fittings, standard waste pipe (enamelled iron) connection and making good with approved material. Urinal 6003				23.2.5.7
i)	White	Each	675.00	6,746.25	
ii)	Coloured	Each	675.00	6,871.25	
a) ii) 23-5 a) ii) b) ii) c) ii) ii)	Providing and fixing export quality glazed earthen ware wash basin manufactured by ICL Boch/Karam Cera or equivalent approved make with single hole chromium plated mixer tap 1/2" (15mm), pillar tap one way delux, stop cocks, C.I. or W.I. brackets 6" (150mm) built into walls 1.5" (40mm) C.P. brass waste with malleable iron or C.P. brass trap with malleable iron or brass union and making requisite number of holes in walls, plinth and floor for pipe connections and making good with approved material. Wash basin 18" (450 mm) without pedestal White Coloured Wash basin 24" (610 mm) Futura without pedestal White Coloured Wash basin 26" (650 mm) without pedestal White	Each Each Each Each Each Each	675.00 675.00 675.00 675.00 675.00 675.00 675.00	6,621.25 6,621.25 11,394.40 11,619.40 12,144.40 12,269.40 12,519.40 12,394.40	23.2.5.1
i)	·	Each	140.65	470.65	
ii)		Each	140.65	513.55	

Sr. No	^	Description	Unit	Rate	e (Rs.)	Ref. Tech.
31. N	<u>. </u>	Description	Offic	Labour	Composite	Specs.
23-6		Providing and fixing English or approved equivalent bath tub of desired colour with and including the cost of 1.5" dia. C.P. brass waste, 1.25" dia. brass overflow, (3/4") size C.P. brass pillar taps, C.P. brass chain with rubber plug and making required number of holes in walls plinth and floor for pipe connections and making good with approved material.				23.2.5.9
	a)	Porcelain enamelled cast iron bath tub 66" x 28" x	Each	2,250.00	30,419.40	
	b)	Fibre glass bath tub 72" x 28" x 23"	Each	2,250.00	26,669.40	
23-7		Providing and fixing ICL /Karam cera or approved equivalent make glazed earthen ware shower tray including fittings, bib cok, stop cock, shower kit, trap and making requisite numbers of holes and making good with approved material.	Each	900.00	5,255.35	
23-8		Providing and fixing stainless steel sink Pakistan made with C.I. or W.I brackets 6" built in wall, 1.5" (40 mm) rubber plug, C.P. brass chain, C.P. brass waste, pillar tap 2 way delux, 1.5" dia malleable iron or C.P. brass trap and unions and making requisite number of holes in walls, plinth and floor for pipe connections and making good with approved material.				23.2.5.3
	a)	Stainless steel sink 40" x 20" (1000 mm x 500 mm)	Each	900.00	6,056.25	
	b)	Stainless steel sink 33" x 18" (825 mm x 450 mm)	Each	900.00	5,556.25	
23-9		Providing and fixing floor trap of approved self cleaning design with screwed down grating with or without a vent arm with and including making requisite number of holes in walls, plinth and floor for pipe connection and making good with				23.2.4.1
	a)	C.I. floor trap 6" x 2" and 6" x 3" size with grating.	Each	225.00	1,475.00	
	b)	C.I. floor trap 4" dia. inlet and outlet with C.I. grating.	Each	225.00	1,725.00	
	c)	C.I. floor trap 6" x 2" size with grating including concrete chamber all round	Each	225.00	1,775.00	
	d)	C.I. floor trap 6" x 4" size with grating including concrete chamber all round	Each	225.00	2,085.00	
23-10		Providing and fixing white glazed earthen ware export quality bidet with fittings in bath room.	Each	675.00	16,875.00	23.2.5.5
23-11		Providing and fixing standing shower concealed in wall with approved quality control valves, mixer unit	Each	900.00	12,900.00	23.2.5.8
23-12		Providing and fixing C.P. brass telephonic shower including holder clamps, screw and bib cock.	Each	168.75	3,993.75	23.2.5.8
23-13		Providing and fixing approved quality chromium plated towel rail with bracket and screws.				
		l l			l l	

Sr. No		Description Unit Rate (e (Rs.)	Ref. Tech.	
31. NO	•	Description	Offic	Labour	Composite	Specs.
	a)	Towel rail 24" x 3/4" (600mm x 20mm)	Each	45.00	2,677.85	
	b)	Towel rail 30" x 3/4" (750mm x 20mm)	Each	45.00	4,324.91	
23-14		Providing and fixing approved quality C.P. brass toilet paper holder Master /Sonex or equivalent make.	Each	112.50	1,066.81	23.2.5.11
23-15		Providing and fixing looking mirror of Belgium/ Malaysian/ Indonesian glass with chromium plated	Sq.m. Sq.ft.	225.00 20.90	1,068.75 99.35	23.2.5.2
23-16		Providing and fixing shelf of standard size.				23.2.5.13
	a)	Glass shelf of 24" x 5" size with guard rails & C.P.	Each	56.25	2,306.25	
	b)	Shelf (Master/Sonex make)	Each	56.25	2,306.25	
23-17		Providing and fixing white glazed vitreous China squatting type W.C. pan with integral treads similar to Orissa type.				23.2.5.4
	a)	/ * N E 1 1 1 1 1 1 1 1 1	Each	450.00	2,443.75	
	b)	With vitreous China trap	Each	450.00	2,608.75	
23-18	a)	Providing and fixing approved quality fixtures European type White glazed earthen ware W.C.	Each	450.00	2,375.00	23.2.5.4
	b)	Providing and fixing plastic flushing cistern of approved quality and colour.	Each	450.00	2,102.50	
	c)	Wash basin 18" (450 mm), White colour	Each	450.00	2,100.00	
	d)	Wash basin 24" (610 mm) ICL Futura make	Each	450.00	2,850.00	
23-19	- \	Providing and fixing ICL (Boch) or Karam Cera export quality glazed earthen ware cistern with lid and kit.	E	005.00	0.450.00	23.2.5.4
	a)	White	Each	225.00	2,153.90	
	b)	Coloured	Each	225.00	2,468.90	
23-20		Providing and fixing approved qualty of Bacolite	Each	56.25	578.75	23.2.5.4
23-21		Providing and fixing glazed pottery/C.P. brass pull.	Each	56.25	181.25	23.2.5.1(d)
23-22		Providing and fixing rubber connection for flush pipe	Each	56.25	175.65	23.2.5.4
23-23		Providing and fixing approved quality white glazed earthenware lavatory basin with 1/2" (15 mm) dia. single hole C.P. mixer tap, 2 way deluxe pillar tap, stop cocks, 6" C.I. or W.I. brackets built into walls, rubber plug, C.P. brass chain, C.P. brass waste, malleable iron or C.P. brass bottle trap with malleable iron or brass union and making requisite number of holes in walls, plinth and floor for pipe connection and making good with approved material. Lavatory basin 22" x 16" (550 mm x 400 mm)	Each	675.00	15,144.40	23.2.5.1
	b)	Lavatory basin 25" x 18" (625 mm x 450 mm)	Each	675.00	17,144.40	
	IJ)	Lavatory basin 20 × 10 (020 mill × 400 mill)	Lauli	073.00	17,144.40	

Sr. No.	Description	Unit		e (Rs.)	Ref. Tech.
	Description	Jint	Labour	Composite	Specs.
23-24	Providing and fixing approved quality glazed fire clay sink 24" x 18" with 6" (150mm) size C.I. or W.I. brackets built in walls, 1.5" (40 mm) rubber plug and C.P. brass chain, C.P. brass waste, pillar tap 2 way deluxe, malleable iron or C.P. brass trap and unions and making requisite numbers of holes in walls, plinth and floor for pipe connections and making good with approved material.	Each	900.00	7,056.25	23.2.5.3
23-25	Providfing and fixing C.P. chain for sink and lavatory	Each	45.00	107.50	23.2.5.1
23-26	Providing and fixing rubber plug for sink and lavatory	Each	45.00	65.65	
23-27	Providing and fixing glazed earthen ware foot rest.	Each	112.50	281.25	
23-28 a)		Each	225.00	1,568.75	23.5.2.4
b)		Each	225.00	2,225.00	
23-29 a)	Providing and fixing soap dish. Chromium plated	Each	45.00	945.00	23.2.5.11
b)	Glazed earthen ware	Each	45.00	1,185.00	
23-30	Providing and fitting superior quality plastic accessories of approved make	Foob	45.00	202.50	23.2.5.11
a)	· ·	Each	45.00	382.50	
b)		Each	45.00	357.50	
C)		Each	45.00	295.00	
d)		Each	45.00	245.00	22.2.5.40
23-31	Providing and fixing C.P. pillar-cock of superior quality of approved make.				23.2.5.10
a)	1/2" (12 mm) dia.	Each	45.00	1,081.90	
b)	3/4" (20 mm) dia.	Each	45.00	1,227.00	
23-32	Providing and fixing C.P. stop-cock of superior quality of approved make.				23.2.5.10
a)		Each	45.00	1,121.10	
b)	3/4" (20 mm) dia.	Each	45.00	1,431.45	
23-33	Providing and fixing undergound stop-cock with superior quality C.P. cover of approved make.				23.2.5.10
a)	1/2" (12 mm) dia.	Each	45.00	1,207.14	
b)	3/4" (20 mm) dia.	Each	45.00	1,507.79	

Sr. No) .	Description	Unit		e (Rs.)	Ref. Tech.
51.140	<i>-</i> -	Description	O i iii	Labour	Composite	Specs.
23-34		Providing and fixing superior quality C.P. bib cock of approved make.				23.2.5.10
	a)	1/2" (12 mm) dia.	Each	45.00	1,200.00	
	b)	3/4" (20 mm) dia.	Each	45.00	1,347.06	
23-35		Providing and fixing superior quality 1/2" size C.P. tee stop cock of approved make.	Each	45.00	541.24	23.2.6.3
23-36		Providing and fixing C.P. brass shower				23.2.5.8
	a)	1/2" (12 mm) dia inlet and 6" (150 mm) dia.	Each	45.00	789.27	
	b)	1/2" (12 mm) dia inlet and 4" (100 mm) dia.	Each	45.00	646.83	
23-37		Providing and fixing 1/2" (12 mm) single hole superior quality C.P. mixer of approved make for wash hand basin. sink or shower.	Each	225.00	3,975.00	23.2.5.1(e)
23-38		Providing and fixing 1" (25 mm) superior quality C.P. flushing valve of approved make for wash hand basin, sink or shower.	Each	225.00	4,131.25	23.3.4.2
23-39		Providing and fixing superior quality gun-metal peet/gate valve (Class150) of approved make.				27.3.1.2
	a) i)	Screwed ends 1/2" (12 mm) dia.	Each	77.59	256.25	
	ii)		Each	77.59	290.10	
	iii)	1" (25 mm) dia.	Each	168.75	359.34	
	iv)		Each	168.75	409.48	
	v)		Each	325.86	490.97	
		2" (50 mm) dia.	Each	325.86	684.59	
	vii	2.5" (65 mm) dia.	Each	543.10	1,469.83	
	viii	3" (75 mm) dia.	Each	543.10	1,753.86	
	ix)	4" (100 mm) dia.	Each	775.86	2,413.79	
	x)		Each	775.86	2,517.83	
	b) i)	Flanged ends 1/2" (12 mm) dia.	Each	232.76	481.25	
	ii)	3/4" (20 mm) dia.	Each	232.76	585.32	
	iii)	1" (25 mm) dia.	Each	465.52	975.00	
	iv)	1.25" (30 mm) dia.	Each	465.52	1,389.18	
	v)	1.5" (40 mm) dia.	Each	600.00	1,493.75	

Sr. No		Description	Unit	Rate	(Rs.)	Ref. Tech.
31. NO	,	Description	Ollit	Labour	Composite	Specs.
	vi)	2" (50 mm) dia.	Each	600.00	1,706.25	
	vii	2.5" (65 mm) dia.	Each	800.00	1,876.87	
,	viii	3" (75 mm) dia.	Each	800.00	2,196.08	
	ix)	4" (100 mm) dia.	Each	900.00	2,373.53	
	x)	6" (150 mm) dia.	Each	900.00	2,584.82	
23-40		Providing and fitting superior quality C.P. or brass oxidised 1/2" (12mm) swan neck pillar cock (tap) of approved make.				23.2.5.10
	a)	Single way	Each	77.59	2,164.20	23.2.5.3 (e)
	b)	Double way	Each	168.75	2,550.00	
23-41		Providing and fixing brass bib cock/ stop cock of approved make.				23.2.5.10
	a)	Ex This	Each	56.25	218.75	23.2.5.10
	b)	3/4" (20 mm) dia.	Each	56.25	243.75	
	c)	1" (25 mm) dia.	Each	56.25	418.75	
23-42		Providing and fixing 'P' trap including concrete chamber and C.I. grating. Cast iron 4" (100 mm) size	Each	225.00	2,178.15	23.2.5.4
	b)	Glazed 4" (100 mm) size	Each	225.00	490.50	
23-43		Providing and fixing C.I. gully trap 6"x6"x4" including concrete embedment and cost of G.I. grating 6"x6" and masonry chamber 12"x12"	Each	56.25	1,790.65	23.2.4.2
23-44		Providing, laying, cutting, jointing, testing and disinfecting cast iron soil pipe with spigot, socket chaulked lead or comet joint or flanged joints/tyton joints including cost of jointing material such as lead, comet and yarn.				23.2.3.1 23.2.6.4
	a)	2" (50 mm) dia.	R.M. R.ft.	69.00 21.05	1,790.25 545.65	
	b)	3" (75 mm) dia.	R.M. R.ft.	69.00 21.05	2,650.90 808.00	
	c)	4" (100 mm) dia.	R.M. R.ft.	69.00 21.05	3,511.50 1,070.30	

Sr. No	_	Description	Unit	Rate	e (Rs.)	Ref. Tech.
or. No	υ.	Description	Unit	Labour	Composite	Specs.
23-45		Providing and laying Asbestos cement building and sanitary pipe with cement chaulked or comet joint including cost of sockets, bends and specials.				23.2.3.4
	a)	2.5" (65 mm) inner dia.	R.M. R.ft.	168.75 51.45	564.00 171.90	
	b)	3" (75 mm) inner dia.	R.M. R.ft.	168.75 51.45	808.60 246.45	
	c)	4" (100 mm) inner dia.	R.M. R.ft.	337.50 102.85	1,216.00 370.65	
	d)	6" (150 mm) inner dia.	R.M. R.ft.	337.50 102.85	1,717.05 523.35	
23-46		Providing and fixing C.I. specials such as bend, tees, collars, cross, reducers, tail pieces, flanged spigots, cap, flanged socket, taper, angle bends and plugs including turning threading, facing and fitting for C.I. pipe line.				23.2.3.1 23.2.6
	a)	Cast iron S.S. specials with spigot and socket joint				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	69.00 31.30	279.10 126.60	
	ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg. Lb.	51.75 23.45	273.45 124.05	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	34.50 15.65	266.55 120.90	
	b)	Cast iron flanged specials with flanged joints				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	34.50 15.65	275.55 125.00	
	ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg. Lb.	26.50 12.00	271.40 123.10	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	17.25 7.80	264.75 120.10	
	c)	Cast iron specials with tyton joints				
	i)	3" to 6" (75 mm to 150 mm) dia.	Kg. Lb.	17.25 7.80	271.65 123.20	
	ii)	8" to 12" (200 mm to 300 mm) inner dia.	Kg. Lb.	17.25 7.80	266.85 121.05	
	iii)	15" to 18" (375 mm to 450 mm) inner dia.	Kg. Lb.	17.25 7.80	259.85 117.85	
23-47	a)	Supplying and fitting C.I. manhole cover with frame weighing not less than 10.25 lbs/sq.ft (50 kg per sq.m.). 12" (300 mm.) dia.	Each	616.50	1,469.50	23.2.7, 25.4.2

Sr. N	ο.	Description	Unit		e (Rs.)	Ref. Tech.
- OI. IN	0.	Безсприон	Oilit	Labour	Composite	Specs.
	b)	18" (450 mm.) dia.	Each	616.50	1,583.05	
	c)	24" (600 mm.) dia.	Each	615.94	1,863.06	
	d)	12" (300 mm.) square	Each	761.11	2,098.81	
	e)	18" (450 mm.) square	Each	761.11	2,209.00	
	f)	24" (600 mm.) square	Each	761.11	2,509.64	
23-48		Providing and fitting C.P. or oxidised gas cock 1/4" (6 mm) dia.				23.3.5.1
	a)	Single way	Each	281.25	285.15	20.0.0.1
	b)	Double way	Each	281.25	433.72	
	c)	Three way	Each	281.25	744.05	
23-49		Providing and fitting nipple or bush 1/4" x 3/8" (6mm - 10mm) inner dia.	Each	45.00	82.50	23.3.5.1
23-50		Providing and fitting union/socket				23.3.5.1
	i)	1/2" (15 mm) inner dia.	Each	45.00	750.00	
	ii)	3/4" (20 mm) inner dia.	Each	45.00	915.00	
	iii)	1" (25 mm) inner dia.	Each	45.00	1,125.00	
23-51	a)	Providing and fixing brass gas cock. 1/2" (15 mm) inner dia.	Each	45.00	461.54	23.3.5.1
	a) b)	3/4" (20 mm) inner dia.	Each	45.00	481.58	
22.50	D)		Eduli	45.00	401.30	23.3.3
23-52		Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe with approved make/brand gas line including the cost of jointing material.				23.3.3
	a)	Light duty				
	i)	1/2" (15 mm) inner dia.	R.M. R.ft.	93.00 28.35	575.44 175.40	
	ii)	3/4" (20 mm) inner dia.	R.M. R.ft.	93.00 28.35	745.94 227.35	
	iii)	1" (25 mm) inner dia.	R.M. R.ft.	106.65 32.50	1,009.61 307.75	
	iv)	1.25" (30 mm) inner dia.	R.M. R.ft.	106.65 32.50	1,253.74 382.15	
	v)	1.5" (40 mm) inner dia.	R.M. R.ft.	126.40 38.55	1,574.15 479.80	
	vi)	2" (50 mm) inner dia.	R.M. R.ft.	126.40 38.55	1,917.11 584.35	

Sr. No.	Description	Unit Rate (Rs.)		Ref. Tech.	
31. NO.	Description	Unit	Labour	Composite	Specs.
23-53	Providing and fixing superior quality C.P. check valve of approved make for water supply or gas lines.				23.2.6.4 23.2.3
a)	1/2" (12 mm) dia.	Each	56.25	2,056.25	
b)	3/4" (20 mm) dia.	Each	56.25	2,681.25	
c)	1" (25 mm) dia.	Each	77.59	3,077.60	
d)	1.25" (30 mm) dia.	Each	168.75	4,543.75	
e)	1.5" (40 mm) dia.	Each	225.00	5,975.00	
f)	2" (50 mm) dia.	Each	337.50	9,087.50	
23-54	Providing and fixing C.P. waste coupling.				00 0 = 0()
a)	1.25" (30 mm) dia.	Each	45.00	146.63	23.2.5.3(e)
b)	1.5" (40 mm) dia.	Each	45.00	204.58	
23-55 a)	Providing and fixing C.P chain with rubber plug. 1.25" (30 mm) dia.	Each	45.00	253.75	23.2.5.3(d)
b)	Assessed KASHA	Each	45.00	350.40	
23-56	Providing and fixing P.V.C. waste pipe		.0.00	000110	
a)	1.25" (30 mm) dia.	Each	45.00	220.19	23.2.5.3(f)
b)	1.5" (40 mm) dia.	Each	45.00	336.27	
23-57	Providing and fixing P.V.C. waste flushing bend				00.0.0.0
a)	1.25" (30 mm) dia.	Each	45.00	77.00	23.3.6.3
b)	1.5" (40 mm) dia.	Each	45.00	106.86	
23-58	Providing and fixing angle iron brackets for wash	Each	56.25	256.25	23.2.5.7
	hand basin, cistern and sinks.				23.5.3
23-59	Providing and fixing 1/2" (12 mm) dia. connection pipe including check nuts.				23.2.6
a)	Plastic rubber connection pipe	Each	45.00	130.65	
b)	Copper connection pipe	Each	45.00	437.50	
23-60	Providing and fixing brass ball valve with unsoldered copper ball.				
a)	1/2" (12 mm) dia.	Each	56.25	143.75	23.3.4.2
b)	3/4" (20 mm) dia.	Each	56.25	200.00	
c)	1" (25 mm) dia.	Each	77.59	243.75	
d)	1.25" (30 mm) dia.	Each	168.75	406.25	

Sr. No.	Description	Unit		e (Rs.)	Ref. Tech.
	Bescription	Onic	Labour	Composite	Specs.
e)	1.5" (40 mm) dia.	Each	225.00	531.25	
f)	2" (50 mm) dia.	Each	337.50	937.50	
23-61	Providing chambers 9" x 6" x 24" for stop cocks and valves etc. with 4-1/2" (115mm) thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:4:8 in foundation, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, 1" thick concrete 1:2:4 flooring complete with C.I. hinged cover and frame 9" x 6" weighing 6.35 kg fixed in 1:2:4 concrete including curing, excavation, back filling and disposal of earth.	Each	407.05	2,875.90	23.3.14.2
23-62	Providing chambers 15" x 9" x 24" for house meters with 4-1/2" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:4:8 in foundation, 1/2" thick plaster in 1.3 cement sand mortar to all inner wall surfaces, 1" thick concrete 1:2:4 flooring complete with cast iron hinged cover and frame 15" x 9" weighing 12.7 kg fixed in 1:2:4 concrete including curing, excavation, back filling and disposal of earth.		558.05	4,630.25	5.3 11.4.1 11.7.2(ii) 11.7.4
23-63 a)	Providing chambers 30" x 18" x 56" as per approved design for sluice valve 3" to 12" dia. with 18" dia. C.l. cover and frame weighing 88.9 Kg. fixed in 4" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing anf fixing C.l. foot rest at every 12" beyond 30" depth including curing, excavation, back filling and disposal of surplus earth.		2,926.70	35,263.40	5.3 11.4.1 11.7.2(ii) 11.7.4
b)	Extra for depth beyond 54" (1.37m) including cost of C.I.foot rest for every 12"(300mm) depth (for depth less than 54" (1.37m) deduct at the same rate).		16.10	190.10	
23-64 a)	Providing chambers 42" x 42" x 7'-0" as per approved design for sluice valve 15" to 24" dia. with 24" dia. C.l. cover and frame weighing 127 Kg. fixed in 6" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing & fixing C.I foot rest at every 12" beyond 30" depth including curing, excavation, back filling and disposal of surplus earth.		6,617.50	74,453.30	5.3 11.4.1 11.7.2(ii) 11.7.4

Sr. No	_	Description	Unit	Rate	e (Rs.)	Ref. Tech.
31.140	0.	Description	Onit	Labour	Composite	Specs.
	b)	Extra for depth beyond 7 ft.(2.14 m) including cost of C.I. foot rest for every 12" (300mm) depth (for depth less than 7 ft (2.14 m) deduct at the same rate).		24.50	226.20	
23-65	a)	Providing chambers 45" x 42" x 8'-0" as per approved design for sluice valve 27" to 30" dia. with 30" dia. C.I. cover and frame weighing 190.5 Kg. fixed in 6" thick R.C.C. 1:2:4 slab with re-steel 5 lbs./cu.ft and 9" thick burnt brick masonry walls in 1:6 cement sand mortar, 6" thick cement concrete 1:3:6 in foundation, 1" thick concrete 1:2:4 flooring, 1/2" thick plaster in 1:3 cement sand mortar to all inner wall surfaces, including providing anf fixing C.I. foot rest at every 12"		9,290.70	95,892.75	5.3 11.4.1 11.7.2(ii) 11.7.4
	b)	beyond 30" depth including curing, excavation, back filling and disposal of surplus earth. Extra for depth beyond 8 ft (2.44 m) including cost of C.I. foot rest for every 12" (300mm) depth (for depth less than 8 ft (2.44 m) deduct at the same rate).	Each	25.20	232.65	
23-66		Supply and fix gas items including all accessories and fittings such as G.I pipe, rubber pipe, specials, gas stop cocks etc.				23.3
	a)	Gyser 35 gallons capacity	Each	1,350.00	13,621.90	
	b)	Gyser 50 gallons capacity	Each	1,350.00	15,131.25	
	c)	Gas room heater (ordinary, single burner)	Each	900.00	1,621.90	
	d)	Gas room heater (ordinary, double burner)	Each	900.00	2,081.25	
	e)	Gas room heater (fancy, single burner)	Each	900.00	5,493.75	
	f)	Gas room heater (fancy, Double burner)	Each	900.00	8,118.75	
	g)	Gas room heater (fire place design with artificial log or coal, double burner)	Each	1,350.00	8,568.75	
	h)	Gas lamp (single)	Each	675.00	1,331.25	
	i)	Gas lamp (double)	Each	675.00	1,987.50	
23-67		Providing and connecting PVC/ Rubber pipe for gas	Per Point	60.00	220.65	23.3
23-68	a)	Add extra for respective payable item of ground floor For first floor	% Increase	0.10	0.10	23.3
	b)	For every additional floor above first floor	% Increase	0.08	0.08	